

OTR #76065-76066



Quote Date: 2018-01-05 REVISED
 Quote Expires: 2018-02-02
 Quote Number: 30353
 Reference ONLY: 29249
 Company Quoting: Ocean Traller - Pete
 Don Aleksejus
 Fontaine Trailer Company
 430 Letson Road
 Haleyville, AL 35565
 daleksejus@fontainetrailer.net

QUOTE

Revolution 60 Alum Flat 53' Tridem Air (Model: HBR6022TAF)	
Qty. 1-4 *CUSTOMER NEEDS ASAP	Est. Wt.: 12,269#
Length / Width: 53 feet x 102 inches	
Suspension Type: Fixed tridem air ride	
Frame Rating: 100,000 lbs. distributed - GAWR and tire ratings determine legal payloads	
Flooring: Knurled extruded 3-1/8 aluminum, multi-hollow friction stir welded floor with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear	
Side Rails: Exclusive Revolution Technology - one piece routed aluminum designed for strength and impact	
Stationary Chain Cargo Tie Downs: *None installed	
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)	
Rubrail: Integrated with side rail	
Main Beams: Extruded aluminum - 12 inch flange	
Kingpin: 18 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: Jost AX100G19 ALUMILIGHT with forward & rear bracing	
Bulkheads: None standard	
Number of Axles: 3	
Axle Spindle: Parallel (Straight)	
Brakes: Hendrickson MAXX 22T air disc; Aluminum air tank; Dust Shields	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 72 inches, 72 inches - Axles set ahead to approximately 40'6" C/L KP to C/L Tridem; Rear axle approximately 60" C/L to rear of trailer	
Hub and Drums: 10-hole hub-piloted with Rotors	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty *** (HXL5)	
Wheels: (12) 22.5 x 8.25 aluminum LVL One buffed wheels	
Tires: (12) 11R 22.5 14PR Yokohama RY023	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson Intraax air ride Fixed Tridem: AANT23K on center axle, AANL23K on front and rear liftable axles for additional tire ground clearance	
Auto Glad Hand Dump: *Not Installed	
Electric Dump Valve: *Not Installed	
Manual Dump Valve: Installed inside box with liquid filled gauge: located road side behind landing gear	
Air Lift: (2) UBL type installed: (1) on front axle, (1) on rear axle; Both axles controlled by one ILAS weight sensing lift control	
Front Corners: Tapered	
Electrical System: Exclusive Revolution Technology: LED: 5 lights/side, 3 rear recessed light bars, with 10 Year Comprehensive Electrical System Warranty	
Other Electrical Specifications: (3) 4 way sockets with one hot/one ground pin for wide load and strobe light connections: 1 ea. side near rear and one on rear	
Paint: Black urethane on steel parts with Revolution decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Meets underride requirements	
Mudflaps: 1 set OEM standard behind rear axle	
Spare Tire Carrier: None standard	
Winch Track: Dual full-length integrated aluminum - double L design	
Sliding Tie Downs: (26) Installed opposite winches	
Sliding Winches: (26) 3-bar type: 13 ea. side with (26) sliding Rope Hook/Winch Strap Hook Retainers; Welded aluminum hooks front and rear	
Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Tite Seal installed	

Tool Box: 1 aluminum double door box - 24 inches x 24 inches x 60 inches - installed road side side near landing gear; Includes 4 sliding securement devices and 4 chocks

Dunnage Rack: Fontaine Select to install (1) 120" Aluminum Fontaine

Wide Load Lights: Install 2 aluminum pull-out lights: 1 ea. side near rear

Strobe Lights: Toggle Switch, harness, and mounting brackets installed between rear bumper risers - *(2) lights not installed but shipped loose

VIN Plate: Bilingual US/Canadian VIN plate

Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not available

Price Each FOB Haleyville, AL (*Special Pricing)

Grand Total (Total price for 4 units)