



4400 So Lowls Blvd
 PO Box 6300
 SIOUX CITY, IA 51106

Phone: 712-252-6500
 Fax: 712-252-6510

Dealer's customer info.: PO 88596 combo tandem step

OCEAN TRAILER (WPG) - (PTS/TRL)
 415 LUCAS AVE
 BOX 58, GROUP 200, RR#2
 WINNIPEG, MB R3C 2E6
 CAN

Pblite Revision: 2

PO# 88596 - 88598



Description	Quantity	Price
1) MODEL CD-1080		
2) TRAILER BUILT FOR EXPORT TO CANADA		
3) --INSTALL CANADIAN AND USA VIN PLATES		
4) 2023 PRODUCTION		
5) 2023 FLATBED PRICING IS SUBJECT TO ADJUSTMENT UP TO NINETY (90) DAYS BEFORE PRODUCTION OF YOUR ORDER		
6) 2023 FLATBED PRICING: (90) DAYS FROM THE START OF PRODUCTION YOU WILL RECEIVE NOTICE IF PRICING ADJUSTMENT IS REQUIRED		
7) 2023 FLATBED PRICING: CUSTOMER HAS THE RIGHT TO ACCEPT THE ADJUSTMENT OR CANCEL THE ORDER		
8) LENGTH 53 FT		
9) WIDTH 102"		
10) FIFTH WHEEL HEIGHT 48" (STD)		
11) KING PIN 24"		
12) KING PIN CORSOL PAINTED (STD)		
13) 10-3/4" KING PIN BEAM DEPTH (STD)		
14) STANDARD KING PIN		
15) JOST UL550 ULTRALIGHT LANDING GEAR W/ CUSHION FOOT (STD)		
16) 11' TOP DECK LENGTH (STD)		
17) REAR DECK HEIGHT 39-1/2" (22.5 TIRES) (STD)		
18) FRONT DROP - 21" (STD)		
19) GN SLOPE - SQUARE (STD)		
20) SUSPENSION SETTING - (TAC LEGAL) MAXIMUM DISTANCE		
21) FRICTION SLIDER (AA250L INTRAAX) FRONT AXLE SLIDE TANDEM		
22) MANUAL SUSPENSION DUMP (STD)		
23) HENDRICKSON HEIGHT CONTROL VALVE (STD)		
24) HENDRICKSON TIREMAAX PRO TIRE INFLATION SYSTEM TANDEM		
25) AIR GAUGE FOR AIR RIDE (100 PSI) W/MANUAL DUMP IN SEALED METAL BOX W/LATCH		
<i>Mounted by landing gear with slider valve in box</i>		
26) ABS BENDIX (EATON) 4S/2M		
27) INTRAAX EXTENDED SERVICE BRAKES (PER AXLE) (STD)	(2)	
28) TAPERED SPINDLE W/ TN BEARINGS (PER AXLE) (STD)	(2)	

- 29) OIL LUBE (STD) (2)
- 30) STEMCO GUARDIAN SEAL (#3070743) (STD) (2)
- 31) STEMCO ALUMINUM HUBCAP (STD) (2)
- 32) AXILOCK SPINDLE NUT (STD) (2)
- 33) DUST SHIELDS - STEEL (PER AXLE) (2)
- 34) DURALITE HUBS/CAST DRUMS (PER AXLE) (STD) (2)
- 35) WABCO BRAKE CHAMBER (STD) (2)
- 36) HALDEX AUTO SLACK ADJUSTERS (STD) (PER AXLE) (2)
- 37) TRAMEC SPRING BRAKE VALVE (STD) (2)
- 38) MUDFLAPS- BLACK RUBBER WTC FOR FRONT AXLE
- 39) MUDFLAPS- BLACK RUBBER WTC FOR SET AHEAD REAR AXLE
- 40) WHEEL ALUM (HP) ALCOA ULTRA ONE 10HOLE 8.25X22.5 (PER EA) (8)
- 41) ROADMASTER RM272 255/70R 22.5 LR-H (PER EA) * (8)
- 42) ***TIRES ARE SUBJECT TO AVAILABILITY, IF A SUBSITUTE TIRE MUST BE USED THE SALE PRICE WILL BE ADJUSTED ACCORDINGLY***
- 43) PLASTIC LINER (SET OF 8) BETWEEN HUB/WHEEL & WHEEL
- 44) FLOOR ALUM 1-3/8 (4) NAILERS (PER FT) (53)
- 45) 18" X-BAR SPACING 4-1/2" ALUM (MAIN BED) (STD) (42)
- 46) C+ STYLE SIDE RAIL 6-1/4" PKTS ON 24" CTRS/SGL SPOOL/RUB BAR
- 47) KNEE BRACES (STD)
- 48) BUMPER WITH ALUMINUM R.I.G. (STD)
- 49) FRONT CORNER POCKETS TURNED TO SIDE (STD)
- 50) FRONT STAKE POCKETS (PER EA) (2)
- 51) GLADHANDS & 7-WAY CONNECTIONS AT FRONT (STD)
- 52) GROTE LED MICRO NOVA CLEARANCE LIGHTS
- 53) RECESSED IN GROTE RUBBER GROMMET
- 54) PACKAGE B - 4 EXTRA (ROW OF 5)
- 55) SPACE LIGHTS EQUALLY - GIVE PRIORITY TO WINCH STRAP CLEARANCE
- 56) GROTE LED CENTER TURN SURFACE MOUNT (STD)
- 57) GROTE LED 4" ROUND TAIL LIGHTS CLUSTER OF 3 (GROMMET) (STD)
- 58) 2 GROTE 4" AMBER STROBE ON INSIDE POSITION OF CLUSTER OF 3 W/SS FLANGE (SNAP-IN)
With on/off switch in box with air gauge.
- 59) WIDE LOAD TELESCOPING LIGHTS 2 SETS OF 2 W/SWITCH IN DUMP BOX
- 60) QUICK TIE PLATE STORAGE BRACKET(HOLDS 16)
- 61) QUICK TIE PLATE STORAGE BRACKET LOCATION - SPECIFY LOCATION
Locate by landing gear on D/S
- 62) QUICK TIE PLATE (PER EA) (16)
- 63) QUICK TIE PLATE STORAGE BRACKET LOCATION - SPECIFY LOCATION
- 64) KINEDYNE WINCH FIXED LO-PRO 3-BAR WITH CLAW HOOK KYN14001 (PER EA) (26)
- 65) PERMANENT WINCH LOCATION - DS/CS STAGGERED SPACED EVENLY
Locate 5 on upper deck staggered, spaced evenly starting on DS, balance on bottom deck, staggered spaced approx even.
- 66) AERO TOOL BOX 24D X 20H X 60L CAM LOCKS W/ 2 POLISHED DOORS (2)
- 67) TOOL BOX LOCATION - AT DROP DS & CS
- 68) MOUNT AS HIGH AND CLOSE TO BEAM AS POSSIBLE
- 69) DUNNAGE RACK: 10FT LONG X 8IN TALL OUTSIDE BEAMS X-BAR MOUNT WITH .184 PUNCHED OVAL FLOOR PAN
- 70) DUNNAGE STORAGE LOCATION - AHEAD OF FRONT AXLE CS
- 71) PAINT WITH FLAT BLACK CORSOL ONLY (STD)
- 72) INSTALL CONSPICUITY TAPE ON RUB BAR (STD)
- 73) INSTALL DECALS AT STANDARD LOCATIONS
- 74) REGISTRATION HOLDER - TUBE TYPE (STD)
Mounted on frame by landing gear on DS.