91810 thm 91812



Quote Date: 2022-07-05
Quote Expires: 2022-07-12
Quote Number: 35361
Reference: October
Company: OCEAN TRAILER
DON Aleksejus
FONTAINE TRAILER
430 Sam Letson Rd
Haleyville AL 35565
daleksejus@fontainetrailer.ne

14605

Estimated Weight (lbs) (+/- 3%)

Canadian Velocity 53' Tridem Air Slider (Model: HBVSF22TAS)

Quantity: 3	3
Overall Length: 53 feet x 102 inches	ſ
Suspension Type: Sliding air tridem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements	
Frame Rating: 100,000 lbs distributed- GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch wood	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Pipe Spools: Double between stake pockets	
Rubrail: 3/8 inch x 2 1/2 inch steel	
Main Beams: 130K load bearing flanges	
Kingpin: 24 inches; 5/16" Plate	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard with Forward & Rear Bracing	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets: None standard	
Number of Axles: 3 Intraax	
Axie Position: 96 inch adjustable	
Axle Spread: 60 inches, 60 inches Kingpin to C/L Rear Axle: 39 feet 4 3/4 inches in front position- 47 feet 4 3/4 inches in rear position	
Axle Spindle:Parallel (Straight)	
Dust Shields: Installed on all axles	
Brakes:TSE Spring brakes, Haldex auto slacks	
Air Line Filters:(2) Meritor In-line type installed	~~~~~
ABS: Meritor Wabco 4S/2M - no cable or tool	,,
Hub and Drums: 10-hole hub-piloted with outboard cast drums (Webb)	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - 12 pre-painted white - STANDARD	
Tires:11R 22.5 14PR OEM standard tires quantity 12 STANDARD	
Tire Brand: OEM standard	
Tire Inflation System:None standard	
Suspension Detail: Hendrickson AAZNT69K Intraax air ride slider with ride height limiters- 96 inch adjustable; (1) Removable slide position	
stop bar	
Air Assist Slide Box Pins: Controls mounted inside box on front of slider box	
Manual Dump Valve: Standard	
Air Load Scale: Installed	
Front Corners: Tapered	
Electrical System:LED: 3 lights/side, 3 lights/side on rear	
Other Electrical Specifications: 3 4-way sockets with one hot/one ground pin for wide load and strobe light connections: 1 rear, 1 ea. side	
at rear	
Paint:Black urethane with Velocity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed on rubrails	
Bumper: Weld-on type - meets underride requirements	
Mudflaps;1 set OEM standard	
Spare Tire Carrier:None standard	
Side Mounted Winches: 26 standard - without straps: 13 per side-three bar type	
Special J Hooks: 26 total - 13 per side-opposite winches	
Tarp Hooks: 2 foot centers on all sides when possible: undermount rs/cs: side mount front/back	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer:None standard	
TO AND THE PARTY OF THE PARTY O	
Registration Holder:Install registration holder - Tite Seal Tool Box:1 aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side	
Tow Hooks: 1 Installed on rear	
VIN Plate: Bilingual US/Canadian VIN plate	
Please Note: Price includes commodity surcharges	
Unit Numbers & Decals: Not available	
Stacking: Price includes Standard stacking of each trailer	
1)	