



The First Name In Trailers

C. Keay Investments Ltd.

Will Tucker
100 Golden Drive
Coquitlam, BC V3K 6T1
Voice 604-945-3718

Stock Tandem
TBR DRY Van

PO# 92134-92158

PO# 92094-92113

PO# 92114-92133

Trailer Quote Prepared For

OCEAN TRAILER STOCK

9076 RIVER ROAD

DELTA, BC V4G 1B5

25 - VS2DX

September 14, 2022

Specifications (☞ = Option to Base Model)

1-Model & Payload Capacity

<i>MODEL</i>	VS2DX
<i>PAYLOAD CAPACITY</i>	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
<i>SPECIAL TRAILER APPLICATION</i>	TALL BOTTOM RAIL(TBR) FOR 4000DX 101.25 SYSTEM (REQUIRES A MIN. 20,000LB FLOOR RATING)
<i>GROSS VEHICLE WEIGHT RATING</i>	65,000 LBS GVWR
<i>INTERNATIONAL IMPORTATION SPECIFICATIONS</i>	☞ FRENCH/ENGLISH SER PLT REQD FOR IMPORT TO CANADA
<i>4000D-X101.25 SYSTEM</i>	BASE SPEC: 4000D-X 101.25
<i>GREENHOUSE GAS COMPLIANCE</i>	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
<i>DQS UPDATE NUMBER</i>	DQS UPDATE #179 (8/1/22)

2-Dimensions

<i>LENGTH</i>	53'0" OVERALL LENGTH
<i>OVERALL HEIGHT</i>	13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST HEIGHT
<i>WIDTH</i>	102-3/8" OVERALL WIDTH
<i>INSIDE HEIGHT</i>	110-1/2" INSIDE HEIGHT AT FRONT; 111" INSIDE HEIGHT AT REAR
<i>INSIDE WIDTH</i>	101" INSIDE WIDTH AT WEARBAND (+/- 1/4" TOLERANCE)

3-Deck

<i>DECK TYPE</i>	STRAIGHT DECK WITH 1/2" WEDGE
------------------	-------------------------------

4-Front Subframe

<i>FRONT SUBFRAME</i>	3-1/2" DEEP BOX BEAM DESIGN FRONT SUBFRAME RAISED 1-3/8" FLUSH WITH TOP OF FLOOR
<i>APPROACH PLATE</i>	1/4" HIGH STRENGTH STEEL APPROACH PLATE
<i>KINGPIN PLATE</i>	3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
<i>KINGPIN TYPE</i>	AAR HARDNESS CRUCIFORM KINGPIN
<i>KINGPIN LOCATION</i>	36" KINGPIN LOCATION
<i>COVER PLATE</i>	☞ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL

5-Support Legs

<i>SUPPORT LEG LOCATION</i>	SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN
-----------------------------	--

<i>SUPPORT LEG CRANK LOCATION</i>	ROADSIDE SUPPORT LEG CRANK LOCATION
<i>SUPPORT LEG BRACING</i>	BOLT-ON CROSS BRACING WITH 7 GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL
<i>SUPPORT LEGS</i>	☞ JOST MODEL A451 MAGNUM SUPPORT LEGS W/10-YR WARRANTY & 10"X10" ULTRA LOW PROFILE CUSHION FOOT
6-Frame, Rails & Crossmembers	
<i>BOTTOM RAILS</i>	10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS
<i>CROSSMEMBERS FRONT SUB TO LEGS</i>	2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE
<i>CROSSMEMBERS OVER SUPPORT LEGS</i>	(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON 12" C/L OVER SUPPORT LEGS
<i>CROSSMEMBERS LEGS TO REAR SUB</i>	4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12" C/L LEGS TO REAR SUB
<i>CROSSMEMBERS OVER REAR SUBFRAME</i>	4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR SUB
7-Rear Subframe	
<i>HORIZONTAL DOCK BUMPER</i>	BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER
<i>RUBBER DOCK BUMPERS</i>	☞ (1) PAIR RUBBER DOCK BUMPERS 1/2" PROUD
<i>VERTICAL & HORIZONTAL DOCK BUMPER</i>	BASE SPEC: DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IHHS-30% OFFSET TEST
8-Suspension/Axles/Actuation	
<i>SLIDER SUSPENSION LOCATION</i>	70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL
<i>OIL SEALS</i>	CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>AIR BRAKE CHAMBERS</i>	BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS
<i>AIR ACTUATION</i>	ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES
<i>SLACK ADJUSTERS</i>	BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS
<i>HUBODOMETER</i>	☞ STEMCO HUBODOMETER MTD R/S FRONT AXLE
<i>DUST SHIELDS</i>	☞ DUST SHIELDS FOR 16-1/2" X 7" BRAKES
<i>BRAKE LINING STYLE</i>	HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX
<i>AXLE SPINDLE NUTS</i>	CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END SYSTEM)

<i>HUB PILOTED SYS W/OUTBOARD DRUMS FOR 16-1/2" X 7" BRAKES</i>	10 STUD HUB PILOTED SYS W/OUTBRD CAST DRUMS W/16-1/2"X 7"BRKS(STD W/CONMET PRESET+WHEEL END SYS)
<i>ANTILOCK BRAKE SYSTEMS (ABS)</i>	BENDIX TABS-6 2S/1M ABS SYSTEM *W/O ROLL STABILITY*
<i>WHEEL BEARING LUBRICATION</i>	FACTORY CHOICE 80W-90 OIL
<i>ANTI-DOCK WALK DEVICES</i>	☞ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE
<i>WHEEL SEPARATOR PLATES</i>	☞ NYLON WHEEL GUARD SEPARATOR PLATE BTWN INNER WHEEL & HUB
<i>AXLE MANUFACTURER</i>	HENDRICKSON "VENTED" AXLES
<i>AXLE SPINDLE TYPE</i>	☞ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM
<i>AUTOMATIC TIRE INFLATION SYSTEM</i>	☞ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
<i>LOAD SCALE KIT</i>	☞ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
<i>WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER</i>	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HENDRICKSON AIRRIDE SYSTEMS WITH INTEGRAL AXLES</i>	BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)
<i>SLIDER PIN RELEASE MECHANISM</i>	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
<i>CONMET WHEEL END SYSTEMS</i>	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT

9-Front Wall

<i>FRONT CORNER POST</i>	.080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS
<i>FRONT WALL POSTS</i>	(4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL POSTS
<i>FRONT PANELS</i>	.040 ALUM FRONT PANELS
<i>GLADHANDS & RECEPTACLE LOCATION</i>	SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET 27-1/2" TO R/S FROM C/L OF TRAILER
<i>FRONT TOP RAIL</i>	EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL

10-Side Walls

<i>SIDE PANELS</i>	COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC POLYURETHANE FOAM CORE BONDS INT/EXT PANELS)
--------------------	---

SIDE POSTS 3/8" 14GA HIGH STR GALV HAT SHPD 24"C/L (FRT/RR SUB 16"C/L)
W/"A" SLOTS ON 8" VERT C/L

11-Roof

TOP RAILS 4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS

ROOF SKIN .040 ONE PIECE ALUM COIL ROOF SKIN

ROOF BOWS 1-1/16" ANTI SNAG 18GA GALV STL HAT SHAPED ROOF BOWS
16"C/L(FRT/ RR SUB 24"C/L)BONDED TO ROOF SKN

12-Rear Doors

REAR DOOR TYPE COMPOSITE REAR SWING DOORS

REAR DOOR PANELS 1/2" COMPOSITE REAR SWING DOORS (PRE-PAINTED WHITE GALV
STEEL PANELS W/POLYETHYLENE CORE)

REAR DOOR LOCK RODS (1) REAR DOOR LOCK ROD PER DOOR

REAR DOOR HINGES (1) ADDITIONAL PAIR OF REAR DOOR HINGES

HOLDBACKS CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS

*REAR CASE & BUCKPLATE
MATERIAL* SATIN FINISH SST REAR DOOR CASE

*GRAB HANDLE AT REAR OF
TRAILER* (1) 36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S
DOOR

REAR TREADPLATE .219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE
INTEGRAL WITH REAR BUCKPLATE

REAR DOOR HINGE MATERIAL NON-POLISHED ALUMINUM

14-Floor

FLOOR TYPE 20,000LB 1-3/8"NOM LAM HDWD FLR; FACTORY CHOICE:OAK OR
SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM

FLOOR JOINT SEALANT CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT

16-Lining

FRONT WALL LINING .016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING

SIDE WALL LINING PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING

WEARBAND (1) 14GA X 5/16" X 8" NOM GALV STL HD SIDEWALL WEARBAND FOR
USE WITH TALL BOTTOM RAIL (TBR)

WEARBAND ON FRONT 14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL
WEARBAND

SIDE WALL LINING CLOSURES 45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING
CLOSURES

17-Electrical System

MAIN HARNESS UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH
INTERNAL GROUND AND 7-WAY PLUG

<i>ELECTRICAL RECEPTACLE</i>	7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED
<i>CLEARANCE LIGHT QUANTITY</i>	⇒ 2-1-2-5 CLEARANCE LIGHT PACKAGE
<i>ADDITIONAL STOP/TAIL LIGHTS</i>	⇒ ONE ADDITIONAL STOP/TAIL LIGHT EACH SIDE WITH EXTENDED LIGHT PROTECTOR BAR
<i>SIDE MOUNTED DIRECTIONAL LIGHT</i>	GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE
<i>STOP/TAIL/TURN LIGHTS</i>	GROTE 4" L.E.D. (10-DIODE) STOP/ TAIL/TURN LIGHTS (2) PER SIDE WITH BLACK SNAP-IN FLANGE
<i>LICENSE LIGHT</i>	GROTE MICRONOVA L.E.D. LICENSE LIGHT
<i>CONSPICUITY TAPE LOCATION</i>	CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION
<i>CONSPICUITY TAPE</i>	FACTORY CHOICE CONSPICUITY TAPE
<i>UPPER CLEARANCE LIGHTS</i>	FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L
<i>LOWER CLEARANCE LIGHTS</i>	GROTE MICRONOVA LED PC RATED LIGHT
<i>ABS (ANTI-LOCK) WARNING LIGHT</i>	GROTE MICRONOVA L.E.D. PC RATED LIGHT
<i>STOP/TAIL/TURN LIGHT CONFIGURATION</i>	GROUPED STOP/TAIL/TURN LIGHTS
<i>REAR HEADER CLEARANCE LIGHTS</i>	GROTE MICRONOVA L.E.D. PC RATED GROMMET MOUNTED REAR HEADER ID/ CLR LIGHTS

18-Finish Specifications

<i>TOP FRONT & TOP SIDE RAIL FINISH</i>	NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS
<i>BOTTOM SIDE RAIL FINISH</i>	NATURAL ALUM FINISH BOTTOM SIDE RAILS
<i>FRONT CORNER POST FINISH</i>	NATURAL ALUMINIUM FINISH FRONT CORNER POSTS
<i>FRONT PANEL FINISH</i>	PREPAINTED WHITE FRONT PANELS
<i>SIDE PANEL FINISH</i>	PREPAINTED WHITE SIDE PANELS
<i>FRONT SUBFRAME ASSEMBLY FINISH</i>	FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED
<i>SUPPORT LEG FINISH</i>	BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS
<i>REAR SUBFRAME FINISH</i>	BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME
<i>REAR CASE FINISH</i>	SATIN FINISH STAINLESS STEEL REAR CASE
<i>VRTCL & HORIZNTL DOCK BUMPR FINISH</i>	UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK SCHARPF ON VERTICAL DOCK BUMPER
<i>ROOF EXTERIOR FINISH</i>	NATURAL ALUM ROOF EXTERIOR FINISH

REAR DOOR COLOR
FLOOR UNDERCOAT

PREPAINTED WHITE REAR DOORS
BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

19-Miscellaneous

MUDFLAP TYPE

BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS

PERMIT HOLDER

☞ TRUCKLITE #97960 ROUND PERMIT HOLDER MOUNTED ON FRONT WALL LOWER R/S

SIDE MOUNTED
AERODYNAMIC AIR
DEFLECTORS

BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE SKIRT MTD BELOW BOTTOM RAIL

20-Tires and Wheels

22.5"X8.25"STANDARD WIDTH
WHEELS

☞ 8 - 22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10 H/P#ULT397

22.5" LOW PROFILE TIRES

8 - 295/75R 22.5 MICH X-LINE ENERGY -T2 14PLY 39.70"T/D,LOAD RG'G' MAX SPEED RATED@75 MPH;

Special Instructions

None.

Weight

Total Weight 13,147 lbs. (+/- 3%)

Terms & Conditions