

Unit #92168-92172
Stock Tandem
Reefer Van



Po#92159-92188

C. Keay Investments Ltd. Po#92189-92208

Will Tucker
100 Golden Drive
Coquitlam, BC V3K 6T1
Voice 604-945-3718

Trailer Quote Prepared For

OCEAN TRAILER STOCK

9076 RIVER ROAD

DELTA, BC V4G 1B5

30 - VS2RA
September 16, 2022

Specifications (☞ = Option to Base Model)

1-Model & Payload Capacity

MODEL	VS2RA
PAYLOAD CAPACITY	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
GROSS VEHICLE WEIGHT RATING	65,000 LBS GVWR
INTERNATIONAL IMPORTATION SPECIFICATIONS	☞ FRENCH/ENGLISH SER PLT REQD FOR IMPORT TO CANADA
GREENHOUSE GAS COMPLIANCE	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
FOAM COMPOSITION	TRAILER CONTAINS NON-HFC FOAM; MAY BE SOLD OR USED IN STATE W/ HFC RESTRICTION
DQS UPDATE NUMBER	DQS UPDATE #179 (8/1/22)

2-Dimensions

LENGTH	53'0" OVERALL LENGTH
OVERALL HEIGHT	13'6" O/A HEIGHT ON 46-1/2" FIFTH HT FOR 107-1/8" POST HT
WIDTH	102-3/8" OVERALL WIDTH

3-Deck

DECK TYPE	STRAIGHT DECK
-----------	---------------

4-Front Subframe

FRONT SUBFRAME	4-1/4" DEEP BOX BEAM DESIGN FRONT SUBFRAME
APPROACH PLATE	9GA HIGH STRENGTH STEEL FULL WIDTH APPROACH PLATE
KINGPIN PLATE	3GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
KINGPIN TYPE	AAR HARDNESS CRUCIFORM KINGPIN
KINGPIN LOCATION	36" KINGPIN LOCATION
CONDUIT	(1) CONDUIT THROUGH FRONT SUB 30-1/2" FROM C/L ON ROADSIDE
COVER PLATE	EXTRUDED ALUM COVER ON FRONT FACE OF APPROACH PLATE

5-Support Legs

SUPPORT LEG LOCATION	SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN
SUPPORT LEG CRANK LOCATION	ROADSIDE SUPPORT LEG CRANK LOCATION
SUPPORT LEG BRACING	BOLT ON SUPPORT LEG X-BRACING W/7GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL

SUPPORT LEGS

- JOST MODEL A451 MAGNUM SUPP LEGS W/10-YR WARRANTY AND 10"X10" LOW PROFILE REMOVABLE CUSHION FOOT

6-Frame, Rails & Crossmembers

BOTTOM RAILS

- DO NOT NOTCH OUT BOTTOM RAIL AT REAR

BOTTOM RAILS

11" DEEP HEAVY DUTY EXTRU ALUM BOTTOM RAILS, TAPERED FRT & REAR

CROSSMEMBERS FRONT SUB TO LEGS

4" ALUM I BEAM CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L FRONT SUB TO SUPPORT LEGS

CROSSMEMBERS OVER SUPPORT LEGS

(5) 4" STEEL I BEAM CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L OVER SUPPORT LEGS.

CROSSMEMBERS LEGS TO REAR SUB

5-1/2" ALUM I SHAPE CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L SUPPORT LEGS TO REAR SUB

CROSSMEMBERS OVER REAR SUBFRAME

4" STEEL I BEAM CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L W/STD REINF OF (1) ADDL CMEM IN REAR 34"

CROSSMEMBERS OVER REAR SUBFRAME

- (2) ADDL STEEL CMEMS IN REAR 58" ON 6" C/L

PREP FOR FUEL TANK FOR USE WITH SIDE SKIRTS

- 50 GAL FUEL TANK PREP (UTM STD) LAST(2)CMEM OVER LEGS & 1ST CMEM IN BAY AREA PUNCHED FOR TANK

7-Rear Subframe

HORIZONTAL DOCK BUMPER

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER

RUBBER DOCK BUMPERS

- (1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD

VERTICAL & HORIZONTAL DOCK BUMPER

- DOT BMPR BOLT-ON VERT & NONSLIP HRZ 21"MAX FROM GRND WITHIN LESS THAN 4"OAW EA SIDE FOR 7"BUMPER

VERTICAL & HORIZONTAL DOCK BUMPER

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IIHS-30% OFFSET TEST

8-Suspension/Axles/Actuation

SLIDER SUSPENSION LOCATION

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL

OIL SEALS

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)

AIR BRAKE CHAMBERS

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

AIR ACTUATION

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

SLACK ADJUSTERS

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

HUBODOMETER

- STEMCO HUBODOMETER MTD R/S FRONT AXLE

DUST SHIELDS

- DUST SHIELDS FOR 16-1/2" X 7" BRAKES

<i>BRAKE LINING STYLE</i>	HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX
<i>AXLE SPINDLE NUTS</i>	CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HUB PILOTED SYS W/OUTBOARD DRUMS FOR 16-1/2" X 7" BRAKES</i>	10 STUD HUB PILOTED SYS W/OUTBRD CAST DRUMS W/16-1/2"X 7"BRKS(STD W/CONMET PRESET+WHEEL END SYS)
<i>ANTILOCK BRAKE SYSTEMS (ABS)</i>	BENDIX TABS-8 ADVANCED W/ROLL STABILITY 2S/1M ABS
<i>WHEEL BEARING LUBRICATION</i>	FACTORY CHOICE 80W-90 OIL
<i>ANTI-DOCK WALK DEVICES</i>	➡ HENDRICKSON ANTI DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE
<i>AXLE MANUFACTURER</i>	HENDRICKSON "VENTED" AXLES
<i>AXLE SPINDLE TYPE</i>	➡ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM
<i>AUTOMATIC TIRE INFLATION SYSTEM</i>	➡ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
<i>LOAD SCALE KIT</i>	➡ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
<i>WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER</i>	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HENDRICKSON AIRRIDE SYSTEMS WITH INTEGRAL AXLES</i>	BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)
<i>SLIDER PIN RELEASE MECHANISM</i>	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
<i>CONMET WHEEL END SYSTEMS</i>	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER & SPINDLE NUT

9-Front Wall

<i>FRONT CORNER POST</i>	BASE SPEC: .080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POST WITHOUT INSERT RECEIVERS
<i>FRONT WALL POSTS</i>	1" "J" EXTRU ALUM FRT WALL POST W/(2) ADDL 3-1/4" DEEP STEEL REEFER UNIT SUPPORT POSTS
<i>FRONT PANELS</i>	.040 ALUM FRONT PANELS
<i>GLADHANDS AND RECEPTACLE</i>	GLADHANDS (W/SCREEN) AND RECEPTACLE MOUNTED ON AN ALUM EXTRU OFFSET TO R/S 30"
<i>REFRIGERATION UNIT OPENING COVER</i>	SHEET METAL COVER (INCLS SEALANT FULL PERIMETER OF OPENING)

PREP FOR THERMO
KING/CARRIER REEFER UNIT

PREP FOR LARGE FRONT MOUNT THERMO KING/CARRIER REEFER
UNIT *****W/O ELECTRIC STANDBY*****

10-Side Walls

SIDE PANELS

- ⇒ .040 ALUM CORR SIDE PANELS, USE W/1-1/2" SIDE WALL INSUL (INCLS 1"HD J POST 16"C/L REAR OF LEGS)

SIDE POSTS

- ⇒ **NOTE** 1" HD "J" posts 16" C/L rear of legs (for use with .040 side panels)

EXTERIOR SIDE WALL
PROTECTION

- ⇒ LOCATE RUB PROTECTOR @ APPROX 14-13/16" FOR TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR

EXTERIOR SIDE WALL
PROTECTION

- ⇒ RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE
REQUIRED INFORMATION:

Dealer must specify location of (1) rub protector c/l of rub rail to top of bottom rail and location of (1) rub protector c/l of rub protector to bottom of top rail.

- >> LOCATE RUB PROTECTOR @ APPROX 14-13/16" FOR TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR

11-Roof

TOP RAILS

- 6-3/8" HEAVY DUTY EXTRUDED ALUM TOP RAILS

ROOF SKIN

- .025 ONE PIECE ALUM COIL ROOF SKIN

ROOF BOWS

- ⇒ 1" EXTRU ALUM "J" SHAPE ROOF BOWS ON 24" C/L

12-Rear Doors

REAR DOOR TYPE

- UTM BARRIER DESIGN DOUBLE SWING REAR DOORS

REAR DOOR PANELS

- ⇒ .040 TRANSLITE POLISHED ALUMINUM DIAMOND PATTERN REAR DOOR PANELS

REAR DOOR CROSSBRACES

- ⇒ EXTEND REAR DOOR HAT SECTION FULL WIDTH WHERE IT MEETS WITH LOWER C/S VENT

REAR DOOR LOCK RODS

- ⇒ (1) ADDL REAR DOOR LOCKROD ON CURBSIDE FOR TOTAL OF (3)

REAR DOOR HINGES

- ⇒ REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT PREVENTION

REAR DOOR HINGES

- ⇒ REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT PREVENTION

REAR DOOR HINGES

- ⇒ (5) REAR DOOR HINGES PER DOOR

VENT DOOR REAR

- ⇒ 6" X 16" REAR VENT W/STAINLESS STEEL COVER ON LOWER C/S (INCLUDES VENT OPENING SCREEN)

HOLDBACKS

- CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS

REAR CASE & BUCKPLATE
MATERIAL

- SST REAR DOOR CASE FOR SWING DOORS

REAR CASE CORNER POSTS &
HEADER

REAR GUSSETS

GRAB HANDLE AT REAR OF
TRAILER

REAR DOOR HINGE MATERIAL

REAR DOOR HINGE PIN
MATERIAL

CORROSION RESISTANT REAR
DOOR HARDWARE

⇒ SHALLOW REAR WEDGE PORTION OF REAR SWING DOOR HEADER
FROM 1-1/8" TO 1/2"

ENHANCED REAR CORNER GUSSET DESIGN FOR IMPROVED
BOTTOM RAIL STRENGTH AT REAR OF TRAILER

⇒ 36" LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S
DOOR

NON-POLISHED ALUMINUM

⇒ **NOTE** Stainless Steel Hinge Pins

⇒ CORROSION RESIST ELECTROPOLISHED SST REAR DOOR
HARDWARE SWING DRS (INCL NON-POLISHED ALUM HINGES)

14-Floor

FLOOR TYPE

⇒ 20,000LBS 1-1/2" NOM EXTRUDED ALUM HIGH WEAR DUCT FLR
KNURLED

FLOOR TURN UP

10" HIGH 3/16" HEAVY DUTY EXTRU ALUM NON-TAPERED W/B
INTEGRAL W/FLOOR (INCLUDES REINFORCING)

TROUGHS

EXTRU ALUM TROUGH FRONT & REAR

DRAINS

(2) DRAINS FRONT AND (2) REAR

REAR THRESHOLD

HEAVY DUTY EXTRU ALUM WEDGE TYPE REAR THRESHOLD W/(4)
DOCK BOARD GUIDE PLATES

FORK LIFT REINFORCING

BEARING GRID SYS AT REAR W/HDWD FILLERS FULL LENGTH &
ALUM I CORES REAR 36" OF FLR IN CTR 68"

STUB POSTS

SIDEWALL STUB POST ON 48" C/L

15-Insulation

INSULATION TYPE

POLYURETHANE INSULATION FOAMED IN PLACE

FRONT WALL THICKNESS

4" THICK FRONT WALL

SIDE WALL THICKNESS

⇒ 1-1/2" SIDEWALL INSULATION

ROOF THICKNESS

⇒ 2" ROOF INSULATION

FLOOR THICKNESS

⇒ 2" FLOOR INSULATION

REAR DOOR THICKNESS

3" THICK REAR DOORS

CROSSMEMBER FLOOR
FILLERS

HARDWOOD FLOOR FILLERS FULL LENGTH

FLOOR UNDERSKIN

.035 THERMOPLASTIC FLOOR UNDERSKIN

16-Lining

FRONT WALL LINING

.065 (NOM) VERSITEX-UTILITY VR2U FRONT WALL LINING

SIDE WALL LINING

⇒ FACTORY CHOICE SIDEWALL LINING VR3U .085
VERSITEX/ARMORTUF-075 FLAT ARMT**SEE DISCLAIMER NOTE**

ROOF LINING	.065 (NOM) VERSITEX-UTILITY VR2U ROOF LINING
REAR DOOR LINING	.065 (NOM) VERSITEX-UTILITY VR2U REAR DOOR LINING
WEARBAND	⇒ 6" EXTRA HEIGHT EXTRUDED ALUM STD DUTY WEARBAND TOTAL OF 16" INCL REINFORCING BEHIND WEARBAND
LOGISTIC RAILS	⇒ LOCATE E-TRACK @ 54" FROM TOP OF FLOOR TO C/L OF TRACK
LOGISTIC RAILS	⇒ (1) ROS SERIES "E" GALV RECESS MTD LOG TRACK FOR USE W/1-1/2" SIDE WALL INSULATION
LOGISTIC RAIL SPL MODIFICATION	⇒ REINFORCE "A" OR "E" TYPE LOG TRACK FOR DOUBLE DECKING
WEARBAND ON REAR SWING DOORS	⇒ 16" HIGH X 1/8" SMOOTH ALUM WEARBAND W/BVELEDED EDGES ON REAR SWING DOORS INCL HARDWOOD REINIF
REAR DOOR LINING COVER	24" HIGH EXTRU ALUM REAR DOOR LINING EDGE PROTECTOR

17-Electrical System

MAIN HARNESS	UTM MOISTURE RESISTANT "MULTI- PURPOSE" HARNESS W/INTERNAL GROUND AND 7-WAY PLUG
ELECTRICAL RECEPTACLE	7-WAY ELECTRICAL RECEPTACLE W/O CIRCUIT BREAKERS
CLEARANCE LIGHT QUANTITY	⇒ 2-1-2-5 CLEARANCE LIGHT PACKAGE
ADDITIONAL STOP/TAIL LIGHTS	⇒ ONE ADDL STOP/TAIL LIGHT EACH SIDE ON SST BUCK PLATE WITH EXTENDED LIGHT PROTECTOR BAR
SIDE MOUNTED DIRECTIONAL LIGHT	GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE
STOP/TAIL/TURN LIGHTS	⇒ GROTE 4"DIA SST SNAP-IN FLANGE MTD LED(10 DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)
LICENSE LIGHT	GROTE MICRONOVA L.E.D. LICENSE LIGHT
CONSPICUITY TAPE LOCATION	CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER (FOR D.O.T. MINIMUM LOCATION)
CONSPICUITY TAPE	FACTORY CHOICE CONSPICUITY TAPE
UPPER CLEARANCE LIGHTS	⇒ TRUCKLITE MODEL 35 PC RATED LED UPPER SIDE RAIL CLEARANCE LIGHTS
LOWER CLEARANCE LIGHTS	GROTE MICRONOVA LED PC RATED LIGHT
ABS (ANTI-LOCK) WARNING LIGHT	GROTE MICRONOVA L.E.D. PC RATED LIGHT
STOP/TAIL/TURN LIGHT CONFIGURATION	GROUPED STOP/TAIL/TURN LIGHTS
REAR HEADER CLEARANCE LIGHTS	⇒ (5) GROTE MICRONOVA L.E.D. P2 RATED MULTI-FUNCTION LIGHTS ON REAR SWING DOOR HEADER

18-Finish Specifications

<i>TOP FRONT & TOP SIDE RAIL FINISH</i>	NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS
<i>BOTTOM SIDE RAIL FINISH</i>	NATURAL ALUM FINISH BOTTOM SIDE RAILS
<i>FRONT CORNER POST FINISH</i>	NATURAL ALUMINIUM FINISH FRONT CORNER POSTS
<i>FRONT PANEL FINISH</i>	PREPAINTED WHITE FRONT PANELS
<i>SIDE PANEL FINISH</i>	PREPAINTED WHITE SIDE PANELS
<i>REAR DOOR PANEL FINISH</i>	PREPAINTED WHITE REAR DOOR PANEL FINISH
<i>FRONT APPROACH PLATE FINISH</i>	NATURAL ALUM FINISH FRONT APPROACH PLATE
<i>FRONT SUBFRAME ASSEMBLY FINISH</i>	FRONT SUBFRAME FULLY IMMERSSED IN BLACK RUST PREVENTATIVE FINISH (ZERO VOC HOT DIP)
<i>SUPPORT LEG FINISH</i>	UTM BLACK SCHARPF ON SUPPORT LEGS
<i>REAR SUBFRAME FINISH</i>	UTM BLACK SCHARPF ON REAR SUBFRAME
<i>REAR CASE FINISH</i>	SATIN FINISH STAINLESS STEEL REAR CASE
<i>VRTCL & HORZNTL DOCK BMPR FINISH</i>	UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK SCHARPF ON VERTICAL DOCK BUMPER
<i>ROOF EXTERIOR FINISH</i>	NATURAL ALUM ROOF EXTERIOR FINISH

19-Miscellaneous

<i>MUDFLAP TYPE</i>	BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS
<i>PERMIT HOLDER</i>	⇒ TRUCKLITE #97960 ROUND PERMIT HOLDER MOUNTED ON FRONT WALL LOWER R/S
<i>SIDE MOUNTED AERODYNAMIC AIR DEFLECTORS</i>	BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE SKIRT MTD BELOW BOTTOM RAIL

20-Tires and Wheels

<i>22.5"X8.25"STANDARD WIDTH WHEELS</i>	⇒ 8 - 22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10 H/P#ULT397
<i>22.5" STANDARD PROFILE TIRES</i>	⇒ 8 - 11R 22.5 MICH XTE 14P 41.00" TIRE DIA. LOAD RANGE 'G' MAX SPBED RATED @75 MPH; TRRL =<6.0

Special Instructions

None.

Weight

Total Weight 12,824 lbs. (+/- 3%)

Terms & Conditions



Unit # 92168-72

4705 61 Ave SE
Calgary AB T2C 4W1
403- 279-8091
403-236-3490

Nov 30,2022
Q81404

SINGLE TEMP TRAILER REEFER X4 7300 - BLACK

INCLUDED IN YOUR X4 7300 REEFER:

- EPA Certified Tier4 final engine (2022)
- Full stealth package and bottom panel
- High capacity alternator
- Battery
- Auto-dimming LED lightbar
- Universal airchute and adapter
- USB Interface with data security
- Black grille
- New fuel lines
- 50 gallon aluminum fuel tank
- Return air bulkhead

REEFER CRASH GUARD
MODULE, E-SOLUTIONS TELEMATICS
SHUTDOWN KIT, LOW FUEL SENSOR

NOTES :

Please be advised Quote may be subject to change on Pricing & Model based on build and availability.

*Installation into your trailer included

*Subject to change and product availability

*Subject to possible manufacturer surcharge.

All installations are to be done into your properly prepared truck or trailer. Thank you for the opportunity to assist you with this equipment selection. We look forward to working with your company in the near future.

Respectfully yours

Vishaal Sherman