

# Trailer Specs

Customer:	STOCK	Production No.	2024-U-0146-050
	000-000-0000	Factory of Production	UTAH
	2023 TANDEM REEFERS	Shipping Instructions	DEALER ARRANGED
Dealer:	894 DELTA,BC		
Salesperson:	MIKE PRINCE-WRIGHT		
Purchase Order:	92209 - 92258		
Quote No.	CA-71486		

**\*\*\*Warning\*\*\***  
**Specifications have been modified by change notice.**

**SPECIFICATIONS**

BASE MODEL: VS2RA

DWG:	GVWR: 65,000
OVERALL LENGTH:	53'
OVERALL WIDTH:	102 3/8"
OVERALL HEIGHT:	13' 6"
FIFTH WHL HT:	46 1/2
POST HT FRONT:	107 1/8 "
POST HT REAR:	107 1/8 "
KINGPIN LOC:	36"
REAR SUSPENSION LOC:	SLIDER
REFRIG. UNIT PREP:	LRG FRONT UNIT

Option No.	Qty	Description	Unit Price	List Price
001-500-008		FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION		
001-664-005		TRAILER CONTAINS NON-HFC FOAM; MAY BE SOLD OR USED IN STATE W/ HFC RESTRICTION		
001-670-004		DQS UPDATE #179 (8/1/22)		
006-018-023		EXTRA HEAVY DUTY BOTTOM RAILS		
006-018-026		DO NOT NOTCH OUT BOTTOM RAIL AT REAR		
006-269-013		(1) ADDL STEEL CMEM IN REAR 46" ON 6" C/L		
008-111-033		STEMCO HUBODOMETER MTD C/S REAR AXLE		
008-112-023		DUST SHIELDS FOR 16-1/2" X 7" BRAKES		
008-113-024		PHILLIPS QWIK-E GLADHAND W/QUICK RELEASE VALVE		
008-435-016		HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE		
008-487-033		P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM		
008-499-023		HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*		

008-501-014		HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
008-585-023		BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT
009-036-045		BASE SPEC: .080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POST WITHOUT INSERT RECEIVERS
009-549-035		PREP FOR TK PRECEDNT S600 SINGLE TEMP FRONT MOUNT REEFER UNIT WITHOUT ELECTRIC STANDBY
010-606-002		RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE
012-052-026		(5) REAR DOOR HINGES PER DOOR
012-053-036		6" X 16" REAR VENT W/STAINLESS STEEL COVER ON LOWER C/S (INCLUDES VENT OPENING SCREEN)
014-057-283		20,000LBS 1-1/2" NOM EXTRUDED ALUM HIGH WEAR DUCT FLR KNURLED
015-065-029		2" ROOF INSULATION
015-066-025		2" FLOOR INSULATION
016-130-158	2.00	(1) ROW SERIES "E" GALV RECESS MTD LOG TRACK ON SIDE WALLS
017-077-161		2-1-2-5 CLEARANCE LIGHT PACKAGE
017-133-024		ONE ADDL STOP/TAIL LIGHT EACH SIDE ON SST BUCK PLATE WITH EXTENDED LIGHT PROTECTOR BAR
017-200-051	1.50	GROTE 4"DIA SST SNAP-IN FLANGE MTD LED (3-DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)
018-194-023		OMIT 3000R DECAL
019-143-024		BETTS PS-1 ROUND PERMIT HOLDER ON R/S FRT WALL
019-191-008	2.00	(4) LABELMASTER #80-SM NATURAL ALUMINUM PLACARD HOLDERS W/O PLACARDS
019-619-041		BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE SKIRT MTD BELOW BOTTOM RAIL
020-640-617	8.00	22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10 H/P#ULT397
020-646-437	8.00	275/80R 22.5 MICH XTE 14P 39.80"TIRES DIA.LOAD RANGE'G' MAX SPEED RATED @75 MPH; TRRL =<6.0

**SPECIAL INSTRUCTIONS:**

## GROUP 10:

A) LOCATE RUB PROTECTOR @ APPROX 2" FROM TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR.

## GROUP 16:

A) LOCATE (2) E-TRACKS @ THE FOLLOWING:

-(1) ROW @ 30" FROM TOP OF FLOOR TO C/L OF TRACK.

-(1) ROW @ 60" FROM TOP OF FLOOR TO C/L OF TRACK.

## GROUP 19:

A) LOCATE (8) PLACARDS AS FOLLOWS:  
(2) ON FRONT WALL ON C/S, (2) ON R/S &

C/S SIDE WALLS C/L OF TRAILER AND (2)  
ON REAR ON R/S, ALL SIDE-BY-SIDE.  
(REF 2019-U-5535)

ATTENTION;  
PLEASE CAREFULLY REVIEW THIS INFORMATION AND  
IMMEDIATELY COMMUNICATE ANY DISCREPANCIES.

Acknowledged by: JOSHUA REGUS  
DIRECT

11/01/22  
11/07/22

Prod Fcty: U Line: 1

**PROPOSED VIN NUMBERS:**

- |                      |                      |
|----------------------|----------------------|
| 1UY VS2534 R20146 01 | 1UY VS2536 R20146 02 |
| 1UY VS2538 R20146 03 | 1UY VS253X R20146 04 |
| 1UY VS2531 R20146 05 | 1UY VS2533 R20146 06 |
| 1UY VS2535 R20146 07 | 1UY VS2537 R20146 08 |
| 1UY VS2539 R20146 09 | 1UY VS2535 R20146 10 |
| 1UY VS2537 R20146 11 | 1UY VS2539 R20146 12 |
| 1UY VS2530 R20146 13 | 1UY VS2532 R20146 14 |
| 1UY VS2534 R20146 15 | 1UY VS2536 R20146 16 |
| 1UY VS2538 R20146 17 | 1UY VS253X R20146 18 |
| 1UY VS2531 R20146 19 | 1UY VS2538 R20146 20 |
| 1UY VS253X R20146 21 | 1UY VS2531 R20146 22 |
| 1UY VS2533 R20146 23 | 1UY VS2535 R20146 24 |
| 1UY VS2537 R20146 25 | 1UY VS2539 R20146 26 |
| 1UY VS2530 R20146 27 | 1UY VS2532 R20146 28 |
| 1UY VS2534 R20146 29 | 1UY VS2530 R20146 30 |
| 1UY VS2532 R20146 31 | 1UY VS2534 R20146 32 |
| 1UY VS2536 R20146 33 | 1UY VS2538 R20146 34 |
| 1UY VS253X R20146 35 | 1UY VS2531 R20146 36 |
| 1UY VS2533 R20146 37 | 1UY VS2535 R20146 38 |
| 1UY VS2537 R20146 39 | 1UY VS2533 R20146 40 |
| 1UY VS2535 R20146 41 | 1UY VS2537 R20146 42 |
| 1UY VS2539 R20146 43 | 1UY VS2530 R20146 44 |
| 1UY VS2532 R20146 45 | 1UY VS2534 R20146 46 |
| 1UY VS2536 R20146 47 | 1UY VS2538 R20146 48 |
| 1UY VS253X R20146 49 | 1UY VS2536 R20146 50 |

This Trailer Production Order is executed pursuant to that Utility Trailer Manufacturing Company Dealer/Distributor Sales and Service Agreement entered into between Utility Trailer Manufacturing Company and Dealer. The Parties agree to conduct this transaction by electronic means and this electronically submitted Trailer Production Order shall be binding on the parties and their respective successors and assigns. In the event that Dealer intends to execute subsequent transactions using a method other than electronic submission, Dealer shall contact Utility Trailer Manufacturing Company.

If you believe that your vehicle has a defect which could cause injury or death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying UTILITY TRAILER MANUFACTURING COMPANY.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer or UTILITY TRAILER MANUFACTURING COMPANY.

To contact NHTSA, you may either call the Auto Safety Hotline toll-free at 1-800-424-9393 (or 366-0123 in Washington, D.C. area) or write to: NHTSA, U.S. Department of Transportation, Washington, D.C. 20590. You can also obtain other information about motor vehicle safety from the Hotline.