

This offer is valid until the printed expiration date, and is subject to change at MAC's discretion based on market conditions.

Quote Date Friday, July 9, 2021 **Quote Pricing Expires** Friday, August 13, 2021

Contact

Customer

Quote # 59587 **Rev#** 2 **FLATBED**

*****Weight** 9819

Cubic Yards 0

*** denotes a weight for reference only. Trailer weight will be provided with the engineering design approval packet.

Quote Qty 12 **Model Code** FB **Plant of Mfg** H
Model FB FLATBED

Job # **VIN Plate** U.S. Certification Plate

■ **BODY**

FRAME RAIL MODEL	26 IN. (52K)
FRAME RAIL ARCH MODEL	3 1/2 IN.
LOAD PROFILE	MATERIAL, 80K GVWR
LENGTH	53
WIDTH	102
NECK STYLE	SQUARE FRONT, 10 IN. NECK, 102 WIDE
CROSSMEMBER SPACING	18 IN. ON CENTER
SPOOLS AND POCKETS	DOUBLE SPOOLS W/ POCKETS & HD RUB RAIL
NAILERS	2 NAILER POSITION, 1 BOARD IN
SIDE RAIL WINCH TRACK	STD W/ BOLT ON LL TRACK B.S. BAR B.S.
REAR END STYLE	REAR SMOOTH (FULL WIDTH BUMPER)
REAR STEPS	2 STEPS
DOCK BUMPERS	(2) 16 IN. OUTSIDE

■ **LIGHTS**

LIGHT TYPE	GROTE L.E.D. FLANGE W/ STAINLESS STEEL SECURITY RING
LIGHT PANEL	4 LARGE - 3 LARGE - 4 LARGE OOOO OOO OOOO
STD. MARKER LIGHTS	9 EACH SIDE
MARKER LIGHT LOCATION	STD.
MID-TURNS	(1) PAIR BOXED (CLOSED)
REAR AUXILIARY PLUG	4 WAY OFF MARKER



Located Facing Down off to the side of the license plate light

■ **PRIMARY AXLES**

MODEL	TANDEM
NO. OF PRIMARY AXLES	2
SUSPENSION	HEND. INTRAAX AANT-23K TP (250 BAGS) DISC BRAKE W /HXL-5

SUSPENSION SLIDER
AXLE SPACING

AXLE SETTING

AXLES
BRAKES
CAM GUARDS
HUB AND DRUM
TIRES
WHEELS
PRIMARY AXLE TIRE
INFLATION SYSTEM

SINGLE AXLE REAR SLIDER
122



Axle Set When Closed Cal Legal



NOTE ALL AXLE SETTINGS

Set Axles to be CAL and Canada Legal

AXLE FOR INTRAAX ONLY
DISC BRAKES - HEND. MAXX22T ADI HUB (23,000 LB ONLY)
NONE (DISC BRAKES)
NONE, DISC BRAKES
COOPER / ROADMASTER RM272, 295/75R 22.5 14 PLY
ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
NONE



Axles to be predrilled for future tirexxxx pro

■ **LIFT AXLES**

■ **STEERABLE LIFT AXLES**

■ **CHASSIS**

FRAME RAILS	MOVED TO BODY
FRAME RAIL ARCH	MOVED TO BODY
PIN SETTING	30
5TH WHEEL PLATE TYPE	POWDER COATED
5TH WHEEL PLATE	5/16 IN. GR-50, 3/8 KP, 102 WIDE
5TH WHEEL PLATE HEIGHT	48 IN. HIGH
SUSPENSION CONTROL	BALL VALVE (FULL SUSPENSION DUMP)
GLADHAND / ELECTRIC	DOLLIES AND FRONT
CONNECTION LOCATION	
ABS	(1) 4S2M MERITOR / WABCO
SLACKS	NONE (DISC BRAKES)
AXLE LUBRICATION	HXL, SYNTHETIC SEMI-FLUID GREASE
TIRE CARRIER(S)	1 CURB SIDE
DOLLIES - LANDING GEAR -	JOST AX-150 - (55,000 lb.) - 10 YEAR ALUMINUM - D.S.
LANDING LEGS	
AIR GAUGE / SYSTEM	YES, IN ENCLOSURE - MUST SELECT ENCLOSURE
ENCLOSURE FOR	STAINLESS STEEL
SWITCHES	
AIR TANKS	ALUMINUM TANK
ADDITIONAL FLAPS	REAR OF REAR AXLE, REAR OF FRONT AXLE (2 SETS)

■ **TARP**

■ **PAINT**

HANGERS	GALVANIZED
SUSPENSION COLOR	BLACK SOFT COAT
PIN STRIPING	BLACK (931716)
LANDING GEAR COLOR	BLACK (930248)
MAC MACHINE FINISH	BLACK (931716)
LOGOS	

■ **ACCESSORIES**

NO. OF TOOLBOXES	2
TOOL BOX SIZE	24X24X60 DOUBLE DOOR
TOOL BOX DOOR TYPE	ALUMINUM
TOOL BOX HARDWARE	T HANDLE
TOOL BOX LOCATION	BEHIND LANDING GEAR BOTH SIDES
	10" from bottom of rail to the top of the box
ROPE HOOKS (24 IN.	BOTH SIDES - FRONT AND REAR
SPACING)	
	Mounted Under Spools on the sides
NO. OF GALVANIZED STD.	16
DOUBLE L LOW PRO	
SLIDING WINCHES	



8 Per Side

