OTR#92470-92479 (10) Pintle Hitch Added

C. Keay Investments Ltd.

Will Tucker 100 Golden Drive Coquitlam, BC V3K 6T1 Voice 604-945-3718

Trailer Quote Prepared For

OCEAN TRAILER STOCK 9076 RIVER ROAD DELTA, BC V4G 1B5

30 - VS2DX September 23, 2022

Specifications (⊃ = Option to Base Model)

1-Model & Payload Capacity

MODEL

VS2DX

PAYLOAD CAPACITY

55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY

SPECIAL TRAILER

TALL BOTTOM RAIL(TBR) FOR 4000DX 101.25 SYSTEM (REQUIRES A

APPLICATION

GROSS VEHICLE WEIGHT

RATING

65,000 LBS GVWR

INTERNATIONAL **IMPORTATION**

SPECIFICATIONS

➡ FRENCH/ENGLISH SER PLT REQD FOR IMPORT TO CANADA

4000D-X101.25 SYSTEM

BASE SPEC: 4000D-X 101.25

MIN. 20,000LB FLOOR RATING)

GREENHOUSE GAS **COMPLIANCE**

THIS TRAILER IS NOT UTMC GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS

DOS UPDATE NUMBER

DQS UPDATE #179 (8/1/22)

2-Dimensions

LENGTH

53'0" OVERALL LENGTH

OVERALL HEIGHT

13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST

HEIGHT

WIDTH

102-3/8" OVERALL WIDTH

INSIDE HEIGHT

110-1/2" INSIDE HEIGHT AT FRONT; 111" INSIDE HEIGHT AT REAR

INSIDE WIDTH

101" INSIDE WIDTH AT WEARBAND (+/- 1/4" TOLERANCE)

3-Deck

DECK TYPE

STRAIGHT DECK WITH 1/2" WEDGE

4-Front Subframe

FRONT SUBFRAME

3-1/2" DEEP BOX BEAM DESIGN FRONT SUBFRAME RAISED 1-3/8"

FLUSH WITH TOP OF FLOOR

APPROACH PLATE

1/4" HIGH STRENGTH STEEL APPROACH PLATE

KINGPIN PLATE

3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE

KINGPIN TYPE

AAR HARDNESS CRUCIFORM KINGPIN

KINGPIN LOCATION

36" KINGPIN LOCATION

COVER PLATE

➡ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL

5-Support Legs

SUPPORT LEG LOCATION

SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN

SUPPORT LEG CRANK LOCATION

ROADSIDE SUPPORT LEG CRANK LOCATION

SUPPORT LEG BRACING

BOLT-ON CROSS BRACING WITH 7 GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL

SUPPORT LEGS

⊃ JOST MODEL A451 MAGNUM SUPPORT LEGS W/10-YR WARRANTY & 10"X10" ULTRA LOW PROFILE CUSHION FOOT

6-Frame, Rails & Crossmembers

BOTTOM RAILS

CROSSMEMBERS FRONT SUB TO LEGS

CROSSMEMBERS OVER SUPPORT LEGS

CROSSMEMBERS LEGS TO REAR SUB

CROSSMEMBERS OVER REAR **SUBFRAME**

10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS

2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE

(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON 12" C/L OVER SUPPORT LEGS

4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12" C/L LEGS TO REAR SUB

4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR **SUB**

7-Rear Subframe

HORIZONTAL DOCK BUMPER

RUBBER DOCK BUMPERS **VERTICAL &HORIZONTAL** BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER

⇒ (1) PAIR RUBBER DOCK BUMPERS 1/2" PROUD

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IIHS-30% OFFSET TEST

8-Suspension/Axles/Actuation

DOCK BUMPER

SLIDER SUSPENSION LOCATION

OIL SEALS

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL

AIR BRAKE CHAMBERS

AIR ACTUATION

SLACK ADJUSTERS

HUBODOMETER

DUST SHIELDS

BRAKE LINING STYLE

AXLE SPINDLE NUTS

END SYSTEM)

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

➡ STEMCO HUBODOMETER MTD R/S FRONT AXLE

⊃ DUST SHIELDS FOR 16-1/2" X 7" BRAKES

HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX CONMET SPINDLE NUT (INCL, W/ CONMET PRESET+ WHEEL END

SYSTEM)

HUB PILOTED SYS 10 STUD HUB PILOTED SYS W/OUTBRD CAST DRUMS W/16-1/2"X W/OUTBOARD DRUMS FOR 7"BRKS(STD W/CONMET PRESET+WHEEL END SYS) 16-1/2" X 7" BRAKES ANTILOCK BRAKE SYSTEMS BENDIX TABS-6 2S/1M ABS SYSTEM *W/O ROLL STABILITY* (ABS) WHEEL BEARING FACTORY CHOICE 80W-90 OIL LUBRICATION ANTI-DOCK WALK DEVICES ➡ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE WHEEL SEPARATOR PLATES ○ NYLON WHEEL GUARD SEPARATOR PLATE BTWN INNER WHEEL & HUB AXLE MANUFACTURER HENDRICKSON "VENTED" AXLES □ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END AXLE SPINDLE TYPE **SYSTEM** ⇒ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT AUTOMATIC TIRE INFLATION SYSTEM CORNER *RETAINS CONMET 8YR WARRANTY* LOAD SCALE KIT ➡ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX WHEEL BEARINGS (CONES) CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END AND RACES (CUPS) SYSTEM) MANUFACTURER HENDRICKSON AIRRIDE BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SYSTEMS WITH INTEGRAL SPRD, HD SLDR & ZERO MAINT DAMPING (ZMD) **AXLES** SLIDER PIN RELEASE HENDRICKSON OUIK DRAW AIR OPERATED SLIDER REPOSITIONING MECHANISM SYSTEM CONMET WHEEL END SYSTEMS BASE SPEC:CONMET PRESET+IRON HUB SYSTEM, INCL:CONMET PREMIUM SEAL, BEARING, SPACER & SPINDLE NUT 9-Front Wall FRONT CORNER POST .080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS FRONT WALL POSTS (4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL POSTS FRONT PANELS .040 ALUM FRONT PANELS SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET GLADHANDS & RECEPTACLE LOCATION 27-1/2" TO R/S FROM C/L OF TRAILER FRONT TOP RAIL EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL 10-Side Walls SIDE PANELS COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC

POLYURETHANE FOAM CORE BONDS INT/EXT PANELS)

SIDE POSTS

3/8" 14GA HIGH STR GALV HAT SHPD 24"C/L (FRT/RR SUB 16"C/L)

W/"A" SLOTS ON 8" VERT C/L

11-Roof

TOP RAILS

4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS

ROOF SKIN

.040 ONE PIECE ALUM COIL ROOF SKIN

ROOF BOWS

1-1/16" ANTI SNAG 18GA GALV STL HAT SHAPED ROOF BOWS

16"C/L(FRT/ RR SUB 24"C/L)BONDED TO ROOF SKN

12-Rear Doors

REAR DOOR TYPE

COMPOSITE REAR SWING DOORS

REAR DOOR PANELS

1/2" COMPOSITE REAR SWING DOORS (PRE-PAINTED WHITE GALV

STEEL PANELS W/POLYETHYLENE CORE)

REAR DOOR LOCK RODS

(1) REAR DOOR LOCK ROD PER DOOR

REAR DOOR HINGES

○ (1) ADDITIONAL PAIR OF REAR DOOR HINGES

HOLDBACKS

CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS

SATIN FINISH SST REAR DOOR CASE

REAR CASE & BUCKPLATE MATERIAL

GRAB HANDLE AT REAR OF

TRAILER

○ 36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S

DOOR

REAR TREADPLATE

.219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE

INTEGRAL WITH REAR BUCKPLATE

REAR DOOR HINGE MATERIAL

NON-POLISHED ALUMINUM

14-Floor

FLOOR TYPE

20,000LB 1-3/8"NOM LAM HDWD FLR; FACTORY CHOICE:OAK OR

SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM

FLOOR JOINT SEALANT

CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT

16-Lining

FRONT WALL LINING

.016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING

SIDE WALL LINING

PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING

WEARBAND

□ 14GA X 5/16" X 8" NOM GALV STL HD SIDEWALL WEARBAND FOR

USE WITH TALL BOTTOM RAIL (TBR)

WEARBAND ON FRONT

14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL

WEARBAND

SIDE WALL LINING CLOSURES

45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING

CLOSURES

17-Electrical System

MAIN HARNESS

UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH

INTERNAL GROUND AND 7-WAY PLUG

ELECTRICAL RECEPTACLE 7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED CLEARANCE LIGHT QUANTITY ■ 2-1-2-5 CLEARANCE LIGHT PACKAGE ADDITIONAL STOP/TAIL ONE ADDITIONAL STOP/TAIL LIGHT EACH SIDE WITH EXTENDED LIGHTS LIGHT PROTECTOR BAR GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON SIDE MOUNTED DIRECTIONAL **LIGHT** BRACKET BELOW BOTTOM RAIL EACH SIDE STOP/TAIL/TURN LIGHTS GROTE 4" L.E.D. (10-DIODE) STOP/ TAIL/TURN LIGHTS (2) PER SIDE WITH BLACK SNAP-IN FLANGE GROTE MICRONOVA L.E.D. LICENSE LIGHT LICENSE LIGHT CONSPICUITY TAPE LOCATION CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION FACTORY CHOICE CONSPICUITY TAPE CONSPICUITY TAPE **UPPER CLEARANCE LIGHTS** FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L LOWER CLEARANCE LIGHTS GROTE MICRONOVA LED PC RATED LIGHT ABS (ANTI-LOCK) WARNING GROTE MICRONOVA L.E.D. PC RATED LIGHT LIGHT STOP/TAIL/TURN LIGHT GROUPED STOP/TAIL/TURN LIGHTS CONFIGURATION REAR HEADER CLEARANCE GROTE MICRONOVA L.E.D. PC RATED GROMMET MOUNTED REAR LIGHTS HEADER ID/CLR LIGHTS 18-Finish Specifications TOP FRONT & TOP SIDE RAIL NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS **FINISH BOTTOM SIDE RAIL FINISH** NATURAL ALUM FINISH BOTTOM SIDE RAILS FRONT CORNER POST FINISH NATURAL ALUMINIUM FINISH FRONT CORNER POSTS FRONT PANEL FINISH PREPAINTED WHITE FRONT PANELS SIDE PANEL FINISH PREPAINTED WHITE SIDE PANELS

FRONT SUBFRAME ASSEMBLY FINISH

11111111

SUPPORT LEG FINISH

REAR SUBFRAME FINISH

REAR CASE FINISH

VRTCL & HORZNTL DOCK

BMPR FINISH

ROOF EXTERIOR FINISH

FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST

PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED

BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS

BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME

SATIN FINISH STAINLESS STEEL REAR CASE

ONTHAL INIDIA DIVINALEDOS SALEED REMIR ONSE

UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK

SCHARPF ON VERTICAL DOCK BUMPER

NATURAL ALUM ROOF EXTERIOR FINISH

REAR DOOR COLOR PREPAINTED WHITE REAR DOORS

FLOOR UNDERCOAT BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

19-Miscellaneous

MUDFLAP TYPE BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH

STEEL REINFORCING STRAPS

PERMIT HOLDER TRUCKLITE #97960 ROUND PERMIT HOLDER MOUNTED ON FRONT

WALL LOWER R/S

SIDE MOUNTED

BASE SPEC: USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE

AERODYNAMIC AIR

SKIRT MTD BELOW BOTTOM RAIL

20-Tires and Wheels

WHEELS

DEFLECTORS

22.5"X8.25"STANDARD WIDTH S 8 - 22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10

H/P#ULT397

22.5" LOW PROFILE TIRES 8 - 295/75R 22.5 MICH X-LINE ENERGY -T2 14PLY 39.70"T/D,LOAD

RG'G' MAX SPEED RATED@75 MPH;

Special Instructions

None.

Weight

Total Weight 13,147 lbs. (+/- 3%)

Terms & Conditions

Quote ID 894-1WIL081022-4245 2022-09-23 Page 7 of 7