

H 92739-92740



Order Date: 2022-10-05
 Quote Expires: 2022-10-15
 Serial Number: A3280-A3281 A3282-A3283
 Company: Ocean Trailer

Tyler Vickers
 FONTAINE SPECIALIZED
 5398 US Highway 11
 Springville, AL 35146
 2054671083
 tvickers@fontainespecialized.com

Please Fax back to this number with your authorization: 2054671083

Canadian Renegade 20C Air Tandem, 20 inch Loaded Deck Height, Mechanical Gooseneck (Model: RENEGADE 20C)	
RENXL40C*F*829542/AXR40**60RC	Est. Wt.: 18,323# +/- 3%
Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Length (Trailer Only): 47 feet 0 inches	
Width: 8 feet 6 inches	
Compatibility: Designed to accept optional flip box (gooseneck extension) and third flip axle	
Gooseneck Design: Mechanical removable with removable fifth wheel guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches	
Gooseneck Platform: Full-width gooseneck platform with 1 1/8 inch wood floor	
Tool Box: Lockable toolbox in riser portion of GN between MB	
Gooseneck Fenders: Aluminum fenders at rear of gooseneck	
Deck Design: Flat level deck design	
Deck Length: 29 ft clear deck length *EDR*	
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Recessed Floor Mounted D-Ring Package: 8 Pair of D-rings recess mounted in floor inboard of outside beams	
Crossmembers: On 12 inch centers	
Flooring: 1 3/8 inch nominal wood (full width)	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Front Bogie Ramp: Sloped steel bogie ramp (full width) with cleat bars	
Outriggers: 13 pair - 26 total outriggers, 1 pair 2 total heavy duty outriggers	
Number of Axles: 2 axles	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: Spring brakes (2 axles)	
Dust Shields: Dust shields on 2 axles	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride with automatic controls	
ABS: 4S/2M system without diagnostic tool and cable	
Load Scale: None Standard	
Wheels: 8.25 x 22.5 Lvl One buffed wheels	
Tires: 255/70R 22.5 H ply OEM Standard	
Hubometer: None Standard	
Tire Inflation: None Standard	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 40 inches	
Bumper: 3 tail light package	

