Trailer Specs

92804-92823 92849-92853

Customer:

Production No.

2024-U-0944-025

Factory of Production

UTAH

Shipping Instuctions

DEALER ARRANGED

Salesperson:

Purchase Order:

92829 - 92853

Quote No.

Warning Specifications have been modified by change notice.

SPECIFICATIONS BASE MODEL: VS3RA

DWG:

GVWR: 80,000 53'

OVERALL LENGTH: **OVERALL WIDTH:**

OVERALL HEIGHT: FIFTH WHL HT:

13' 6" 46 1/2 107 1/8 "

102 3/8"

POST HT FRONT: POST HT REAR: KINGPIN LOC:

107 1/8 " 36"

REAR SUSPENSION LOC:

SLIDER

REFRIG. UNIT PREP:

PRECEDNT C600

Option No.	Qty	Description	Unit Price	List Price
001-304-022		VS3RA DERIVED DESIGNATION (DERIVED FROM DUAL AXLE REEFER BASE SPECIFICATIONS/OPTIONS)		
001-376-029	The state of the s	80,000 LBS GVWR FOR USE W/(3) AXLE TRAILER	The comment of the sign of the content of the conte	
001-500-008		FRENCH/ENGLISH VIN LABEL REOD FOR IMPORT TO CANADA AND QAI CERTIFICATION		
001-664-005		TRAILER CONTAINS NON-HFC FOAM; MAY BE SOLD OR USED IN STATE W/ HFC RESTRICTION		
001-670-004	organization of the state of th	DQS UPDATE #179 (8/1/22)		
004-007-035		3GA (1/4" NOM) HIGH STRENGTH STEEL APPROACH PLATE (TWO PIECE CONSTRUCTION)		
005-097-XXX		3/4" SQUARE BAR WING PLATE REINF FOR FORE & AFT LOADS		
005-197-085		JOST MODEL A451 MAGNUM SUPP LEGS W/10-YR WARRANTY AND 10"X10" LOW PROFILE REMOVABLE CUSHION FOOT		
006-018-023		EXTRA HEAVY DUTY BOTTOM RAILS		
006-018-026		DO NOT NOTCH OUT BOTTOM RAIL AT REAR		
007-103-040		(1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD	***************************************	
007-107-070		DOT BMPR WELD-ON VERT & BOLT-ON NONSLIP HRZ 21"MAX GRND CLR,W/IN		

ΑI	vi		LESS 4"OAW EA SIDE FOR 7"BUMPER	
	008-111-033	T Dela Tital and Control of Contr	STEMCO HUBODOMETER MTD C/S REAR AXLE	
	008-112-026		DUST SHIELDS FOR 16-1/2" X 7" BRAKES FOR USE WITH TRIDEM	
	008-435-016		HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE	
	008-450-002		CALIBRATE HUBODOMETER IN KILOMETERS	
	008-487-035		P-SPINDLE TYPE FOR USE WITH TRIDEM & CONMET PRESET PLUS WHEEL END SYSTEM	
	008-499-047		HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRT CRNR FOR USE W/TRIDEM (RETAINS CNMT 8YR WRTY)	
	008-501-014		HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX	
	008-522-058		HENDRICKSON HKANT 69K23 TRIAXLE AIRRIDE/AXLE SYSTEM, 60" AXLE SPACING	
	009-549-037		PREP FOR TK PRECEDNT C600 SINGLE TEMP FRONT MOUNT REEFER UNIT WITHOUT ELECTRIC STANDBY	
	010-606-002		RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE	
	011-047-041		1" EXTRU ALUM "J" SHAPE ROOF BOWS ON 24" C/L	
	012-049-054		.040 TRANSLITE POLISHED ALUMINUM DIAMOND PATTERN REAR DOOR PANELS	
	012-051-032		(1) ADDITIONAL REAR DOOR LOCK ROD ON BOTH DOORS (TOTAL 4)	
	012-052-026		(5) REAR DOOR HINGES PER DOOR	
	012-053-036		6" X 16" REAR VENT W/STAINLESS STEEL COVER ON LOWER C/S (INCLUDES VENT OPENING SCREEN)	
	012-169-015		SHALLOW REAR WEDGE PORTION OF REAR SWING DOOR HEADER FROM 1-1/8" TO 1/2"	
	012-204-020		36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S DOOR	
	012-441-002		SST SWING REAR DOOR HINGE PINS	
	012-561-005	2.00	CORROSION RESIST ELECTROPOLISHED SST REAR DOOR HARDWARE SWING DRS (INCL NON-POLISHED ALUM HINGES)	
	014-057-283		20,000LBS 1-1/2" NOM EXTRUDED ALUM HIGH WEAR DUCT FLR KNURLED	
	015-064-037		1-1/2" SIDEWALL INSULATION	
	015-065-029		2" ROOF INSULATION	
	015-066-025		2" FLOOR INSULATION	
	016-074-125		6" EXTRA HEIGHT EXTRUDED ALUM STD DUTY WEARBAND TOTAL OF 16" INCL REINFORCING BEHIND WEARBAND	
	016-130-167	2.00	(1) ROW SERIES "E" GALV RECESS MTD LOG TRACK FOR USE W/1-1/2"	

AIV!		Offility Trailer Mig Co.
		SIDE WALL INSULATION
016-182-003	2.00	REINFORCE "A" OR "E" TYPE LOG TRACK FOR DOUBLE DECKING
017-077-161	An internal designation of the second	2-1-2-5 CLEARANCE LIGHT PACKAGE
017-133-024	The Article Control of	ONE ADDL STOP/TAIL LIGHT EACH SIDE ON SST BUCK PLATE WITH EXTENDED LIGHT PROTECTOR BAR
017-200-046	1.50	GROTE 4"DIA SST SNAP-IN FLANGE MTD LED(10 DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)
017-505-009	To constitute the same of the	TRUCKLITE MODEL 35 PC RATED LED UPPER SIDE RAIL CLEARANCE LIGHTS
017-506-034		CONVERT STD BTM RAIL LIGHTS TO GROTE TURTLEBACK II LED
017-613-006		(5) GROTE MICRONOVA L.E.D. P2 RATED MULTI-FUNCTION LIGHTS ON REAR SWING DOOR HEADER
018-194-002		CUST FURN DECALS INSTALLED BY UTM CONTRACTOR(EVALUATE POSSIBLE CONFLICT W/OPER/WARNING DECALS)
019-142-030		ALUMINUM LINE #2001 8" X 13" MANIFEST BOX MOUNTED ON R/S FRONT
019-143-023		TRUCKLITE #97960 ROUND PERMIT HOLDER MOUNTED ON FRONT WALL LOWER R/S
019-619-039		OMIT BASE SPEC UTM USS120A-4 AERODYNAMIC SIDESKIRTS
020-640-617	12.00	22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10 H/P#ULT397
020-647-439	12.00	11R 22.5 MICH XTE 14P 41.00"TIRE DIA.LOAD RANGE'G' MAX SPEED RATED @75 MPH;TRRL =<6.0

SPECIAL INSTRUCTIONS:

GROUP 10:

A) LOCATE RUB PROTECTOR @ APPROX 6" FROM TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR.

GROUP 16:

A) LOCATE REINFORCED E-TRACK @ THE FOLLOWING:

-(1) ROW OF E-TRACK @ 24" FROM TOP OF FLOOR TO C/L OF TRACK.

-(1) ROW OF E-TRACK @ 54" FROM TOP OF FLOOR TO C/L OF TRACK.

ATTENTION; PLEASE CAREFULLY REVIEW THIS INFORMATION AND IMMEDIATELY COMMUNICATE ANY DISCREPANCIES. Acknowledged by: JOSHUA REGUS

DIRECT 2/24/23 Prod Fcty: U PROPOSED VIN NUMBERS: 1UY VS3533 R20944 01 1UY VS3535 R20944 02 1UY VS3537 R20944 03 1UY VS3539 R20944 04 1UY VS3530 R20944 05 1UY VS3532 R20944 06 1UY VS3534 R20944 07 1UY VS3536 R20944 08 1UY VS3538 R20944 09 1UY VS3534 R20944 10 1UY VS3536 R20944 11 1UY VS3538 R20944 12 1UY VS353X R20944 13 1UY VS3531 R20944 14

2/21/23

1UY VS3535 R20944 16

1UY VS3539 R20944 18

1UY VS3537 R20944 20

1UY VS3530 R20944 19 https://www.utm.com/WEB-BIN/SIS012CN.PGM?&order=2024-U-0944

1UY VS3533 R20944 15

1UY VS3537 R20944 17

Line: 1

Utility Trailer Mfg Co.

1UY VS3539 R20944 21 1UY VS3532 R20944 23 1UY VS3536 R20944 25 1UY VS3530 R20944 22 1UY VS3534 R20944 24

This Trailer Production Order is executed pursuant to that Utility Trailer Manufacturing Company Dealer/Distributor Sales and Service Agreement entered into between Utility Trailer Manufacturing Company and Dealer. The Parties agree to conduct this transaction by electronic means and this electronically submitted Trailer Production Order shall be binding on the parties and their respective successors and assigns. In the event that Dealer intends to execute subsequent transactions using a method other than electronic submission, Dealer shall contact Utility Trailer Manufacturing Company.

If you believe that your vehicle has a defect which could cause injury or death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying UTILITY TRAILER MANUFACTURING COMPANY.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer or UTILITY TRAILER MANUFACTURING COMPANY.

To contact NHTSA, you may either call the Auto Safety Hotline toll-free at 1-800-424-9393 (or 366-0123 in Washington, D.C. area) or write to: NHTSA, U.S. Department of Transportation, Washington, D.C. 20590. You can also obtain other information about motor vehicle safety from the Hotline.