



# 92890-92892

Order Date: 2022-11-08

Order Number: 35557  
Reference: February  
Company: OCEAN TRAILER  
Don Aleksejus  
FONTAINE TRAILER  
430 Sam Letson Rd  
Haleyville AL 35565  
daleksejus@fontainetrailer.n

Order

## Canadian Velocity 53' Tridem Air Slider (Model: HBVSF22TAS)

Quantity:	3
<b>Overall Length:</b> 53 feet x 102 inches	
<b>Suspension Type:</b> Sliding air tridem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements	
<b>Frame Rating:</b> 100,000 lbs distributed- GAWR and tire ratings determine legal payloads	
<b>Flooring:</b> 1 1/8 inch wood	
<b>Crossmembers:</b> 12 Inch centers - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers	
<b>Pipe Spools:</b> Double between stake pockets	
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel	
<b>Main Beams:</b> 130K load bearing flanges	
<b>Kingpin:</b> 24 inches; 5/16" Plate	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkhead Pockets:</b> None standard	
<b>Number of Axles:</b> 3 Intraax	
<b>Axle Position:</b> 96 Inch adjustable	
<b>Axle Spread:</b> 60 inches, 60 inches -- Kingpin to C/L Rear Axle: 39 feet 4 3/4 inches in front position- 47 feet 4 3/4 inches in rear	
<b>Axle Spindle:</b> Parallel (Straight)	
<b>Dust Shields:</b> Installed on all axles	
<b>Brakes:</b> TSE Spring brakes, Haldex auto slacks	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> Meritor Wabco 4S/2M - no cable or tool	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums (Webb)	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - 12 pre-painted white - STANDARD	
<b>Tires:</b> 11R 22.5 14PR OEM standard tires -- quantity 12 -- STANDARD	
<b>Tire Brand:</b> OEM standard	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> Hendrickson AAZNT69K Intraax air ride slider with ride height limiters- 96 inch adjustable; (1) Removable slide position stop bar	
<b>Air Assist Slide Box Plns:</b> Controls mounted inside box on front of slider box	
<b>Manual Dump Valve:</b> Standard	
<b>Air Load Scale:</b> Installed	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 3 lights/side, 3 lights/side on rear	
<b>Other Electrical Specifications:</b> 3 4-way sockets with one hot/one ground pin for wide load and strobe light connections: 1 rear, 1 ea. side at rear	
<b>Paint:</b> Black urethane with Velocity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements	
<b>Mudflaps:</b> 1 set OEM standard	
<b>Spare Tire Carrier:</b> None standard	
<b>Side Mounted Winches:</b> 26 standard - without straps: 13 per side-three bar type	
<b>Special J Hooks:</b> 26 total - 13 per side-opposite winches	
<b>Tarp Hooks:</b> 2 foot centers on all slides when possible: undermount rs/cs: side mount front/back	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> Install registration holder - Tite Seal	
<b>Tool Box:</b> 1 aluminum double door box - 18 inches x 24 inches x 60 inches - installed Road Side	
<b>Tow Hooks:</b> 1 Installed on rear	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	
<b>Please Note:</b> Price Includes commodity surcharges	
<b>Unit Numbers &amp; Decals:</b> Not available	
<b>Stacking:</b> Price Includes Standard stacking of each trailer	