



PO# 94631-94639

Order Date: 2023-02-09

Order Number: 35827
 Reference: MayJune
 Company: OCEAN TRAILER
 Don Aleksejus
 FONTAINE TRAILER
 430 Sam Letson Rd
 Haleyville AL 35565
 daleksejus@fontainetrailer.ne

**Canadian Velocity Drop Deck 53' Tridem Air Ride
 (Model: HBVSD22TAF)**

9

Quantity:	
Overall Length: 53 feet x 102 Inches	
Suspension Type: Tri-axle air	
Deck Lengths: 11 feet front and 42 feet rear	
Frame Rating: 100,000 lbs distributed- GAWR and tire ratings determine legal payloads	
Rear Deck Height: 40 inches - loaded	
Flooring: 1 1/8 inch wood	
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Pipe Spools: Double between stake pockets	
Rubrail: 3/8 inch x 2 1/2 inch steel	
Main Beams: 130K load bearing flanges	
Kingpin: 18 inches; 5/16" Plate	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets: None standard	
Number of Axles: 3 Intraax	
Axle Position: Fixed	
Axle Spread: 60 inches, 60 inches -- kingpin to center axle 40 feet 10 7/8 inches -- center axle to rear 126 1/8 inches	
Axle Spindle: Parallel (Straight)	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: Meritor Wabco 4S/2M - no cable or tool	
Hub and Drums: 10-hole hub-piloted with outboard cast drums (Webb)	
Dust Shields: dust shields installed on all axles	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - 12 pre-painted white - STANDARD	
Tires: 255/70R 22.5 16PR - quantity 12 OEM standard	
Tire Inflation System: None standard	
Suspension Detail: AANL23K Intraax air ride	
Manual Dump Valve: Installed Inside Box with Liquid Filled Load Gauge	
Air Lift: None Standard	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 3 lights/side on rear	
Other Electrical Specifications: (5) 4 way sockets with one hot/one ground pin each for wide load and strobe light connections: 1 on rear, 2 each side	
Air Load Scale: Installed	
Paint: Black urethane with Velocity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed on rubrails	
Bumper: Weld-on type - meets underride requirements	
Mudflaps: 1 set OEM standard	
Side Mounted Winches: 26 standard - without straps; 13 per side-three bar type	
Special J Hooks: 26 total - 13 per side-opposite winches	
Tarp Hooks: 2 foot centers on all sides when possible; undermount rs/cs: side mount front/back	
Dock Bumpers: 1 pair rubber on rear	
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams	
Hubodometer: None standard	
Registration Holder: Install registration holder - Tite Seal	
Tool Box: 1 aluminum double door box - 18 inches x 18 inches x 60 inches - Installed Road Side	
Tow Hooks: 1 Installed on rear	
VIN Plate: Bilingual US/Canadian VIN plate	
Please Note: Price includes commodity surcharges	
Unit Numbers & Decals: Not available	
Stacking: Price Includes Standard stacking of each trailer	

Estimated Weight (lbs) (+/- 3%)

14425