



PO# 94916-94930

Order Date: 2023-03-17

Order Number: 35980  
Reference: revised3Q  
Company: OCEAN TRAILER  
Don Aleksejus  
FONTAINE TRAILER  
430 Sam Letson Rd  
Haleyville AL 35565  
daleksejus@fontainetrailer.ne

**Canadian Velocity Drop Deck 53' Tridem Air Ride  
(Model: HBVSD22TAF)**

Quantity:	15
<b>Overall Length:</b> 53 feet x 102 Inches	
<b>Suspension Type:</b> Tri-axle air	
<b>Deck Lengths:</b> 11 feet front and 42 feet rear	
<b>Frame Rating:</b> 100,000 lbs distributed- GAWR and tire ratings determine legal payloads	
<b>Rear Deck Height:</b> 40 inches - loaded	
<b>Flooring:</b> 1 1/8 inch wood	
<b>Crossmembers:</b> 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers	
<b>Pipe Spools:</b> Double between stake pockets	
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel	
<b>Main Beams:</b> 130K load bearing flanges	
<b>Kingpin:</b> 18 inches; 5/16" Plate	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkhead Pockets:</b> None standard	
<b>Number of Axles:</b> 3 Intraax	
<b>Axle Position:</b> Fixed	
<b>Axle Spread:</b> 60 inches, 60 inches -- kingpin to center axle 40 feet 10 7/8 inches -- center axle to rear 126 1/8 inches	
<b>Axle Spindle:</b> Parallel (Straight)	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> Meritor Wabco 4S/2M - no cable or tool	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums (Webb)	
<b>Dust Shields:</b> dust shields installed on all axles	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - 12 pre-painted white - STANDARD	
<b>Tires:</b> 255/70R 22.5 16PR - quantity 12 OEM standard	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> AANL23K Intraax air ride	
<b>Manual Dump Valve:</b> Installed Inside Box with Liquid Filled Load Gauge	
<b>Air Lift:</b> None Standard	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 3 lights/side, 3 lights/side on rear	
<b>Other Electrical Specifications:</b> (5) 4 way sockets with one hot/one ground pin each for wide load and strobe light connections: 1 on rear, 2 each side	
<b>Air Load Scale:</b> Installed	
<b>Paint:</b> Black urethane with Velocity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements	
<b>Mudflaps:</b> 1 set OEM standard	
<b>Side Mounted Winches:</b> 26 standard - without straps: 13 per side-three bar type	
<b>Special J Hooks:</b> 26 total - 13 per side-opposite winches	
<b>Tarp Hooks:</b> 2 foot centers on all sides when possible: undermount rs/cs: side mount front/back	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Spare Tire Carrier:</b> 1 standard - mounted between lower gooseneck beams	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> Install registration holder - Tite Seal	
<b>Tool Box:</b> 1 aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side	
<b>Tow Hooks:</b> 1 Installed on rear	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	
<b>Please Note:</b> Price includes commodity surcharges	
<b>Unit Numbers &amp; Decals:</b> Not available	
<b>Stacking:</b> Price includes Standard stacking of each trailer	

EST WEIGHT 14,425