

Trailer Specs

Customer:		Production No.	2024-U-2353-008
		Factory of Production	UTAH
Dealer:	CENTER DIVIDE MULTI TEMPS	Shipping Instructions	DEALER ARRANGED
Salesperson:	894 DELTA,BC		
Purchase Order:	94996 - 95003		
Quote No.:	CA-72423		

SPECIFICATIONS

BASE MODEL: VS2RA
QUANTITY: 8

DWG: PB-???

GWWR: 65,000

OVERALL LENGTH:	53'
OVERALL WIDTH:	102 3/8"
OVERALL HEIGHT:	13' 6"
FIFTH WHL HT:	46 1/2
POST HT FRONT:	107 1/8 "
POST HT REAR:	107 1/8 "
KINGPIN LOC:	36"
REAR SUSPENSION LOC:	SLIDER
REFRIG. UNIT PREP:	LRG FRONT UNIT

Option No.	Qty	Description	Unit Price	List Price
001-304-012		CENTERSEAL OPERATION		
001-500-008		FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION		
001-664-005		TRAILER CONTAINS NON-HFC FOAM; MAY BE SOLD OR USED IN STATE W/ HFC RESTRICTION		
001-670-006		DQS UPDATE #181 (2/10/23)		
005-197-117		JOST MODEL H451 MAGNUM SUPP LEGS W/10-YR WARRANTY AND 10"X10" CUSHION FOOT		
006-018-026		DO NOT NOTCH OUT BOTTOM RAIL AT REAR		
007-103-040		(1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD		
007-107-070		DOT BMPR WELD-ON VERT & BOLT-ON NONSLIP HRZ 21"MAX GRND CLR,W/IN LESS 4"OAW EA SIDE FOR 7"BUMPER		
008-350-163		BENDIX TABS-6 2S/1M ABS *W/O ROLL STABILITY*		
008-393-020		MOBILITH SHC007 SYNTH SEMI-FLUID GREASE W/ 1YR/100,000 MILE SERVICE INTERVAL		
008-487-033		P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM		

008-499-023		HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
008-501-014		HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
010-606-001		RUB PROTECTRS(EXT S/WALL)EXTR AL W/END CAPS;(1)BELOW TOP RAIL(1) ABOVE BOT RAIL FULL LGTH EA SIDE
011-047-041		1" EXTRU ALUM "J" SHAPE ROOF BOWS ON 24" C/L
012-051-030		(1) ADDL REAR DOOR LOCKROD ON CURBSIDE FOR A TOTAL OF (3)
012-052-026		(5) REAR DOOR HINGES PER DOOR
012-169-015		SHALLOW REAR WEDGE PORTION OF REAR SWING DOOR HEADER FROM 1-1/8" TO 1/2"
012-204-020		36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S DOOR
014-430-003		2" WIDE LONGITUDINAL TROUGH IN CENTER OF FLOOR WITHOUT THERMAL BREAK
015-066-025		2" FLOOR INSULATION
016-071-095		.085 (NOM) VERSITEX-UTILITY VR3U SIDE WALL LINING ***SEE NOTES FOR DISCLAIMER***
016-074-125		6" EXTRA HEIGHT EXTRUDED ALUM STD DUTY WEARBAND TOTAL OF 16" INCL REINFORCING BEHIND WEARBAND
016-130-158	2.00	(1) ROW SERIES "E" GALV RECESS MTD LOG TRACK ON SIDE WALLS
016-366-009		16" HIGH X 1/8" SMOOTH ALUM WEARBAND W/BEVELED EDGES ON REAR SWING DOORS INCL HARDWOOD REINF
016-515-001		2" WIDE LONGITUDINAL TROUGH IN CENTER OF CEILING W/HDWD REINF (INCLS HAT CARLINS ON 24" C/L)
017-077-161		2-1-2-5 CLEARANCE LIGHT PACKAGE
017-077-202		SIDE RR CLR LTS ON BTM RAIL. ABS LT ON RR GUSSET; CLR LTS ARE IN VERT ALIGNMENT W/TOP SIDE RR LTS
017-505-006		GROTE SUPERNOVA THIN-LINE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L
017-613-006		(5) GROTE MICRONOVA L.E.D. P2 RATED MULTI-FUNCTION LIGHTS ON REAR SWING DOOR HEADER
019-095-068		BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS
019-143-023		TRUCKLITE #97960 ROUND PERMIT HOLDER MOUNTED ON FRONT WALL LOWER R/S
019-191-008	2.00	(4) LABELMASTER #80-SM NATURAL ALUMINUM PLACARD HOLDERS W/O PLACARDS
019-619-039		OMIT BASE SPEC UTM USS120A-4 AERODYNAMIC SIDESKIRTS
020-640-617	8.00	22.5X8.25 ALCOA HIGH POLISH

ULTRA ONE ALUMINUM 10 H/P#ULT397

020-647-439

8.00

11R 22.5 MICH XTE 14P
41.00" TIRE DIA. LOAD RANGE 'G' MAX
SPEED RATED @75 MPH; TRRL =<6.0

SPECIAL INSTRUCTIONS:

GROUP 1:

A) CEILING TROUGH TO EXTEND 626" REARWARD FROM INSIDE FRONT WALL

GROUP 10:

A) LOCATE RUB PROTECTORS APPROX. 14" FROM TOP OF BOTTOM RAIL TO C/L OF RUB RAIL AND APPROX. 18" FROM BOTTOM OF TOP RAIL TO C/L OF RUB RAIL

GROUP 16:

A) LOCATE "E" TRACK AT 30" AND 60" FROM TOP OF FLOOR TO C/L OF TRACK

GROUP 19:

A) (2) SETS OF PLACARD HOLDERS TO BE SIDE BY SIDE @ UTM STANDARD LOCATIONS ON FRONT WALL & SIDE WALLS.

(2) REAR DOOR PLACARD HOLDERS TO BE LOCATED AS FOLLOWS:

(1) ON R/S REAR DOOR & (1) ON C/S REAR DOOR.

ATTENTION;
PLEASE CAREFULLY REVIEW THIS INFORMATION AND IMMEDIATELY COMMUNICATE ANY DISCREPANCIES.

Acknowledged by: BOBBY MALANCHE
DIRECT

4/25/23
5/03/23

Prod Fcty: U Line: 2

PROPOSED VIN NUMBERS:

1UY VS2531 R22353 01	1UY VS2533 R22353 02
1UY VS2535 R22353 03	1UY VS2537 R22353 04
1UY VS2539 R22353 05	1UY VS2530 R22353 06
1UY VS2532 R22353 07	1UY VS2534 R22353 08

This Trailer Production Order is executed pursuant to that Utility Trailer Manufacturing Company Dealer/Distributor Sales and Service Agreement entered into between Utility Trailer Manufacturing Company and Dealer. The Parties agree to conduct this transaction by electronic means and this electronically submitted Trailer Production Order shall be binding on the parties and their respective successors and assigns. In the event that Dealer intends to execute subsequent transactions using a method other than electronic submission, Dealer shall contact Utility Trailer Manufacturing Company.

If you believe that your vehicle has a defect which could cause injury or death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying UTILITY TRAILER MANUFACTURING COMPANY.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer or UTILITY TRAILER MANUFACTURING COMPANY.

To contact NHTSA, you may either call the Auto Safety Hotline toll-free at 1-800-424-9393 (or 366-0123 in Washington, D.C. area) or write to: NHTSA, U.S. Department of Transportation, Washington, D.C. 20590. You can also obtain other information about motor vehicle safety from the Hotline.