



The First Name In Trailers

OCEAN TRAILER

CHRIS DAVIDCHUK
15205 131 AVE NW
EDMONTON, AB T5V 0A4
Voice 780-447-7373

Trailer Quote Prepared For

Ocean Stock

, T5V0A4

20 - VS2DX
December 22, 2023

Specifications (☞ = Option to Base Model)

1-Model & Payload Capacity

<i>MODEL</i>	VS2DX
<i>PAYLOAD CAPACITY</i>	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
<i>GROSS VEHICLE WEIGHT RATING</i>	65,000 LBS GVWR
<i>INTERNATIONAL IMPORTATION SPECIFICATIONS</i>	☞ FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION
<i>4000D-X100.25 SYSTEM</i>	☞ 4000D-X100.25 SIDEWALL SYS INCLS 3/4" 14GA & 18GA STEEL HAT SHPD POSTS W/"A" SLOTS ON 4" C/L
<i>GREENHOUSE GAS COMPLIANCE</i>	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
<i>DQS UPDATE NUMBER</i>	DQS UPDATE #184 (11/01/23)

2-Dimensions

<i>LENGTH</i>	53'0" OVERALL LENGTH
<i>OVERALL HEIGHT</i>	13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST HEIGHT
<i>WIDTH</i>	102-3/8" OVERALL WIDTH
<i>INSIDE HEIGHT</i>	110-1/2" INSIDE HEIGHT AT FRONT; 111" INSIDE HEIGHT AT REAR
<i>INSIDE WIDTH</i>	☞ **NOTE** 100" (+/- 1/4")inside width at wearband, 100-1/4" at lining (+/- 1/4")

3-Deck

<i>DECK TYPE</i>	STRAIGHT DECK WITH 1/2" WEDGE
------------------	-------------------------------

4-Front Subframe

<i>FRONT SUBFRAME</i>	3-1/2" DEEP BOX BEAM DESIGN FRONT SUBFRAME RAISED 1-3/8" FLUSH WITH TOP OF FLOOR
<i>APPROACH PLATE</i>	8 GA CARBON STEEL FULL WIDTH APPROACH PLATE
<i>KINGPIN PLATE</i>	3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
<i>KINGPIN TYPE</i>	AAR HARDNESS CRUCIFORM KINGPIN
<i>KINGPIN LOCATION</i>	36" KINGPIN LOCATION
<i>COVER PLATE</i>	☞ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL

5-Support Legs

<i>SUPPORT LEG LOCATION</i>	SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN
<i>SUPPORT LEG CRANK LOCATION</i>	ROADSIDE SUPPORT LEG CRANK LOCATION

SUPPORT LEG BRACING

BOLT-ON CROSS BRACING WITH 7 GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL

SUPPORT LEGS

JOST A401 ENHANCED 50,000 LBS CAPACITY SUPPORT LEGS W/10"X10" ULTRA LOW PROFILE CUSHION FOOT

6-Frame, Rails & Crossmembers

BOTTOM RAILS

10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS

CROSSMEMBERS FRONT SUB TO LEGS

2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE

CROSSMEMBERS OVER SUPPORT LEGS

(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON 12" C/L OVER SUPPORT LEGS

CROSSMEMBERS LEGS TO REAR SUB

4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12" C/L LEGS TO REAR SUB

CROSSMEMBERS OVER REAR SUBFRAME

4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR SUB

PREP FOR FUEL TANK FOR USE WITH SIDE SKIRTS

➤ 50 GAL FUEL TANK PREP, LAST (2) CMEM OVER LEGS & 1ST CMEM IN BAY AREA PUNCHED FOR TANK

7-Rear Subframe

HORIZONTAL DOCK BUMPER

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER

PINTLE HOOK

➤ PREMIER #2200L PINTLE HOOK WITH TYPE 30 CHAMBERS, QUICK GUIDES & REINF FOR SUPER DOUBLES

RUBBER DOCK BUMPERS

➤ (1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD

VERTICAL &HORIZONTAL DOCK BUMPER

➤ DOT BMPR WELD-ON VERT & BOLT-ON NONSLIP HRZ 21"MAX GRND CLR,W/IN LESS 4"OAW EA SIDE FOR 7"BUMPER

VERTICAL &HORIZONTAL DOCK BUMPER

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IIHS-30% OFFSET TEST

8-Suspension/Axles/Actuation

SLIDER SUSPENSION LOCATION

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL

OIL SEALS

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)

AIR BRAKE CHAMBERS

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

AIR ACTUATION

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

SLACK ADJUSTERS

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

HUBODOMETER

➤ STEMCO HUBODOMETER MTD ON AXLE

DUST SHIELDS

➤ DUST SHIELDS FOR 16-1/2" X 7" BRAKES

<i>AIRRIDE DUMP VALVES</i>	HENDRICKSON AUTOMATIC DUMP VALVE
<i>BRAKE LINING STYLE</i>	HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX
<i>AXLE SPINDLE NUTS</i>	CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HUB PILOTED SYS W/OUTBOARD DRUMS FOR 16-1/2" X 7" BRAKES</i>	10 STUD HUB PILOTED SYS W/OUTBRD CAST DRUMS W/16-1/2"X 7"BRKS(STD W/CONMET PRESET+WHEEL END SYS)
<i>ANTILOCK BRAKE SYSTEMS (ABS)</i>	BENDIX TABS-6 2S/1M ABS SYSTEM *W/O ROLL STABILITY*
<i>WHEEL BEARING LUBRICATION</i>	FACTORY CHOICE 80W-90 OIL
<i>ANTI-DOCK WALK DEVICES</i>	☞ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE
<i>WHEEL SEPARATOR PLATES</i>	☞ NYLON WHEEL GUARD SEPARATOR PLATE BTWN INNER WHEEL & HUB
<i>AXLE MANUFACTURER</i>	HENDRICKSON "VENTED" AXLES
<i>AXLE SPINDLE TYPE</i>	☞ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM
<i>AUTOMATIC TIRE INFLATION SYSTEM</i>	☞ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
<i>LOAD SCALE KIT</i>	☞ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
<i>WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER</i>	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HENDRICKSON AIRRIDE SYSTEMS WITH INTEGRAL AXLES</i>	BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)
<i>SLIDER PIN RELEASE MECHANISM</i>	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
<i>CONMET WHEEL END SYSTEMS</i>	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT

9-Front Wall

<i>FRONT CORNER POST</i>	.080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS
<i>FRONT WALL POSTS</i>	(4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL POSTS
<i>FRONT PANELS</i>	.040 ALUM FRONT PANELS
<i>GLADHANDS & RECEPTACLE LOCATION</i>	SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET 27-1/2" TO R/S FROM C/L OF TRAILER
<i>FRONT TOP RAIL</i>	EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL

*FRONT WALL HEATER UNIT
PREPARATION*

- ☞ PREP FOR FRT MT THERMO KING HEAT KING450;INCL PPW POLYCORE FRONT WALL LINING & STEEL BANG PLATE

10-Side Walls

SIDE PANELS

COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC POLYURETHANE FOAM CORE BONDS INT/EXT PANELS)

SIDE POSTS

- ☞ ****NOTE**** 3/4" 14GA & 18GA STL HAT SHPD POST W/A SLOTS ON 4" C/L

*EXTERIOR SIDE WALL
PROTECTION*

- ☞ RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE
REQUIRED INFORMATION:

Dealer must specify location of (1) rub protector c/l of rub rail to top of bottom rail and location of (1) rub protector c/l of rub protector to bottom of top rail.

>> LOCATE RUB PROTECTOR (EXT S/WALL) APPROX 6" FROM TOP OF RUB RAIL TO C/L OF RUB PROTECTOR

*EXTERIOR SIDE WALL
PROTECTION*

- ☞ LOCATE RUB PROTECTOR (EXT S/WALL) APPROX 6" FROM TOP OF RUB RAIL TO C/L OF RUB PROTECTOR

11-Roof

TOP RAILS

4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS

ROOF SKIN

.040 ONE PIECE ALUM COIL ROOF SKIN

ROOF BOWS

1-1/16" ANTI SNAG 18GA GALV STL HAT SHAPED ROOF BOWS
16"C/L(FRT/ RR SUB 24"C/L)BONDED TO ROOF SKN

12-Rear Doors

REAR DOOR TYPE

COMPOSITE REAR SWING DOORS

REAR DOOR PANELS

1/2" COMPOSITE REAR SWING DOORS (PRE-PAINTED WHITE GALV STEEL PANELS W/POLYETHYLENE CORE)

REAR DOOR LOCK RODS

(1) REAR DOOR LOCK ROD PER DOOR

REAR DOOR HINGES

- ☞ REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT

REAR DOOR HINGES

- ☞ (1) ADDITIONAL PAIR OF REAR DOOR HINGES

HOLDBACKS

CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS

*REAR CASE & BUCKPLATE
MATERIAL*

SATIN FINISH SST REAR DOOR CASE

*GRAB HANDLE AT REAR OF
TRAILER*

- ☞ 36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S DOOR

REAR TREADPLATE

.219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE INTEGRAL WITH REAR BUCKPLATE

REAR DOOR HINGE MATERIAL

NON-POLISHED ALUMINUM

14-Floor

FLOOR TYPE 20,000LB 1-3/8"NOM LAM HDWD FLR; FACTORY CHOICE:OAK OR SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM

FLOOR JOINT SEALANT CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT

15-Insulation

FRONT WALL THICKNESS ➤ POLYSTYRENE FOAM BLOCK INSULATION ON FRONT WALL

SIDE WALL THICKNESS ➤ ADDITIONAL POLYURETHANE FOAM BETWEEN 24" C/L SIDE WALL POST SPACING (THIN WALL DESIGN ONLY)

ROOF THICKNESS ➤ POLY FOAM BLOCK INSULATION IN ROOF FULL WIDTH FOR USE WITH VERSITEX CEILING LINING

16-Lining

FRONT WALL LINING .016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING

SIDE WALL LINING PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING

ROOF LINING ➤ .100 NOM VERSITEX VX4 CEILING LINING FULL WIDTH;INCL.HEAVY DTY 14GA STEEL HAT ROOF BOWS

WEARBAND 18GA 12" HIGH CORRUGATED STEEL SURFACE MTD WEARBAND

WEARBAND ON FRONT 14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL WEARBAND

SIDE WALL LINING CLOSURES 45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING CLOSURES

SIDEWALL LINING/POST MODIFICATION ➤ (1) FOAM POST PLUG IN EA SIDE POST BELOW THE LOWEST "A" SLOT FOR USE W/ 3/4" POSTS (DX-100)

17-Electrical System

MAIN HARNESS UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH INTERNAL GROUND AND 7-WAY PLUG

ELECTRICAL RECEPTACLE 7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED

CLEARANCE LIGHT QUANTITY ➤ 2-1-2-5 CLEARANCE LIGHT PACKAGE

ADDITIONAL STOP/TAIL LIGHTS ➤ ONE ADDITIONAL STOP/TAIL LIGHT EACH SIDE WITH EXTENDED LIGHT PROTECTOR BAR

SIDE MOUNTED DIRECTIONAL LIGHT GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE

STOP/TAIL/TURN LIGHTS ➤ GROTE 4" DIA SST SNAP-IN FLANGE FOR ADDITIONAL STOP/TAIL LIGHT

STOP/TAIL/TURN LIGHTS ➤ GROTE 4"DIA SST SNAP-IN FLANGE MTD LED(10 DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)

LICENSE LIGHT GROTE MICRONOVA L.E.D. LICENSE LIGHT

CONSPICUITY TAPE LOCATION CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION

CONSPICUITY TAPE

FACTORY CHOICE CONSPICUITY TAPE

UPPER CLEARANCE LIGHTS

☞ GROTE SUPERNOVA THIN-LINE LED PC RATED UPPER SIDE RAIL CLEARANCE LIGHTS W/3" MOUNTING HOLE C/L

LOWER CLEARANCE LIGHTS

GROTE MICRONOVA LED PC RATED LIGHT

ABS (ANTI-LOCK) WARNING LIGHT

GROTE MICRONOVA L.E.D. PC RATED LIGHT

STOP/TAIL/TURN LIGHT CONFIGURATION

GROUPED STOP/TAIL/TURN LIGHTS

REAR HEADER CLEARANCE LIGHTS

GROTE MICRONOVA L.E.D. PC RATED GROMMET MOUNTED REAR HEADER ID/ CLR LIGHTS

18-Finish Specifications

TOP FRONT & TOP SIDE RAIL FINISH

NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS

BOTTOM SIDE RAIL FINISH

NATURAL ALUM FINISH BOTTOM SIDE RAILS

FRONT CORNER POST FINISH

NATURAL ALUMINIUM FINISH FRONT CORNER POSTS

FRONT PANEL FINISH

PREPAINTED WHITE FRONT PANELS

SIDE PANEL FINISH

PREPAINTED WHITE SIDE PANELS

FRONT SUBFRAME ASSEMBLY FINISH

FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED

SUPPORT LEG FINISH

BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS

REAR SUBFRAME FINISH

BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME

REAR CASE FINISH

SATIN FINISH STAINLESS STEEL REAR CASE

VRTCL & HORZNTL DOCK BMPR FINISH

UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK SCHARPF ON VERTICAL DOCK BUMPER

ROOF EXTERIOR FINISH

NATURAL ALUM ROOF EXTERIOR FINISH

REAR DOOR COLOR

PREPAINTED WHITE REAR DOORS

FLOOR UNDERCOAT

BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

19-Miscellaneous

MUDFLAP TYPE

BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS

PERMIT HOLDER

☞ BETTS PS-1 ROUND PERMIT HOLDER MTD ON FRONT WALL
REQUIRED INFORMATION:
Dealer must specify location of permit/document/registration holder on either R/S, C/S or C/L in special instructions unless otherwise stated in the option description.
>> ROUND PERMIT HOLDER MOUNTED ON FRONT WALL
LOWER R/S

*SIDE MOUNTED
AERODYNAMIC AIR
DEFLECTORS*

BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE
SKIRT MTD BELOW BOTTOM RAIL

20-Tires and Wheels

*22.5"X8.25"STANDARD WIDTH
WHEELS*

☞ 8 - 22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10H/P
#ULT367

*22.5" STANDARD PROFILE
TIRES*

☞ 8 - 11R 22.5 MICH XTE 14P 41.00" TIRE DIA. LOAD RANGE 'G' MAX
SPEED RATED @75 MPH; TRRL =<6.0

Special Instructions

None.

Weight

Total Weight 13,998 lbs. (+/- 3%)

Terms & Conditions