



For all Quotations, pricing valid for 10 days from date of quotation, thereafter subject to change without notice. For all Orders, prices shown are not firm-fixed. Prices will be reassessed ten (10) weeks prior to order completion date and modified, if deemed necessary. Order cancellations must be received no later than nine (9) weeks prior to order completion date.
 Credit Terms: all Orders are subject to Fontaine's current terms and conditions of sale. Go to Terms and Conditions for details.

Order Date: 09-05-2024
Serial Number: A5298-A5309

PO: 96447-96458 **Company: Ocean Trailer**

Tyler Vickers
 Fontaine Trailer - Heavy Haul
 5398 US Highway 11
 Springville, AL 35146
 205-467-6171
 tvickers@fontaineheavyhaul.com

Please Fax back to this number with your authorization: 205.467.2962

Xcalibur Step Deck Extendable 51' - 71.5' Air Ride Tridem	Pr ile (Canadian)
	Est. Wt.: 23,070# +/- 3%
Length / Width: 11 feet upper and 40 feet lower /OAL 51 feet closed to 71.5 feet open - adjustable with locks approx. every 5 feet - 102 inches wide	
Suspension Type: Fixed Tridem	
Frame Rating: 80,000 lbs distributed - self-supporting, properly blocked	
Dead Roll: Located at edge of drop, 3 inch pipe 0.60 thickness	
Flooring: Steel decking over wheels, 1 1/4" Apitong over center section bogie	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers with double pipe spools	
Rubrail: 2 1/2 inch rolled formed steel	
Pin Pockets: (13) sets of round pin pockets to include 2 sets at the live roll mounted at 45 and 90 degrees, 1 set at dead roll mounted at 45 degrees	
Outriggers: (4) Sets - minimum 3/8" wall thickness 102 " length	
Main Beams: Minimum grade 80 flanges	
Air and Electrical @ Extension Locks: Inside track system	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: Holland Mark V with oversize sand shoes	
Bulkheads: None standard	
Bulkhead Pockets: None Standard	
Number of Axles: 3	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Dust Shields: None due to low profile design	
ABS: 4S/2M - no cable or tool	
Axle Spread: 60 inches	
Hub and Drums: 8-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs	
Wheels: 17.5 x 6.75 steel disc wheels - pre-painted white - Tires 235/75R 17.5	
Suspension Detail: Hendrickson air ride	
Dump Valve: Manual dump valve, ride height over-ride control and liquid filled air gauge in box	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 3 lights/side on rear , 3 marker lights rear, Four 4-way plugs two at the drop and two at the rear web for pull out lights.	
Wide Load Lights - 2 Pair (One set at gooseneck, second set at bogie)	
Paint: Black urethane - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Tool Box: None standard	
Mudflaps: 1 set Fontaine	
Side Mounted Winches: 16 standard - without straps: three bar type	
Special J Hooks: 16 total -opposite winches	
Deck Extension Lock/Air Chamber side impact guard	
Winch Straps: None standard	
Deck Lift-Air Controlled-Front of outer deck	
Live Roll: 7 inch live roll located at top of rear border with SKF bearings set live roll in floor of deck	
Air Operated, Clock Wise rotation only	
Liquid Filled Gauge: Included in dump valve box	
VIN Plate: Bilingual VIN plate	

