



Quote Date: 2024-08-21
Quote Expires: 2024-08-31
Quote Number: 3010178
Serial Number: A5282-A5285 A5286-A5289
PO: 96459-96462
Company: Ocean Trailer

Tyler Vickers
 FONTAINE SPECIALIZED
 5398 US Highway 11
 Springville, AL 35146
 2054671083
 tvickers@fontainespecialized.com

Please Fax back to this number with your authorization: 2054671083

Canadian Renegade X20C Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, Mechanical Gooseneck (Model: RENEGADE X20C)	
RENLXT40CF*828602/AXR40**60RC	Est. Wt.: 22,775# +/- 3%
TRAILER - GENERAL	
Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Length (Trailer Only): 47 feet 3 inches	
Width: 8 feet 6 inches	
Compatibility: Designed to accept optional flip box (gooseneck extension) and third flip axle	
GOOSENECK	
Gooseneck Design: Mechanical removable with removable fifth wheel guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches	
Gooseneck Platform: Full width gooseneck platform with 1 1/8 inch wood floor	
Tool Box: Lockable toolbox in riser portion of GN between MB	
Gooseneck Fenders: Aluminum fenders at rear of gooseneck	
DECK	
Deck Design: Flat level telescopic deck design	
Deck Length: 27 feet 7 inch clear deck length (retracted) - 47 feet 2 inches (extended)	
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: 8 Pair of D-rings recess mounted in floor inboard of outside beams	
Crossmembers: On 24 inch centers	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Mini Boom Trough & Traction Cleats: Mini boom trough and traction cleats installed on sloped bogie ramp	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Outriggers: 13 pair - 26 total outriggers, 1 pair 2 total heavy duty outriggers	
Deck to Bogie Connection: Fixed	
AXLES	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches spread (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: Spring brakes on 2 axles	
Dust Shields: Dust shields on 2 axles	
SUSPENSION	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride with automatic controls	
ABS: 2S/2M system without diagnostic tool and cable	
Load Scale: None Standard	

WHEELS AND TIRES	
Wheels: 8.25 x 22.5 Lvl One buffed wheels	
Tire Brand: OEM Standard	
Tires: 255/70R 22.5 H ply OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
REAR BRIDGE	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 41 inches	
Bumper: 3 tail light package	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Liquid Filled Gauge: Included	
Winches: 11 - three bar type, 4 per side on deck, 2 mount roadside on gooseneck, 1 mounted curbside center of gooseneck	
Special J Hooks: Opposite winches	
Accent Package: Stainless steel accent package	
Electrical System: Two (2) pair 4-way receptacles (One pair on gooseneck, one pair on bogie)	
LIGHTING	
Lighting: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Marker Lights: 7 marker lights per side including mid-turn	
Electrical Receptacle: J560 7-pin connector	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel	
MISCELLANEOUS	
Lash Rings: 8 pair - 16 total side mount 8 Pair of D-Rings Recess Mounted in Floor Inboard of Outside Beams. 2 Pair Additional D-Rings on rear bridge.	
Flag Holders: 2 pair flag holders	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	
Flipbox: None	
AVAILABLE COMPONENTS	
Flip Axle: Rear Axle -Lvl One buffed wheels Serial Number A5286-A5289	
Dust Shields on Flip Axle: Standard	
Two Additional D-Rings in Bogie Transition	
Total	
Total Weight	Est. Wt.: 23,023# +/- 3%

1% 10, Net 30 days

For all Quotations, pricing valid for 10 days from date of quotation, thereafter subject to change without notice.

For all Orders, prices shown are not firm-fixed.

Prices will be reassessed ten (10) weeks prior to order completion date and modified, if deemed necessary.

Order cancellations must be received no later than nine (9) weeks prior to order completion date.

Credit Terms: All Orders are subject to Fontaine's current Terms and Conditions of Sale. Go to Terms and Conditions for details at www.fontainespecialized.com