

Unit #96484

SPECIFICATIONS

BASE MODEL: VS2DX

DWG: PB-???

GVWR: 65,000

OVERALL LENGTH:

53'

OVERALL WIDTH:

102 3/8"

OVERALL HEIGHT:

13' 6"

FIFTH WHL HT:

46 1/2

POST HT FRONT:

110 3/16 "

POST HT REAR:

110 3/16 "

KINGPIN LOC:

36"

REAR SUSPENSION LOC:

SLIDER

| Option No. | Qty | Description | Unit Price | List Price |
|-------------|-----|---|------------|------------|
| 001-361-XXX | | CUSTOMER REQUIRED PROTOTYPE (INCLS WEIGHT) | | |
| 001-500-001 | | FRENCH/ENGLISH SER PLT REQD FOR IMPORT TO CANADA | | |
| 001-614-001 | | NON-THIN WALL DESIGN SIDE WALL SYSTEM | | |
| 005-014-XXX | | LEG LOCATION TO BE 6" REARWARD OF STANDARD (111" FROM K.P.) | | |
| 006-022-146 | | 4" ALUM I-BEAM CROSSMEMBERS ON 12" C/L LEGS TO REAR SUB | | |
| 006-626-005 | | 50 GAL FUEL TANK PREP (UTM STD) LAST(2)CMEM OVER LEGS & 1ST CMEM IN BAY AREA PUNCHED FOR TANK | | |
| 007-101-043 | | PREMIER #270 PINTLE HOOK (FOR SUPER DOUBLES) WITH SLIDER | | |
| 007-101-XXX | | DUAL SAFETY LOOPS @ PINTLE HOOK ONE EACH SIDE OF PITLE HOOK | | |
| 007-103-020 | | (1) PAIR RUBBER DOCK BUMPERS 2" PROUD | | |
| 008-111-XXX | | STEMCO "DATA TRAK" DIGITAL HUBOMETER IN KILOMETERS MTD R/S REAR AXLE. | | |
| 008-113-022 | | PHILLIPS QWIK-E GLADHAND WITH QUICK RELEASE VALVE | | |

| | | |
|-------------|-------|--|
| 008-350-XXX | | HALDEX 4S/2M AND WITH DUAL AXLE SENSING. CALLIBRATED TO SPECIFIC TIRE SIZE (SEE SP'L INST) |
| 008-487-011 | | P-SPINDLE TYPE |
| 008-499-010 | | HEND "TIREMAAX CP" TIRE INFL SYS MTD FRT SLIDER, INCLS AXLE PREP & WARN LGT MTD LOWER RS/FRONT |
| 008-512-XXX | 40.00 | INSTALL SAFETY LINK INTER-NATIONAL WHEEL NUT LOCKS ON ALL WHEEL NUTS. |
| 008-537-XXX | | MANUAL LEVER FOR SLIDER PIN RELEASE (ILO QUIK DRAW) |
| 008-610-006 | | BENDIX DISC BRAKES FOR USE WITH 'P' SPINDLE |
| 009-503-003 | | PREP FOR FRONT MOUNT THERMO KING HEAT KING 400 |
| 009-504-009 | | PRE-PAINTED WHITE FRONT CORNER POST INSERTS (OVER NATURAL ALUMINUM FRONT CORNER POSTS) |
| 009-555-XXX | | INSTALL CUSTOMER FURNISHED TK HEAT KING 400 HEATER & TANK |
| 010-043-101 | | 1-1/4"GALV STL LOG POSTS ON 24" C/L W/"A"SLOT ON 4"C/L W/REC MTD PLYWOOD LINING |
| 012-049-046 | | REAR SWING PLATE DOOR PANELS WITH POLYETHYLENE CORE |
| 014-057-XXX | | 1-3/16" HAVCO COMPOSITE FLOOR W/ FIBERGLASS BACKING (FLOOR RATING IS 12,000 LBS) |
| 014-475-XXX | | 1" WIDE TROUGH W/ DRAINS AT REAR BETWEEN TREADPLATE AND THRESHOLD |
| 014-559-003 | | (3) SCREWS PER BOARD PER CROSSMEMBER |
| 015-062-014 | | FOAM BLOCK INSUL ON FRT & SIDE |

| | |
|-------------|---|
| | WALLS,& ROOF(1/4" PLYROOF LINING INCL)(NON-THIN WALL DESIGN) |
| 015-067-XXX | INSULATE REAR DOORS USING 1" BLOCK FOAM & COVER WITH .060 VERSITEX |
| 015-XXX-XXX | BLOCK FOAM IN HAT CAVITY OF 1-1/4" HAT POSTS,FOAM WILL BLOCK SLOTS |
| 016-070-XXX | FRONT WALL LINING TO BE 1/4" PLY, FULL HEIGHT. |
| 016-071-XXX | .060 (VX3) VERSITEX LNG REC MTD BTWN 1-1/4" LOG PST(VS PLY) |
| 016-074-XXX | .160 X 13" VERSITEX W/B SURFACE MOUNTED ON SIDEWALLS TO 18GA GALV W/B |
| 017-076-XXX | 7-WAY PLUG W/ SPLIT (SPREADABLE) PINS (UTM STD) |
| 017-077-161 | 2-1-2-5 CLEARANCE LIGHT PACKAGE |
| 017-144-XXX | GROTE #52393 LED COMBO MIDSHIP MARKER/TURN FASTENED W/SST RIVETS AND SST BRACKETS |
| 017-200-XXX | GROTE 4" DIA SST FLANGE MTD LED (10 DIODE) STOP/TAIL/TURN LIGHTS |
| 017-216-011 | GROTE SUPERNOVA LED 12V LICENSE LIGHT |
| 017-374-XXX | ENSURE NYK 77 SERIES GREASE IS APPLIED TO ALL ELECTRICAL CONNECTIONS. |
| 017-505-006 | GROTE SUPERNOVA THIN-LINE LED UPPER RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L |
| 017-506-034 | CONVERT STD BTM RAIL LIGHTS TO GROTE TURTLEBACK II LED |
| 017-507-XXX | GROTE #78433, 2" DIA LED ABS |

| | | |
|-------------|------|--|
| | | LIGHT W/ GROTE #43690 TWIST ON SURFACE MOUNTING BRACKET. |
| 018-154-016 | | STENCILING BY UTM CONTRACTED INSTALLER *REQD W/GRAPHICS OTHER THAN BLOCK LETTERS/NUMBERS/LINES |
| 018-194-002 | | CUST FURN DECALS INSTALLED BY UTM CONTRACTOR(EVALUATE POSSIBLE CONFLICT W/OPER/WARNING DECALS) |
| 019-095-XXX | | FURNISH AND INSTALL PLAIN WHITE ANTI-SAIL MUDFLAPS (NO LOGOS) |
| 019-141-XXX | | INSTALL CUSTOMER FURNISHED TRANSTEX COMPOSIT "SIDE SKIRT" MTD UNDERNEATH BTM RAIL R/S &C/S |
| 019-142-XXX | | PENZ #10-01 (8X13") ALUM MANIFEST BOX MOUNTED ON R/S FRONT WALL. |
| 019-143-021 | | BETTS PS-1 ROUND PERMIT HOLDER ON R/S FRONT WALL |
| 019-191-XXX | 2.00 | (4) ALUM #4 TPH SLIDE IN TYPE PLACARD HOLDERS (2 PER SIDE) WITHOUT BACK PLATE. |
| 019-387-XXX | | VALVE STEMS FOR USE WITH DISC BRAKES |

SPECIAL INSTRUCTIONS:

GRP 8:

- A) ABS SYSTEM TO BE CALIBRATED TO SPECIFIC TIRE SIZE. (295/75R 22.5")
- B) CALIBRATE TIREMAXX SYSTEM TO 100 PSI.
- C) TIREMAXX INDICATOR LIGHT TO BE MTD APPX. 30"-36" FROM THE BOTTOM OF THE PANEL TO THE C/L OF THE LIGHT (THIS WILL PUT THE LIGHT ABOVE THE MANIFEST BOX ON THE FRONT WALL)

Grp 9:

- FUEL TANK TO BE MOUNTED BEHIND SKIRT,
- CUT LARGE HOLE FOR FILLER NECK &

SMALL

HOLE TO VIEW GAUGE.

GRP 14:

A) 1" WIDE TROUGH WITH DRAINS AT REAR
BETWEEN TREADPLATE AND THRESHOLD.

GRP 16:

A) RUN CHAULKING FULL HEIGHT ON SEAMS
@ R/S & C/S FRONT CORNER POSTS.

GRP 19:

A) LOCATE PLACARDS AT STANDARD LOCATIONS,
SIDE-BY-SIDE.

ATTENTION;

PLEASE CAREFULLY REVIEW THIS INFORMATION AND
IMMEDIATELY COMMUNICATE ANY DISCREPANCIES.

Tires and Wheels:

020-000-435

8 295/75R22.5 BSTN R195F 14P

020-000-490

8 22.5X8.25 ACRD 50487PKWHT21