



4400 So Lewis Blvd
PO Box 6300
SIOUX CITY, IA 51106

Phone: 712-252-6500
Fax: 712-252-6510

Dealer's customer info.: Stock Tandem Front Slide

OCEAN TRAILER (WPG) - (PTS/TRL)
415 LUCAS AVE
BOX 58, GROUP 200, RR#2
WINNIPEG, MB R3C 2E6
CAN

Confirmation

Type of order.....: Flatbed
Number: 636499-1
Mfg. Location: Plant 6
Order date.....: 11/25/2024
Revision date: 11/25/2024
Requested ship date: 1/25/2025
Customer Account: 100439
Customer PO#: 96895
Trailer number.....: 636499
Model Year.....: 2026
VIN number.....:
Sales person: Schlines, Danielle L
Salesperson phone: 712-252-6539

Contact person.....
Customer phone

Pblite Revision: 1



PO# 96895-96896

Description	Quantity
1) MODEL CD-1080	
2) TRAILER BUILT FOR EXPORT TO CANADA	
3) --INSTALL CANADIAN VIN PLATE ILO US	
4) 2025 PRODUCTION	
5) --FLATBED PRICING IS SUBJECT TO ADJUSTMENT UP TO NINETY (90) DAYS BEFORE PRODUCTION OF YOUR ORDER	
6) --(90) DAYS FROM THE START OF PRODUCTION YOU WILL RECEIVE NOTICE IF PRICING ADJUSTMENT IS REQUIRED	
7) --CUSTOMER HAS THE RIGHT TO ACCEPT THE ADJUSTMENT OR CANCEL THE ORDER	
8) LENGTH 53 FT	
9) WIDTH 102"	
10) FIFTH WHEEL HEIGHT 48" (STD)	
11) KING PIN 24"	
12) KING PIN CORSOL PAINTED (STD)	
13) 10-3/4" KING PIN BEAM DEPTH (STD)	
14) STANDARD KING PIN	
15) JOST UL550 ULTRALIGHT LANDING GEAR W/ CUSHION FOOT (STD)	
16) 11' TOP DECK LENGTH (STD)	
17) REAR DECK HEIGHT 39-1/2" (22.5 TIRES) (STD)	
18) FRONT DROP - 21" (STD)	
19) GN SLOPE - SQUARE (STD)	
20) SUSPENSION SETTING - (TAC LEGAL) MAXIMUM DISTANCE	
21) FRICTION SLIDER (AA250L INTRAAX) FRONT AXLE SLIDE TANDEM	
22) MANUAL SUSPENSION DUMP (STD)	
23) HENDRICKSON HEIGHT CONTROL VALVE (STD)	
24) HENDRICKSON TIREMAAX PRO TIRE INFLATION SYSTEM TANDEM	
25) AIR GAUGE (100 PSI) W/DUMP & SLIDER IN PLASTIC BOX	
MOUNTED BY LANDING GEAR WITH SLIDER VALVE IN BOX	
26) ABS MERITOR WABCO (PLC) 4S/2M	
27) HENDRICKSON H26 BRAKE LININGS (26K BRAKE RATING) ILO STANDARD H20 BRAKES (PER AXLE)	(2)
28) TAPERED SPINDLE W/ TN BEARINGS (PER AXLE) (STD)	(2)
29) OIL LUBE (STD)	(2)

- 30) STEMCO GUARDIAN SEAL (#3070743) (STD) (2)
- 31) STEMCO ALUMINUM HUBCAP (STD) (2)
- 32) AXILOCK SPINDLE NUT (STD) (2)
- 33) DUST SHIELDS - STEEL (PER AXLE) (2)
- 34) DURALITE HUBS/CAST DRUMS (PER AXLE) (STD) (2)
- 35) GOLD SEAL CHAMBERS W/3" STROKE AND INDICATOR (PER AXLE) (2)
- 36) HALDEX AUTO SLACK ADJUSTERS (STD) (PER AXLE) (2)
- 37) TRAMEC SPRING BRAKE VALVE (STD) (2)
- 38) MUDFLAPS- BLACK RUBBER WTC FOR SET AHEAD REAR AXLE
- 39) WHEEL ALUM (HP) ALCOA ULTRA ONE 10HOLE 8.25X22.5 (PER EA) (8)
- 40) ROADMASTER RM272 255/70R 22.5 LR-H (PER EA) (8)
- 41) ***TIRES ARE SUBJECT TO AVAILABILITY, IF A SUBSITUTE TIRE MUST BE
USED THE SALE PRICE WILL BE ADJUSTED ACCORDINGLY***
- 42) PLASTIC LINER (SET OF 8) BETWEEN HUB/WHEEL & WHEEL
- 43) FLOOR ALUM 1-3/8 (4) NAILERS (PER FT) (53)
- 44) 18" X-BAR SPACING 4-1/2" ALUM (MAIN BED) (STD) (42)
- 45) C+ STYLE SIDE RAIL 6-1/4" PKTS ON 24" CTRS/SGL SPOOL/RUB BAR
- 46) KNEE BRACES (STD)
- 47) BUMPER WITH ALUMINUM R.I.G. (STD)
- 48) FRONT CORNER POCKETS TURNED TO SIDE (STD)
- 49) FRONT STAKE POCKETS (PER EA) (2)
- 50) GLADHANDS & 7-WAY CONNECTIONS AT FRONT (STD)
- 51) GROTE LED MICRO NOVA CLEARANCE LIGHTS
- 52) RECESSED IN GROTE RUBBER GROMMET
- 53) PACKAGE B - 4 EXTRA (ROW OF 5)
- 54) SPACE LIGHTS EQUALLY - GIVE PRIORITY TO WINCH STRAP CLEARANCE
- 55) GROTE LED CENTER TURN SURFACE MOUNT (STD)
- 56) GROTE LED 4" ROUND TAIL LIGHTS CLUSTER OF 3 (GROMMET) (STD)
- 57) 2 GROTE 4" AMBER STROBE ON INSIDE POSITION OF CLUSTER OF 3 W/SS
FLANGE (SNAP-IN)
- WITH ON/OFF SWITCH IN DUMP BOX**
- 58) WIDE LOAD TELESCOPING LIGHTS 2 SETS OF 2 W/SWITCH IN DUMP BOX
- 59) QUICK TIE PLATE (PER EA) (16)
- 60) QUICK TIE PLATE STORAGE BRACKET(HOLDS 16)
- 61) QUICK TIE PLATE STORAGE BRACKET LOCATION - SPECIFY LOCATION
- LOCATE BY LANDING GEAR ON D/S**
- 62) KINEDYNE WINCH FIXED LO-PRO 3-BAR WITH CLAW HOOK KYN14001 (PER (26)
EA)
- 63) PERMANENT WINCH LOCATION - DS/CS STAGGERED SPACED EVENLY
**LOCATE 5 ON UPPER DECK STAGGERED, SPACED EVENLY STARTING ON D/S,
BALANCE ON BOTTOM DECK, STAGGERED SPACING APPROX EVEN**
- 64) AERO TOOL BOX 24D X 20H X 60L CAM LOCKS W/ 2 POLISHED DOORS (2)
- 65) TOOL BOX LOCATION - AT DROP DS & CS
- 66) MOUNT AS HIGH AND CLOSE TO BEAM AS POSSIBLE
- 67) DUNNAGE RACK: 10FT LONG X 8IN TALL OUTSIDE BEAMS X-BAR MOUNT
WITH .184 PUNCHED OVAL FLOOR PAN
- 68) DUNNAGE STORAGE LOCATION - AHEAD OF FRONT AXLE CS
- 69) PAINT WITH FLAT BLACK CORSOL ONLY (STD)
- 70) INSTALL CONSPICUITY TAPE ON RUB BAR (STD)
- 71) INSTALL DECALS AT STANDARD LOCATIONS
- 72) REGISTRATION HOLDER - TUBE TYPE (STD)
- 73) CUSTOMER IS RESPONSIBLE FOR SECURING DECKED TRAILERS AND
COMPLYING WITH LOAD HEIGHT RESTRICTIONS