

PO# 97254-97255

Build Sheet

MODEL: 53' Sliding Triaxle Flat Deck ITEM ID:98036 MODEL YEAR:2026

Body Structure

Dimensions: Length 53', Width 102" Front Deck Height 59 13/16" Rear Deck Height 55 1/2",
Beams: Web 3/16" GR90 KSI HTS, Flange GR130 KSI 5" x 3/8" Top, 1/2" Bottom HTS, Robotically Welded. Camber 3.25"
Crossmembers: 4" Superlight I Beam 16" on center
Floor: 1-5/16 BC Douglas FIR Shiplap
Side Rails: 6" Cold Rolled Formed Steel Channel
Rub Rail: 2 1/2" x 3/8" Steel Continuous
Knee Braces: Steel Tube @ 4/side
Kingpin: 24" Inset, 2.0" SAF Holland
Coupler Assembly 3/8" Plate @ 48" Coupler Plate Height
Front Bolster: Formed Front Bolster W/ 4 Integrated Stake Pockets
Rear Bolster: Formed W/ 5 Integrated Stake Pockets
Impact Guard: Weld On, Meets CMVSS

Securement

Stake Pockets: Formed, 24" Centers
Pipe Spools: Single 1 1/2" Pipe Spool Between Stake Pockets
Winches: 27 – Side/Bottom Mount 3 Bar Welded, Staggered Config(First Winch 12" Center From Front, Following 16" Center Spacing)
J-Hooks: Opposite of Winches
Accessory Tie Flat Bar 2 1/2" X 3/8" Steel: No
Tarp Rope Hooks: Yes

Axles/Suspension/Tires/Wheels

Suspension: Hendrickson AAT23K Air Ride with 3-23,000lb axles, HP Spindle, 60"-60" Spread -, 17" Ride Height, 77 1/2" Track Width, 3 Axle Sliding Boggy
Brakes: HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Spring Brake Pots 30/30 TSE, Short 28 Spline Cam Bendix TABS-6 ABS (2 Sensors/1 Modulator), Dust Shields
Hubs: Ductile Iron w/Long Studs, HXL5 5-year Wheel End Warranty, Semi Fluid CHEVRON DELO SF w/Ventless
Hub/Vented Axle, Precision 320 Spindle Nut
Drums: Cast
Tires: 11R24.5 Cooper Roadmaster RM 872
Rims: 22.5" x 8.25" White Steel Powder coated (inner & outer)

Ratings

Distributed Load: 70,000lbs, 20' Concentrated-60,000lbs, 10' Concentrated-51,000lbs, 4' Concentrated-45,000lbs,
GVWR: 38,500kgs
Weight: 14,990Lbs
Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards
Safety: Reflective 2" Red/White Conspicuity Tape

Systems - Air/Electrical

Control Box: SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

Air System: 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

Air Tanks: Steel Tank Air Brake 9.0" - 1488 Cu. In. Small, Tank Air Brake 12.0" - 2850 Cu. In. Large

Lighting: 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Stop/Tail/Turn W/Anti-Theft Bezels, 1/Side - Amber - 3/4" Micro Nova Located Front Bolster, 8/Side - Amber - 3/4" Micro Nova Located On Side Rails, 1 - Signal/Marker Per Side, 1/Side - Red - 3/4" Micro Nova Located Rear Side Rail, 5 Red - 3/4" Micro Nova In Rear Bolster Plate, 1 - License Plate Light,

Auxiliary Power Plug: 2 Pin Plug at Rear Bolster

Components

Document Holder: 1 - Tube Style

Landing Gear: Pair - 62500lb Dual Speed SAF Holland Mark V with Low Pro Sand Shoe

Dock Bumper: 2 - Mounted Rear Bolster

Tow Point: 2 - Rear Web Mounted w/1.5" Hole

Options

Toolbox: Aluminum Box with Barn Doors 24"h x 23"d x 60" 1 Curb Side

Paint: Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Black

Fenders: N/A

Dunnage Rack: 0

Dunnage Basket: 0

Wide Load Pull Out Lights – 0

Steps: N/A

Mudflaps: 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 4

Strobe Lights: 0

Logo Checker Plate: Yes **Logo:** Renn

Tire Chain Carrier Formed: 0