



The First Name In Trailers

OTR# 97342-97361
OTR# 97382-97401

C. Keay Investments Ltd.

Will Tucker
100 Golden Drive
Coquitlam, BC V3K 6T1
Voice 604-945-3718

Trailer Quote Prepared For

OCEAN TRAILER STOCK
9076 RIVER ROAD
DELTA, BC V4G 1B5

20 - VS2DX
April 21, 2025

Specifications (☞ = Option to Base Model)

1-Model & Payload Capacity

MODEL	VS2DX
PAYLOAD CAPACITY	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
GROSS VEHICLE WEIGHT RATING	65,000 LBS GVWR
INTERNATIONAL IMPORTATION SPECIFICATIONS	☞ FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION
4000D-X101.25 SYSTEM	BASE SPEC:4000DX101.25 SYS;8"C/L "A"SLOT;ID WIDTH@LINING 101-1/4" @W/B 101";TOL:+/-1/4";14GA POST
GREENHOUSE GAS COMPLIANCE	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
DQS UPDATE NUMBER	DQS UPDATE #190 (02/10/25)

2-Dimensions

LENGTH	53'0" OVERALL LENGTH
OVERALL HEIGHT	13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST HEIGHT
WIDTH	102-3/8" OVERALL WIDTH
INSIDE HEIGHT	110-1/2" INSIDE HEIGHT AT FRONT; 111" INSIDE HEIGHT AT REAR
INSIDE WIDTH	101" INSIDE WIDTH AT WEARBAND (+/- 1/4" TOLERANCE)

3-Deck

DECK TYPE	STRAIGHT DECK WITH 1/2" WEDGE
-----------	-------------------------------

4-Front Subframe

FRONT SUBFRAME	3-1/2" DEEP BOX BEAM DESIGN FRONT SUBFRAME RAISED 1-3/8" FLUSH WITH TOP OF FLOOR
APPROACH PLATE	8 GA CARBON STEEL FULL WIDTH APPROACH PLATE
KINGPIN PLATE	3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
KINGPIN TYPE	AAR HARDNESS CRUCIFORM KINGPIN
KINGPIN LOCATION	36" KINGPIN LOCATION
COVER PLATE	☞ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL

5-Support Legs

SUPPORT LEG LOCATION	SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN
SUPPORT LEG CRANK LOCATION	ROADSIDE SUPPORT LEG CRANK LOCATION

SUPPORT LEG BRACING

BOLT-ON CROSS BRACING WITH 7 GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL

WING PLATE MATERIAL

➤ SATIN FINISH SST WING PLATES (INCLUDES SST MOUNTING BOLTS)

SUPPORT LEGS

➤ JOST MODEL A451 MAGNUM SUPPORT LEGS W/10-YR WARRANTY & 10"X10" ULTRA LOW PROFILE CUSHION FOOT

6-Frame, Rails & Crossmembers

BOTTOM RAILS

10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS

CROSSMEMBERS FRONT SUB TO LEGS

2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE

CROSSMEMBERS OVER SUPPORT LEGS

(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON 12" C/L OVER SUPPORT LEGS

CROSSMEMBERS LEGS TO REAR SUB

4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12" C/L LEGS TO REAR SUB

CROSSMEMBERS OVER REAR SUBFRAME

4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR SUB

7-Rear Subframe

HORIZONTAL DOCK BUMPER

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER

RUBBER DOCK BUMPERS

➤ (1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD

VERTICAL &HORIZONTAL DOCK BUMPER

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IIHS-30% OFFSET TEST

VERTICAL &HORIZONTAL DOCK BUMPER

➤ DOT BMPR WELD-ON VERT & BOLT-ON NONSLIP HRZ 21"MAX GRND CLR,W/IN LESS 4"OAW EA SIDE FOR 7"BUMPER

VERTICAL &HORIZONTAL DOCK BUMPER

➤ DOT SST WELD-ON VERT & BOLT-ON NONSLIP HRZ 21"MAX GRND CLR W/IN LESS 4"O.A.W.EA SIDE FOR 7" BMPR

8-Suspension/Axles/Actuation

SLIDER SUSPENSION LOCATION

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL

OIL SEALS

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)

AIR BRAKE CHAMBERS

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

AIR ACTUATION

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

SLACK ADJUSTERS

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

HUBODOMETER

➤ STEMCO HUBODOMETER MTD ON AXLE

DUST SHIELDS

➤ DUST SHIELDS FOR 16-1/2" X 7" BRAKES

AIRRIDE DUMP VALVES

HENDRICKSON AUTOMATIC DUMP VALVE

<i>BRAKE LINING STYLE</i>	HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAAX
<i>AXLE SPINDLE NUTS</i>	CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HUB PILOTED SYS W/OUTBOARD DRUMS FOR 16-1/2" X 7" BRAKES</i>	BASE SPEC:STL JACKET 10STD HBPLT SYS W/OB BLNCD STL LT WT DRUMS 16-1/2"X7"BRKS FOR CNMET PRESET+
<i>ANTILOCK BRAKE SYSTEMS (ABS)</i>	BENDIX TABS-6 2S/1M ABS SYSTEM *W/O ROLL STABILITY*
<i>WHEEL BEARING LUBRICATION</i>	FACTORY CHOICE 80W-90 OIL
<i>ANTI-DOCK WALK DEVICES</i>	➤ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE
<i>WHEEL SEPARATOR PLATES</i>	➤ NYLON WHEEL GUARD SEPARATOR PLATE BTWN INNER WHEEL & HUB
<i>AXLE MANUFACTURER</i>	HENDRICKSON "VENTED" AXLES
<i>AXLE SPINDLE TYPE</i>	➤ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM
<i>AUTOMATIC TIRE INFLATION SYSTEM</i>	➤ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
<i>LOAD SCALE KIT</i>	➤ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
<i>WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER</i>	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
<i>HENDRICKSON AIRRIDE SYSTEMS WITH INTEGRAL AXLES</i>	BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)
<i>SLIDER PIN RELEASE MECHANISM</i>	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
<i>CONMET WHEEL END SYSTEMS</i>	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT
9-Front Wall	
<i>FRONT CORNER POST</i>	.080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS
<i>FRONT WALL POSTS</i>	(4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL POSTS
<i>FRONT PANELS</i>	.040 ALUM FRONT PANELS
<i>GLADHANDS & RECEPTACLE LOCATION</i>	SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET 27-1/2" TO R/S FROM C/L OF TRAILER
<i>FRONT TOP RAIL</i>	EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL

10-Side Walls

SIDE PANELS	COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC POLYURETHANE FOAM CORE BONDS INT/EXT PANELS)
SIDE POSTS	3/8" 14GA HIGH STR GALV HAT SHPD 24"C/L (FRT/RR SUB 16"C/L) W/"A" SLOTS ON 8" VERT C/L
EXTERIOR SIDE WALL PROTECTION	☛ LOCATE RUB PROTECTOR @ APPROX 6" FROM TOP OF RUB RAIL TO C/L OF RUB PROTECTOR
EXTERIOR SIDE WALL PROTECTION	☛ RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE REQUIRED INFORMATION: <u>Dealer must specify location of (1) rub protector c/l of rub rail to top of bottom rail and location of (1) rub protector c/l of rub protector to bottom of top rail.</u> >> LOCATE RUB PROTECTOR @ APPROX 6" FROM TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR

11-Roof

TOP RAILS	4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS
ROOF SKIN	.040 ONE PIECE ALUM COIL ROOF SKIN
ROOF BOWS	1-1/16" ANTI SNAG 18GA GALV STL HAT SHAPED ROOF BOWS 16"C/L(FRT/ RR SUB 24"C/L)BONDED TO ROOF SKN

12-Rear Doors

REAR DOOR TYPE	COMPOSITE REAR SWING DOORS
REAR DOOR PANELS	1/2" COMPOSITE REAR SWING DOORS (PRE-PAINTED WHITE GALV STEEL PANELS W/POLYETHYLENE CORE)
REAR DOOR LOCK RODS	(1) REAR DOOR LOCK ROD PER DOOR
REAR DOOR HINGES	☛ REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT
REAR DOOR HINGES	☛ (1) ADDITIONAL PAIR OF REAR DOOR HINGES
HOLDBACKS	CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS
REAR CASE & BUCKPLATE MATERIAL	SATIN FINISH SST REAR DOOR CASE
GRAB HANDLE AT REAR OF TRAILER	☛ 36"LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S DOOR
REAR TREADPLATE	.219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE INTEGRAL WITH REAR BUCKPLATE
REAR DOOR HINGE MATERIAL	NON-POLISHED ALUMINUM

14-Floor

FLOOR TYPE	20,000LB 1-3/8"NOM LAM HDWD FLR; FACTORY CHOICE:OAK OR SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM
------------	--

FLOOR JOINT SEALANT

CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT

16-Lining

FRONT WALL LINING

.016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING

SIDE WALL LINING

PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING

WEARBAND

☛ 14GA X5/16"CORR X12" NOM GALV STL HD S/WALL W/B (REDUCES ID WIDTH 3/8"@W/B)-USE W/THINWALL

WEARBAND ON FRONT

14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL WEARBAND

SIDE WALL LINING CLOSURES

45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING CLOSURES

SIDEWALL LINING/POST MODIFICATION

☛ (1) FOAM POST PLUG IN EA SIDE POST BELOW THE LOWEST "A" SLOT FOR USE W/ 3/8" POSTS (DX-101)

17-Electrical System

MAIN HARNESS

UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH INTERNAL GROUND AND 7-WAY PLUG

ELECTRICAL RECEPTACLE

7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED

CLEARANCE LIGHT QUANTITY

☛ 2-1-2-5 CLEARANCE LIGHT PACKAGE

ADDITIONAL STOP/TAIL LIGHTS

☛ ONE ADDITIONAL STOP/TAIL LIGHT EACH SIDE WITH EXTENDED LIGHT PROTECTOR BAR

SIDE MOUNTED DIRECTIONAL LIGHT

GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE

STOP/TAIL/TURN LIGHTS

☛ GROTE 4"DIA SST SNAP-IN FLANGE MTD LED(10 DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)

LICENSE LIGHT

GROTE MICRONOVA L.E.D. LICENSE LIGHT

CONSPICUITY TAPE LOCATION

CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION

CONSPICUITY TAPE

FACTORY CHOICE CONSPICUITY TAPE

UPPER CLEARANCE LIGHTS

FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L

LOWER CLEARANCE LIGHTS

GROTE MICRONOVA LED PC RATED LIGHT

ABS (ANTI-LOCK) WARNING LIGHT

GROTE MICRONOVA L.E.D. PC RATED LIGHT

STOP/TAIL/TURN LIGHT CONFIGURATION

GROUPED STOP/TAIL/TURN LIGHTS

REAR HEADER CLEARANCE LIGHTS

☛ (5) GROTE MICRONOVA L.E.D. MULTI-FUNCTION LIGHTS ON REAR SWING DOOR HEADER

18-Finish Specifications

TOP FRONT & TOP SIDE RAIL
FINISH

NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS

BOTTOM SIDE RAIL FINISH

NATURAL ALUM FINISH BOTTOM SIDE RAILS

FRONT CORNER POST FINISH

NATURAL ALUMINIUM FINISH FRONT CORNER POSTS

FRONT PANEL FINISH

PREPAINTED WHITE FRONT PANELS

SIDE PANEL FINISH

PREPAINTED WHITE SIDE PANELS

FRONT SUBFRAME ASSEMBLY
FINISH

FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST
PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED

SUPPORT LEG FINISH

BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS

REAR SUBFRAME FINISH

BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME

REAR CASE FINISH

SATIN FINISH STAINLESS STEEL REAR CASE

VRTCL & HORZNTL DOCK
BMPR FINISH

UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK
SCHARPF ON VERTICAL DOCK BUMPER

ROOF EXTERIOR FINISH

NATURAL ALUM ROOF EXTERIOR FINISH

REAR DOOR COLOR

PREPAINTED WHITE REAR DOORS

FLOOR UNDERCOAT

BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

19-Miscellaneous

MUDFLAP TYPE

BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH
STEEL REINFORCING STRAPS

PERMIT HOLDER

- TRUCKLITE #97960 ROUND PERMIT HOLDER MTD ON FRONT WALL
REQUIRED INFORMATION:
Dealer must specify location of permit/document/registration holder on
either R/S, C/S or C/L in special instructions unless otherwise stated in
the option description.

>> R/S

SIDE MOUNTED
AERODYNAMIC AIR
DEFLECTORS

BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE
SKIRT MTD BELOW BOTTOM RAIL

20-Tires and Wheels

22.5"X8.25"STANDARD WIDTH
WHEELS

- 8 - 22.5X8.25 ALCOA ^{Stand} POLISH ULTRA ONE ALUMINUM 10H/P
#881677 10 HAND HOLE *Accuride*

22.5" STANDARD PROFILE
TIRES

- 8 - 11R 22.5 MICH X-LINE ENERGY-T2 14PLY 40.80"T/D,LOAD RING'
MAX SPEED RATED @75 MPH;

Special Instructions

None.

Weight

Total Weight 13,072 lbs. (+/- 3%)

Terms & Conditions