

97382-  
7401



*The First Name In Trailers*

**C. Keay Investments Ltd.**

**Will Tucker**  
100 Golden Drive  
Coquitlam, BC V3K 6T1  
Voice 604-945-3718

Trailer Quote Prepared For

***OCEAN TRAILER STOCK***  
***9076 RIVER ROAD***  
***DELTA, BC V4G 1B5***

*20 - VS2RA*  
*April 24, 2025*

---

## Specifications (☞ = Option to Base Model)

### 1-Model & Payload Capacity

MODEL	VS2RA
PAYLOAD CAPACITY	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
GROSS VEHICLE WEIGHT RATING	65,000 LBS GVWR
INTERNATIONAL IMPORTATION SPECIFICATIONS	☞ FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION
GREENHOUSE GAS COMPLIANCE	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
FOAM COMPOSITION	TRAILER CONTAINS NON-HFC FOAM; MAY BE SOLD OR USED IN STATE W/ HFC RESTRICTION
DQS UPDATE NUMBER	DQS UPDATE #190 (02/10/25)

### 2-Dimensions

LENGTH	53'0" OVERALL LENGTH
OVERALL HEIGHT	13'6" O/A HEIGHT ON 46-1/2" FIFTH HT FOR 107-1/8" POST HT
WIDTH	102-3/8" OVERALL WIDTH

### 3-Deck

DECK TYPE	STRAIGHT DECK
-----------	---------------

### 4-Front Subframe

FRONT SUBFRAME	4-1/4" DEEP BOX BEAM DESIGN FRONT SUBFRAME
APPROACH PLATE	9GA HIGH STRENGTH STEEL FULL WIDTH APPROACH PLATE
KINGPIN PLATE	3GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
KINGPIN TYPE	AAR HARDNESS CRUCIFORM KINGPIN
KINGPIN LOCATION	36" KINGPIN LOCATION
CONDUIT	(1) CONDUIT THROUGH FRONT SUB 30-1/2" FROM C/L ON ROADSIDE
COVER PLATE	EXTRUDED ALUM COVER ON FRONT FACE OF APPROACH PLATE

### 5-Support Legs

SUPPORT LEG LOCATION	SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN
SUPPORT LEG CRANK LOCATION	ROADSIDE SUPPORT LEG CRANK LOCATION
SUPPORT LEG BRACING	BOLT ON SUPPORT LEG X-BRACING W/7GA 3-1/4" DEEP HIGH STRENGTH STEEL CHANNEL

*SUPPORT LEGS*

- JOST MODEL A451 MAGNUM SUPP LEGS W/10-YR WARRANTY AND 10"X10" LOW PROFILE REMOVABLE CUSHION FOOT

**6-Frame, Rails & Crossmembers**

*BOTTOM RAILS*

- DO NOT NOTCH OUT BOTTOM RAIL AT REAR

*BOTTOM RAILS*

11" DEEP HEAVY DUTY EXTRU ALUM BOTTOM RAILS, TAPERED FRT & REAR

*CROSSMEMBERS FRONT SUB TO LEGS*

4" ALUM I BEAM CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L FRONT SUB TO SUPPORT LEGS

*CROSSMEMBERS OVER SUPPORT LEGS*

(5) 4" STEEL I BEAM CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L OVER SUPPORT LEGS.

*CROSSMEMBERS LEGS TO REAR SUB*

5-1/2" ALUM I SHAPE CMEMS W/(4) RIVET ENDCLIPS ON 12" C/L SUPPORT LEGS TO REAR SUB

*CROSSMEMBERS OVER REAR SUBFRAME*

4" STEEL I BEAM CMEMS W/(4)RIVET ENDCLIPS ON 12" C/L W/STD REINF OF (1) ADDL CMEM IN REAR 34"

*CROSSMEMBERS OVER REAR SUBFRAME*

- (2) ADDL STEEL CMEMS IN REAR 58" ON 6" C/L

*PREP FOR FUEL TANK FOR USE WITH SIDE SKIRTS*

- 50 GAL FUEL TANK PREP (UTM STD) FOR USE WITH SIDE SKIRTS

**7-Rear Subframe**

*HORIZONTAL DOCK BUMPER*

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK CLEARANCE X11"LG @ C/L OF BUMPER

*RUBBER DOCK BUMPERS*

- (1) PAIR POLYURETHANE DOCK BUMPERS 5/8" PROUD W/EMBEDDED STUD

*VERTICAL &HORIZONTAL DOCK BUMPER*

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX GROUND CLRN; MEETS IIHS-30% OFFSET TEST

**8-Suspension/Axles/Actuation**

*SLIDER SUSPENSION LOCATION*

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION LOCATION FOR 96" OF SLDR TRAVEL

*OIL SEALS*

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)

*AIR BRAKE CHAMBERS*

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

*AIR ACTUATION*

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

*SLACK ADJUSTERS*

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

*DUST SHIELDS*

- DUST SHIELDS FOR 16-1/2" X 7" BRAKES

*AIRRIDE DUMP VALVES*

HENDRICKSON AUTOMATIC DUMP VALVE

*BRAKE LINING STYLE*

HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX

AXLE SPINDLE NUTS	CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END SYSTEM)
HUB PILOTED SYS W/OUTBOARD DRUMS FOR 16-1/2" X 7" BRAKES	BASE SPEC:STL JACKET 10STD HBPLT SYS W/OB BLNCD STL LT WT DRUMS 16-1/2"X7"BRKS FOR CNMET PRESET+
ANTILOCK BRAKE SYSTEMS (ABS)	BENDIX TABS-8 ADVANCED W/ROLL STABILITY 2S/1M ABS
WHEEL BEARING LUBRICATION	➤ MOBILITH SHC007 SYNTH SEMI-FLUID GREASE W/ 1YR/100,000 MILE SERVICE INTERVAL
ANTI-DOCK WALK DEVICES	➤ HENDRICKSON ANTI DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE
AXLE MANUFACTURER	HENDRICKSON "VENTED" AXLES
AXLE SPINDLE TYPE	➤ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END SYSTEM
AUTOMATIC TIRE INFLATION SYSTEM	➤ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT CORNER *RETAINS CONMET 8YR WARRANTY*
LOAD SCALE KIT	➤ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX
WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
HENDRICKSON AIRRIDE SYSTEMS WITH INTEGRAL AXLES	BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)
SLIDER PIN RELEASE MECHANISM	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
CONMET WHEEL END SYSTEMS	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT

#### 9-Front Wall

FRONT CORNER POST	BASE SPEC: .080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POST WITHOUT INSERT RECEIVERS
FRONT WALL POSTS	1" "J" EXTRU ALUM FRT WALL POST W/(2) ADDL 3-1/4" DEEP STEEL REEFER UNIT SUPPORT POSTS
FRONT PANELS	.040 ALUM FRONT PANELS
GLADHANDS AND RECEPTACLE	GLADHANDS (W/SCREEN) AND RECEPTACLE MOUNTED ON AN ALUM EXTRU OFFSET TO R/S 30"
FRONT CORNER POST INSERTS	➤ FLAT STAINLESS STEEL INSERTS ON FRONT CORNER POSTS W/ RECEIVERS
REFRIGERATION UNIT OPENING COVER	SHEET METAL COVER (INCLS SEALANT FULL PERIMETER OF OPENING)

PREP FOR THERMO  
KING/CARRIER REEFER UNIT

PREP FOR LARGE FRONT MOUNT THERMO KING/CARRIER REEFER  
UNIT \*\*\*\*\*W/O ELECTRIC STANDBY\*\*\*\*\*

**10-Side Walls**

*SIDE PANELS*

- .040 ALUM CORR SIDE PANELS, USE W/1-1/2" SIDE WALL INSUL (INCLS 1"HD J POST 16"C/L REAR OF LEGS)

*SIDE POSTS*

- \*\*NOTE\*\* 1" HD "J" posts 16" C/L rear of legs (for use with .040 side panels)

*EXTERIOR SIDE WALL  
PROTECTION*

- RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE

REQUIRED INFORMATION:

Dealer must specify location of (1) rub protector c/l of rub rail to top of bottom rail and location of (1) rub protector c/l of rub protector to bottom of top rail.

>> LOCATE RUB PROTECTOR @ APPROX  
14-13/16" FOR TOP OF BOTTOM RAIL  
TO C/L  
OF RUB PROTECTOR

*EXTERIOR SIDE WALL  
PROTECTION*

- LOCATE RUB PROTECTOR @ APPROX 14-13/16" FOR TOP OF BOTTOM RAIL TO C/L OF RUB PROTECTOR

**11-Roof**

*TOP RAILS*

6-3/8" HEAVY DUTY EXTRUDED ALUM TOP RAILS

*ROOF SKIN*

.025 ONE PIECE ALUM COIL ROOF SKIN

*ROOF BOWS*

- 1" EXTRU ALUM "J" SHAPE ROOF BOWS ON 24" C/L

**12-Rear Doors**

*REAR DOOR TYPE*

UTM BARRIER DESIGN DOUBLE SWING REAR DOORS

*REAR DOOR PANELS*

- .040 TRANSLITE POLISHED ALUMINUM DIAMOND PATTERN REAR DOOR PANELS

*REAR DOOR CROSSBRACES*

- EXTEND REAR DOOR HAT SECTION FULL WIDTH WHERE IT MEETS WITH LOWER C/S VENT

*REAR DOOR LOCK RODS*

- (1) ADDL REAR DOOR LOCKROD ON CURBSIDE FOR A TOTAL OF (3)

*REAR DOOR HINGES*

- (5) REAR DOOR HINGES PER DOOR

*REAR DOOR HINGES*

- REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT PREVENTION

*VENT DOOR REAR*

- 6" X 16" REAR VENT W/STAINLESS STEEL COVER ON LOWER C/S (INCLUDES VENT OPENING SCREEN)

*HOLDBACKS*

CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS

*REAR CASE & BUCKPLATE  
MATERIAL*

SST REAR DOOR CASE FOR SWING DOORS

*REAR CASE CORNER POSTS &  
HEADER*

- SHALLOW REAR WEDGE PORTION OF REAR SWING DOOR HEADER FROM 1-1/8" TO 1/2"

*REAR GUSSETS*

ENHANCED REAR CORNER GUSSET DESIGN FOR IMPROVED  
BOTTOM RAIL STRENGTH AT REAR OF TRAILER

*GRAB HANDLE AT REAR OF  
TRAILER*

- 36" LONG CHROME PLATED GRABHANDLE ON C/S EDGE OF R/S  
DOOR

*REAR DOOR HINGE MATERIAL*

NON-POLISHED ALUMINUM

*REAR DOOR HINGE PIN  
MATERIAL*

- **\*\*NOTE\*\*** Stainless Steel Hinge Pins

*CORROSION RESISTANT REAR  
DOOR HARDWARE*

- CORROSION RESIST ELECTROPOLISHED SST REAR DOOR  
HARDWARE SWING DRS (INCL NON-POLISHED ALUM HINGES)

**14-Floor**

*FLOOR TYPE*

- 20,000LBS 1-1/2" NOM EXTRUDED ALUM HIGH WEAR DUCT FLR  
KNURLED

*FLOOR TURN UP*

10" HIGH 3/16" HEAVY DUTY EXTRU ALUM NON-TAPERED W/B  
INTEGRAL W/FLOOR (INCLUDES REINFORCING)

*TROUGHS*

EXTRU ALUM TROUGH FRONT & REAR

*DRAINS*

(2) DRAINS FRONT AND (2) REAR

*REAR THRESHOLD*

HEAVY DUTY EXTRU ALUM WEDGE TYPE REAR THRESHOLD W/(4)  
DOCK BOARD GUIDE PLATES

*FORK LIFT REINFORCING*

BEARING GRID SYS AT REAR W/HDWD FILLERS FULL LENGTH &  
ALUM I CORES REAR 36" OF FLR IN CTR 68"

*STUB POSTS*

SIDEWALL STUB POST ON 48" C/L

**15-Insulation**

*INSULATION TYPE*

POLYURETHANE INSULATION FOAMED IN PLACE

*FRONT WALL THICKNESS*

4" THICK FRONT WALL

*SIDE WALL THICKNESS*

- 1-1/2" SIDEWALL INSULATION

*ROOF THICKNESS*

- 2" ROOF INSULATION

*FLOOR THICKNESS*

- 2" FLOOR INSULATION

*REAR DOOR THICKNESS*

3" THICK REAR DOORS

*CROSSMEMBER FLOOR  
FILLERS*

HARDWOOD FLOOR FILLERS FULL LENGTH

*FLOOR UNDERSKIN*

.035 THERMOPLASTIC FLOOR UNDERSKIN

**16-Lining**

*FRONT WALL LINING*

.065 (NOM) VERSITEX-UTILITY VR2U FRONT WALL LINING

*SIDE WALL LINING*

.065 (NOM) VERSITEX-UTILITY VR2U SIDE WALL LINING

*ROOF LINING*

.065 (NOM) VERSITEX-UTILITY VR2U ROOF LINING

*REAR DOOR LINING*

.065 (NOM) VERSITEX-UTILITY VR2U REAR DOOR LINING

WEARBAND	➤ 6" EXTRA HEIGHT EXTRUDED ALUM STD DUTY WEARBAND TOTAL OF 16" INCL REINFORCING BEHIND WEARBAND
LOGISTIC RAILS	➤ LOCATE E-TRACK @ 54" FROM TOP OF FLOOR TO C/L OF TRACK
LOGISTIC RAILS	➤ (1) ROS SERIES "E" GALV RECESS MTD LOG TRACK FOR USE W/1-1/2" SIDE WALL INSULATION
LOGISTIC RAIL SPL MODIFICATION	➤ REINFORCE "A" OR "E" TYPE LOG TRACK FOR DOUBLE DECKING
WEARBAND ON REAR SWING DOORS	➤ 16" HIGH X 1/8" SMOOTH ALUM WEARBAND W/BEVELED EDGES ON REAR SWING DOORS INCL HARDWOOD REINF
REAR DOOR LINING COVER	24" HIGH EXTRU ALUM REAR DOOR LINING EDGE PROTECTOR

#### 17-Electrical System

MAIN HARNESS	UTM MOISTURE RESISTANT "MULTI- PURPOSE" HARNESS W/INTERNAL GROUND AND 7-WAY PLUG
ELECTRICAL RECEPTACLE	7-WAY ELECTRICAL RECEPTACLE W/O CIRCUIT BREAKERS
CLEARANCE LIGHT QUANTITY	➤ 2-3-4-5 CLEARANCE LIGHT PACKAGE (INCLS CLEARANCE LIGHT ON BTM RAIL ABOVE COMBO)
ADDITIONAL STOP/TAIL LIGHTS	➤ ONE ADDL STOP/TAIL LIGHT EACH SIDE ON SST BUCK PLATE WITH EXTENDED LIGHT PROTECTOR BAR
SIDE MOUNTED DIRECTIONAL LIGHT	GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE
STOP/TAIL/TURN LIGHTS	➤ GROTE 4"DIA SST SNAP-IN FLANGE MTD LED(10 DIODE) S/T/T LIGHTS (ENHANCES THEFT RESISTANCE)
LICENSE LIGHT	GROTE MICRONOVA L.E.D. LICENSE LIGHT
CONSPICUITY TAPE LOCATION	CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER (FOR D.O.T. MINIMUM LOCATION)
CONSPICUITY TAPE	FACTORY CHOICE CONSPICUITY TAPE
UPPER CLEARANCE LIGHTS	FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L
LOWER CLEARANCE LIGHTS	➤ LOWER REAR CLEAR/ABS LGTS MTD OUTBOARD ON FLUSH VERTICAL FACE OF REAR CORNER GUSSET R/S & C/S
ABS (ANTI-LOCK) WARNING LIGHT	GROTE MICRONOVA L.E.D. PC RATED LIGHT
STOP/TAIL/TURN LIGHT CONFIGURATION	GROUPED STOP/TAIL/TURN LIGHTS
REAR HEADER CLEARANCE LIGHTS	➤ (5) GROTE MICRONOVA L.E.D. MULTI-FUNCTION LIGHTS ON REAR SWING DOOR HEADER

#### 18-Finish Specifications

TOP FRONT & TOP SIDE RAIL FINISH	NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS
----------------------------------	--

<i>BOTTOM SIDE RAIL FINISH</i>	NATURAL ALUM FINISH BOTTOM SIDE RAILS
<i>FRONT CORNER POST FINISH</i>	NATURAL ALUMINIUM FINISH FRONT CORNER POSTS
<i>FRONT PANEL FINISH</i>	PREPAINTED WHITE FRONT PANELS
<i>SIDE PANEL FINISH</i>	PREPAINTED WHITE SIDE PANELS
<i>REAR DOOR PANEL FINISH</i>	PREPAINTED WHITE REAR DOOR PANEL FINISH
<i>FRONT APPROACH PLATE FINISH</i>	NATURAL ALUM FINISH FRONT APPROACH PLATE
<i>FRONT SUBFRAME ASSEMBLY FINISH</i>	FRONT SUBFRAME FULLY IMMERSSED IN BLACK RUST PREVENTATIVE FINISH (ZERO VOC HOT DIP)
<i>SUPPORT LEG FINISH</i>	UTM BLACK SCHARPF ON SUPPORT LEGS
<i>REAR SUBFRAME FINISH</i>	UTM BLACK SCHARPF ON REAR SUBFRAME
<i>REAR CASE FINISH</i>	SATIN FINISH STAINLESS STEEL REAR CASE
<i>VRTCL &amp; HORZNTL DOCK BMPR FINISH</i>	UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK SCHARPF ON VERTICAL DOCK BUMPER
<i>ROOF EXTERIOR FINISH</i>	NATURAL ALUM ROOF EXTERIOR FINISH

#### 19-Miscellaneous

<i>MUDFLAP TYPE</i>	BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS
<i>PERMIT HOLDER</i>	<p>☞ TRUCKLITE #97960 ROUND PERMIT HOLDER MTD ON FRONT WALL</p> <p>REQUIRED INFORMATION:</p> <p><u>Dealer must specify location of permit/document/registration holder on either R/S, C/S or C/L in special instructions unless otherwise stated in the option description.</u></p> <p>&gt;&gt; R/S</p>
<i>SIDE MOUNTED AERODYNAMIC AIR DEFLECTORS</i>	BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE SKIRT MTD BELOW BOTTOM RAIL

#### 20-Tires and Wheels

<i>22.5"X8.25"STANDARD WIDTH WHEELS</i>	☞ 8 - 22.5X8.25 ALCOA HIGH POLISH ULTRA ONE ALUMINUM 10H/P #881677 10 HAND HOLE
<i>22.5" STANDARD PROFILE TIRES</i>	☞ 8 - 11R 22.5 MICH X-LINE ENERGY-T2 14PLY 40.80"T/D,LOAD RNG'G' MAX SPEED RATED @75 MPH;

## Special Instructions

LOCATE E-TRACK @ 54" FROM TOP OF FLOOR TO C/L OF TRACK