

OTR #97603-97610



*The First Name In Trailers*

## **OCEAN TRAILER**

**Ryan Patzer**  
9076 RIVER ROAD  
DELTA, BC V4G 1B5  
Voice 604-940-0210  
Fax 604-940-0610

Trailer Quote Prepared For

***OCEAN TRAILER (RENTAL)***

***9076 RIVER ROAD***

***DELTA, BC V4G 1B5***

*10 - VS2DX*

*April 29, 2025*

---

## Specifications (☞ = Option to Base Model)

### 1-Model & Payload Capacity

MODEL	VS2DX
PAYLOAD CAPACITY	55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY
GROSS VEHICLE WEIGHT RATING	65,000 LBS GVWR
INTERNATIONAL IMPORTATION SPECIFICATIONS	☞ FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION
4000D-X100.25 SYSTEM	☞ 4000D-X100.25 SYSTEM; 4" C/L "A" SLOTS;ID WIDTH @LINING 100-1/4", @ W/B 100",TOL:+/-1/4";14GA POST
GREENHOUSE GAS COMPLIANCE	THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS
DQS UPDATE NUMBER	DQS UPDATE #190 (02/10/25)

### 2-Dimensions

LENGTH	☞ 36'0" OVERALL LENGTH
OVERALL HEIGHT	13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST HEIGHT
WIDTH	102-3/8" OVERALL WIDTH
INSIDE HEIGHT	☞ **NOTE** 110-1/2" inside height at front; 111" inside height at rear
INSIDE WIDTH	☞ **NOTE** 100" (+/- 1/4")inside width at wearband, 100-1/4" at lining (+/- 1/4")

### 3-Deck

DECK TYPE	☞ **NOTE** Straight Deck with 1/2" wedge
-----------	--

### 4-Front Subframe

FRONT SUBFRAME	☞ 3-1/2" DEEP H.D. BOX BEAM DESIGN FRT SUB W/5/16" TOP PLT, KINGPIN PLT AND APPROACH PLT
APPROACH PLATE	8 GA CARBON STEEL FULL WIDTH APPROACH PLATE
KINGPIN PLATE	3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE
KINGPIN TYPE	AAR HARDNESS CRUCIFORM KINGPIN
KINGPIN LOCATION	36" KINGPIN LOCATION
COVER PLATE	☞ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL

### 5-Support Legs

SUPPORT LEG LOCATION	☞ LANDING GEAR TO BE 105" FROM KP TO CL
SUPPORT LEG CRANK LOCATION	ROADSIDE SUPPORT LEG CRANK LOCATION

SUPPORT LEG BRACING

SUPPORT LEGS

➡ HEAVY DUTY SUPPORT LEG REINF

JOST A401 ENHANCED 50,000 LBS CAPACITY SUPPORT LEGS  
W/10"X10" ULTRA LOW PROFILE CUSHION FOOT

#### 6-Frame, Rails & Crossmembers

BOTTOM RAILS

10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS

CROSSMEMBERS FRONT SUB  
TO LEGS

2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE

CROSSMEMBERS OVER  
SUPPORT LEGS

(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON  
12" C/L OVER SUPPORT LEGS

CROSSMEMBERS LEGS TO  
REAR SUB

4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12"  
C/L LEGS TO REAR SUB

CROSSMEMBERS OVER REAR  
SUBFRAME

4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR  
SUB

#### 7-Rear Subframe

HORIZONTAL DOCK BUMPER

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK  
CLEARANCE X11"LG @ C/L OF BUMPER

VERTICAL &HORIZONTAL  
DOCK BUMPER

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX  
GROUND CLRN; MEETS IIHS-30% OFFSET TEST

#### 8-Suspension/Axles/Actuation

SLIDER SUSPENSION  
LOCATION

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION  
LOCATION FOR 96" OF SLDR TRAVEL

OIL SEALS

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL  
END SYSTEM)

AIR BRAKE CHAMBERS

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

AIR ACTUATION

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

SLACK ADJUSTERS

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE  
W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

HUBODOMETER

➡ STEMCO HUBODOMETER MTD ON AXLE

DUST SHIELDS

➡ DUST SHIELDS FOR 16-1/2" X 7" BRAKES

AIRRIIDE DUMP VALVES

HENDRICKSON AUTOMATIC DUMP VALVE

BRAKE LINING STYLE

HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX

AXLE SPINDLE NUTS

CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END  
SYSTEM)

HUB PILOTED SYS  
W/OUTBOARD DRUMS FOR  
16-1/2" X 7" BRAKES

BASE SPEC:STL JACKET 10STD HBPLT SYS W/OB BLNCD STL LT WT  
DRUMS 16-1/2"X7"BRKS FOR CNMET PRESET+

ANTILOCK BRAKE SYSTEMS  
(ABS)

BENDIX TABS-6 2S/1M ABS SYSTEM \*W/O ROLL STABILITY\*

WHEEL BEARING LUBRICATION	FACTORY CHOICE 80W-90 OIL
ANTI-DOCK WALK DEVICES	➡ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE
HUBODOMETER CALIBRATION	➡ CALIBRATE HUBODOMETER IN KILOMETERS
AXLE MANUFACTURER	HENDRICKSON "VENTED" AXLES
AXLE SPINDLE TYPE	N-SPINDLE TYPE (STANDARD WITH CONMET PRESET+ WHEEL END SYSTEM)
WHEEL BEARINGS (CONES) AND RACES (CUPS) MANUFACTURER	CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END SYSTEM)
SLIDER PIN RELEASE MECHANISM	HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING SYSTEM
CONMET WHEEL END SYSTEMS	BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT

#### 9-Front Wall

FRONT CORNER POST	.080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS
FRONT WALL POSTS	(4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL POSTS
FRONT PANELS	.040 ALUM FRONT PANELS
ELECTRICAL NOSEBOX	➡ UTM MULTI-FUNCT ZINC RECEPT/BOX W/BRAKE ACT RELAY;DUAL CIRCUIT; 60MIN TIMER;SWITCH;INDICATOR LGT
GLADHANDS & RECEPTACLE LOCATION	SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET 27-1/2" TO R/S FROM C/L OF TRAILER
FRONT TOP RAIL	EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL

#### 10-Side Walls

SIDE PANELS	COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC POLYURETHANE FOAM CORE BONDS INT/EXT PANELS)
SIDE POSTS	➡ <b>**NOTE**</b> Side posts are located on 16" C/L over the front sub and 24" C/L to rear

#### 11-Roof

TOP RAILS	4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS
ROOF SKIN	.040 ONE PIECE ALUM COIL ROOF SKIN
ROOF BOWS	➡ <b>**NOTE**</b> 1" anti snag 16ga galv steel hat shaped roof bows on 24" C/L

#### 12-Rear Doors

REAR CASE & BUCKPLATE MATERIAL	SATIN FINISH SST REAR DOOR CASE
--------------------------------	---------------------------------

REAR DOOR ROLLUP TYPE	➤ TODCO 1/2" ARMORPLATE ROLL-UP DOOR W/ PPW FACE (4-3/4" REAR CORNER POST)
INSTALL REAR LIFT GATE	➤ FURNISH AND INSTALL MAXON BMR 55G - PWR DWN/ COMBO NOSE BOX / DUAL PUMP
PREP FOR REAR LIFT GATE	➤ PREP FOR MAXON BMR (BOLT-ON OR WELD-ON) LIFTGATE INCL LOWERED BOLT-ON S/T/T LGTS FOR 7" BUMPER
REAR TREADPLATE	.219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE INTEGRAL WITH REAR BUCKPLATE
ROLL UP DOOR TRACK GUARD FOR 4000D-X	➤ EXTRUDED ALUMINUM TRACK GUARD FOR ROLL UP DOOR (FOR USE WITH STEEL-LINED TRAILERS ONLY)

#### 14-Floor

FLOOR TYPE	20,000LB 1-3/8" NOM LAM HDWD FLR; FACTORY CHOICE: OAK OR SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM
FLOOR JOINT SEALANT	CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT

#### 16-Lining

FRONT WALL LINING	.016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING
SIDE WALL LINING	PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING
WEARBAND	➤ 5/8" X 24" NOM HDPE PLASTIC W/B WITH RECESSED FASTENERS
IMPACT PROTECTION (BANG PLATES)	➤ 16GA STEEL X 13" HIGH FULL WIDTH FRONT WALL BANG PLATE
WEARBAND ON FRONT	14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL WEARBAND
SIDE WALL LINING CLOSURES	45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING CLOSURES

#### 17-Electrical System

MAIN HARNESS	UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH INTERNAL GROUND AND 7-WAY PLUG
ELECTRICAL RECEPTACLE	7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED
CLEARANCE LIGHT QUANTITY	➤ 2-1-2-5 CLEARANCE LIGHT PACKAGE
DOMELIGHTS MOUNTED IN CEILING	➤ 4 - GROTE SUPERNOVA 24-DIODE L.E.D. DOMELIGHT W/O SWITCH REC MTD IN CEILING PERPENDICULAR TO SIDEWALL
SIDE MOUNTED DIRECTIONAL LIGHT	GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE
STOP/TAIL/TURN LIGHTS	GROTE 4" L.E.D. (10-DIODE) STOP/ TAIL/TURN LIGHTS (2) PER SIDE WITH BLACK SNAP-IN FLANGE
LICENSE LIGHT	GROTE MICRONOVA L.E.D. LICENSE LIGHT

*SWITCHES FOR DOME/SPOT LIGHTS*

➡ (1) MOMENTARY SWITCH FOR DOME/ SPOT LIGHTS, RECESS MTD IN C/S REAR CORNER POST

*CONSPICUITY TAPE LOCATION*

CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION

*CONSPICUITY TAPE*

FACTORY CHOICE CONSPICUITY TAPE

*UPPER CLEARANCE LIGHTS*

FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L

*LOWER CLEARANCE LIGHTS*

GROTE MICRONOVA LED PC RATED LIGHT

*ABS (ANTI-LOCK) WARNING LIGHT*

GROTE MICRONOVA L.E.D. PC RATED LIGHT

*STOP/TAIL/TURN LIGHT CONFIGURATION*

GROUPED STOP/TAIL/TURN LIGHTS

*REAR HEADER CLEARANCE LIGHTS*

GROTE MICRONOVA L.E.D. PC RATED GROMMET MOUNTED REAR HEADER ID/ CLR LIGHTS

#### **18-Finish Specifications**

*TOP FRONT & TOP SIDE RAIL FINISH*

NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS

*BOTTOM SIDE RAIL FINISH*

NATURAL ALUM FINISH BOTTOM SIDE RAILS

*FRONT CORNER POST FINISH*

NATURAL ALUMINIUM FINISH FRONT CORNER POSTS

*FRONT PANEL FINISH*

PREPAINTED WHITE FRONT PANELS

*SIDE PANEL FINISH*

PREPAINTED WHITE SIDE PANELS

*FRONT SUBFRAME ASSEMBLY FINISH*

FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED

*SUPPORT LEG FINISH*

BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS

*REAR SUBFRAME FINISH*

BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME

*REAR CASE FINISH*

SATIN FINISH STAINLESS STEEL REAR CASE

*VRTCL & HORZNTL DOCK BUMPR FINISH*

UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK SCHARPF ON VERTICAL DOCK BUMPER

*ROOF EXTERIOR FINISH*

NATURAL ALUM ROOF EXTERIOR FINISH

*REAR DOOR COLOR*

PREPAINTED WHITE REAR DOORS

*FLOOR UNDERCOAT*

BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

#### **19-Miscellaneous**

*MUDFLAP TYPE*

BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH STEEL REINFORCING STRAPS

*PERMIT HOLDER*

➡ BETTS PS-1 ROUND PERMIT HOLDER MTD ON FRONT WALL

REQUIRED INFORMATION:

Dealer must specify location of permit/document/registration holder on either R/S, C/S or C/L in special instructions unless otherwise stated in the option description.

>>

*SIDE MOUNTED  
AERODYNAMIC AIR  
DEFLECTORS*

➡ OMIT BASE SPEC UTM USS120A-4 AERODYNAMIC SIDESKIRTS

**20-Tires and Wheels**

*22.5"X8.25"STANDARD WIDTH  
WHEELS*

➡ 8 - 22.5X8.25 ACRD 51487PKWHT21PWDR COAT WHITE 10H/P W/SHH -  
NEXTGEN ACCU-LITE

*22.5" LOW PROFILE TIRES*

8 - 295/75R 22.5 MICH X-LINE ENERGY -T2 14PLY 39.70"TD,LOAD  
RG'G' MAX SPEED RATED@75 MPH;

---

## Special Instructions

CONFIRM THAT WEARBAND IS INSTALLED SAME AS JOB 2008-G-4418

RUN INTERIOR DOMELIGHT OFF OF MARKER CIRCUIT TO HAVE LIGHTS ON WHEN KEY IS OUT OF  
IGNITION

DOMELIGHTS TO BE CENTERED ON FROM SIDEWALL AND EVENLY SPACED FRONT TO REAR.

---

---

## Terms & Conditions

<b>Phone</b>	
<b>Email</b>	
<b>Quoted By</b>	Joe Carrico
<b>Email</b>	jcarrico@maxonlift.com

<b>Quote Date</b>	
<b>Quote Valid Until</b>	
<b>End User</b>	()
<b>Leasing</b>	()

<b>Sold To</b>	(EU592) OCEAN TRAILERS USA
<b>Phone:</b>	

<b>Ship To</b>	(EU592) OCEAN TRAILERS
<b>ATTN:</b>	

Un-Laden Bed Height: 50.00"	Bed Height Range: 44"-56"	Vehicle Width: 102"	Platform Material: Steel
-----------------------------	---------------------------	---------------------	--------------------------

Ln#	Qty	Part Number
1	1	BMR55SG85424216PDG-1457      BMR-55 LIFTGATE BMR-55 (5500 LB Capacity) for 102" Wide Weld-On, Galvanized Extension Plate Galvanized Finish with Rollers Steel Galvanized Platform 84" x 85" Wide (42+42 Split) 16" Aluminum Retention Ramp Power Down on Demand Dual Pump/Motor  Selected Options: 20 foot Pump Extension Kit Cycle Counter Exxon Univis 13 Hydraulic Oil - 1 Gallon(s) Composite Battery Box (holds 2 batteries-batteries not included) Trailer Charge Line with Combo Single & Dual Pole Nose Box Dual Hanger Frame for Pump & Battery Boxes
2	1	FRT-W-RCBM      FREIGHT WEST RC BMRA

Please contact your Maxon  
Distributor for Pricing

**Notes :**

This quote is CONFIDENTIAL and is only intended for the person named above. Quotations do not include any applicable sales tax. Please confirm any necessary sales tax prior to order.

Accepted by : \_\_\_\_\_ Date : \_\_\_\_\_ PO# : \_\_\_\_\_ Page 1 of 1