



**C. Keay Investments Ltd.**

**Will Tucker**  
100 Golden Drive  
Coquitlam, BC V3K 6T1  
Voice 604-945-3718

Trailer Quote Prepared For

***OCEAN TRAILER STOCK***  
***9076 RIVER ROAD***  
***DELTA, BC V4G 1B5***

*20 - VS2DX*  
*July 18, 2025*

---

## Specifications (☞ = Option to Base Model)

### 1-Model & Payload Capacity

|  |   |
|--|---|
| MODEL                                    | VS2DX   |
| PAYLOAD CAPACITY                         | 55,000 LBS EVENLY DISTRIBUTED PAYLOAD CAPACITY  |
| SPECIAL TRAILER APPLICATION              | TALL BOTTOM RAIL(TBR) FOR 4000DX 101.25 SYSTEM (REQUIRES A MIN. 20,000LB FLOOR RATING)            |
| GROSS VEHICLE WEIGHT RATING              | 65,000 LBS GVWR   |
| INTERNATIONAL IMPORTATION SPECIFICATIONS | ☞ FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION                        |
| 4000D-X101.25 SYSTEM                     | BASE SPEC:4000DX101.25 SYS;8"C/L "A"SLOT;ID WIDTH@LINING 101-1/4" @W/B 101",TOL:+/-1/4";14GA POST |
| GREENHOUSE GAS COMPLIANCE                | THIS TRAILER IS NOT UTMG GHG2 CERTIFIED, GHG2 CERTIFICATION MAY REQUIRE ADDL OPTIONS/COSTS        |
| DQS UPDATE NUMBER                        | DQS UPDATE #191 (05/01/25)  |

### 2-Dimensions

|                |  |
|----------------|--|
| LENGTH         | 53'0" OVERALL LENGTH   |
| OVERALL HEIGHT | 13'6" O/A HEIGHT ON 46-1/2" FIFTH HEIGHT FOR 110-3/16" POST HEIGHT |
| WIDTH          | 102-3/8" OVERALL WIDTH   |
| INSIDE HEIGHT  | 110-1/2" INSIDE HEIGHT AT FRONT; 111" INSIDE HEIGHT AT REAR        |
| INSIDE WIDTH   | 101" INSIDE WIDTH AT WEARBAND (+/- 1/4" TOLERANCE)                 |

### 3-Deck

|           |                               |
|-----------|-------------------------------|
| DECK TYPE | STRAIGHT DECK WITH 1/2" WEDGE |
|-----------|-------------------------------|

### 4-Front Subframe

|                  |  |
|------------------|--|
| FRONT SUBFRAME   | 3-1/2" DEEP BOX BEAM DESIGN FRONT SUBFRAME RAISED 1-3/8" FLUSH WITH TOP OF FLOOR |
| APPROACH PLATE   | 1/4" HIGH STRENGTH STEEL APPROACH PLATE  |
| KINGPIN PLATE    | 3 GA HIGH STRENGTH STEEL FULL WIDTH KINGPIN PLATE                                |
| KINGPIN TYPE     | AAR HARDNESS CRUCIFORM KINGPIN   |
| KINGPIN LOCATION | 36" KINGPIN LOCATION   |
| COVER PLATE      | ☞ EXTRUDED ALUMINUM COVER PLATE ON LOWER FRONT WALL                              |

### 5-Support Legs

|                      |  |
|----------------------|--|
| SUPPORT LEG LOCATION | SUPPORT LEG LOCATION OF 105" FROM C/L OF KINGPIN |
|----------------------|--|

SUPPORT LEG CRANK  
LOCATION

ROADSIDE SUPPORT LEG CRANK LOCATION

SUPPORT LEG BRACING

BOLT-ON CROSS BRACING WITH 7 GA 3-1/4" DEEP HIGH STRENGTH  
STEEL CHANNEL

SUPPORT LEGS

➡ JOST MODEL A451 MAGNUM SUPPORT LEGS W/10-YR WARRANTY &  
10"X10" ULTRA LOW PROFILE CUSHION FOOT

#### 6-Frame, Rails & Crossmembers

BOTTOM RAILS

10-5/8" DEEP HEAVY DUTY EXTRU ALUMINUM BOTTOM RAILS

CROSSMEMBERS FRONT SUB  
TO LEGS

2-3/16" STEEL HAT SHAPED C-MEMS WITH CONTINUOUS ENDPLATE

CROSSMEMBERS OVER  
SUPPORT LEGS

(5) 4" STEEL I BEAM CROSSMEMBERS WITH (4) RIVET END CLIPS ON  
12" C/L OVER SUPPORT LEGS

CROSSMEMBERS LEGS TO  
REAR SUB

4" STEEL I BEAM CROSSMEMBERS W/ (4) RIVET END CLIPS ON 12"  
C/L LEGS TO REAR SUB

CROSSMEMBERS OVER REAR  
SUBFRAME

4" STL I BEAM C-MEMS W/(4) RIVET END CLIPS 12" C/L OVER REAR  
SUB

#### 7-Rear Subframe

HORIZONTAL DOCK BUMPER

BASE SPEC: 7"HRZ BMPR W/ 1/4" REINF PLATE & 2"ADDL DOCK LOCK  
CLEARANCE X11"LG @ C/L OF BUMPER

RUBBER DOCK BUMPERS

➡ (1) PAIR RUBBER DOCK BUMPERS 1/2" PROUD

VERTICAL &HORIZONTAL  
DOCK BUMPER

BASE SPEC:DOT VERT W/NONSLIP 7" HORIZONTAL 22" MAX  
GROUND CLRN; MEETS IIHS-30% OFFSET TEST

#### 8-Suspension/Axles/Actuation

SLIDER SUSPENSION  
LOCATION

70" REAR SUSPENSION LOCATION AND 166" FORWARD SUSPENSION  
LOCATION FOR 96" OF SLDR TRAVEL

OIL SEALS

CONMET PREMIUM OIL SEALS (INCL W/ CONMET PRESET+ WHEEL  
END SYSTEM)

AIR BRAKE CHAMBERS

BENDIX ENDURASURE 3030 AIR BRAKE CHAMBERS

AIR ACTUATION

ONE TANK AIR ACTUATION SYSTEM W/SPRING BRAKES

SLACK ADJUSTERS

BENDIX VERSAJUST AUTOMATIC SLACK ADJUSTERS FOR USE  
W/BENDIX ENDURASURE OR TSE BRAKE CHAMBERS

HUBODOMETER

➡ STEMCO HUBODOMETER MTD ON AXLE

DUST SHIELDS

➡ DUST SHIELDS FOR 16-1/2" X 7" BRAKES

AIRRIIDE DUMP VALVES

HENDRICKSON AUTOMATIC DUMP VALVE

BRAKE LINING STYLE

HENDRICKSON HXS BRAKE LINING STYLE FOR USE W/ INTRAAX

AXLE SPINDLE NUTS

CONMET SPINDLE NUT (INCL. W/ CONMET PRESET+ WHEEL END  
SYSTEM)

|   |   |
|---|---|
| <i>HUB PILOTED SYS<br/>W/OUTBOARD DRUMS FOR<br/>16-1/2" X 7" BRAKES</i> | BASE SPEC:STL JACKET 10STD HBPLT SYS W/OB BLNCD STL LT WT<br>DRUMS 16-1/2"X7"BRKS FOR CNMET PRESET+ |
| <i>ANTILOCK BRAKE SYSTEMS<br/>(ABS)</i>                                 | BENDIX TABS-6 2S/1M ABS SYSTEM *W/O ROLL STABILITY*   |
| <i>WHEEL BEARING<br/>LUBRICATION</i>                                    | FACTORY CHOICE 80W-90 OIL   |
| <i>ANTI-DOCK WALK DEVICES</i>   | ➤ HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH<br>MANUAL DUMP VALVE                       |
| <i>WHEEL SEPARATOR PLATES</i>   | ➤ NYLON WHEEL GUARD SEPARATOR PLATE BTWN INNER WHEEL &<br>HUB                                       |
| <i>AXLE MANUFACTURER</i>  | HENDRICKSON "VENTED" AXLES  |
| <i>AXLE SPINDLE TYPE</i>  | ➤ P-SPINDLE TYPE FOR USE WITH CONMET PRESET PLUS WHEEL END<br>SYSTEM                                |
| <i>AUTOMATIC TIRE INFLATION<br/>SYSTEM</i>                              | ➤ HEND TIREMAAX PRO TIRE INFL SYS W/WARN LGT ON FRONT<br>CORNER *RETAINS CONMET 8YR WARRANTY*       |
| <i>LOAD SCALE KIT</i>   | ➤ HENDRICKSON AKLS1006 LOAD SCALE (INCLS MANUAL DUMP<br>VALVE) IN FULLY ENCLOSED POLYCARBONATE BOX  |
| <i>WHEEL BEARINGS (CONES)<br/>AND RACES (CUPS)<br/>MANUFACTURER</i>     | CONMET BEARINGS (INCL W/ CONMET PRESET+ WHEEL END<br>SYSTEM)  |
| <i>HENDRICKSON AIRRIDE<br/>SYSTEMS WITH INTEGRAL<br/>AXLES</i>          | BASE SPEC:HEND ULTRAA-K AIRRIDE/ SLDR SYS,INCLS 49" AXL<br>SPRD,HD SLDR & ZERO MAINT DAMPING (ZMD)  |
| <i>SLIDER PIN RELEASE<br/>MECHANISM</i>                                 | HENDRICKSON QUIK DRAW AIR OPERATED SLIDER REPOSITIONING<br>SYSTEM                                   |
| <i>CONMET WHEEL END SYSTEMS</i>   | BASE SPEC:CONMET PRESET+IRON HUB SYSTEM,INCL:CONMET<br>PREMIUM SEAL,BEARING,SPACER &SPINDLE NUT     |

**9-Front Wall**

|  |  |
|--|--|
| <i>FRONT CORNER POST</i>                       | .080 EXTRUDED ALUM 4-3/4" RADIUS FRONT CORNER POSTS  |
| <i>FRONT WALL POSTS</i>                        | (4) 2" 14 GA HIGH STRENGTH STEEL HAT SHAPED FRONT WALL<br>POSTS                              |
| <i>FRONT PANELS</i>                            | .040 ALUM FRONT PANELS   |
| <i>GLADHANDS &amp; RECEPTACLE<br/>LOCATION</i> | SURFACE MTD GLADHANDS (W/SCREEN) AND RECEPTACLE OFFSET<br>27-1/2" TO R/S FROM C/L OF TRAILER |
| <i>FRONT TOP RAIL</i>                          | EXTRUDED ALUM WRAPAROUND FRONT TOP RAIL  |

**10-Side Walls**

|                    |   |
|--------------------|---|
| <i>SIDE PANELS</i> | COMPOSITE PANEL SIDEWALL DESIGN (INJECTED NON-HFC<br>POLYURETHANE FOAM CORE BONDS INT/EXT PANELS) |
|--------------------|---|

|   |  |
|---|--|
| <i>SIDE POSTS</i>                         | 3/8" 14GA HIGH STR GALV HAT SHPD 24"C/L (FRT/RR SUB 16"C/L)<br>W/"A" SLOTS ON 8" VERT C/L            |
| <i>EXTERIOR SIDE WALL PROTECTION</i>      | ➤ RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE                |
| <i>EXTERIOR SIDE WALL PROTECTION</i>      | ➤ LOCATE RUB PROTECTOR @ APPROX 6" FROM TOP OF RUB RAIL TO C/L OF RUB PROTECTOR                      |
| <b>11-Roof</b>                            |  |
| <i>TOP RAILS</i>                          | 4-1/2" DEEP HEAVY DUTY EXTRUDED ALUMINUM TOP RAILS   |
| <i>ROOF SKIN</i>                          | .040 ONE PIECE ALUM COIL ROOF SKIN   |
| <i>ROOF BOWS</i>                          | 1-1/16" ANTI SNAG 18GA GALV STL HAT SHAPED ROOF BOWS<br>16"C/L(FRT/ RR SUB 24"C/L)BONDED TO ROOF SKN |
| <b>12-Rear Doors</b>                      |  |
| <i>REAR DOOR TYPE</i>                     | COMPOSITE REAR SWING DOORS   |
| <i>REAR DOOR PANELS</i>                   | 1/2" COMPOSITE REAR SWING DOORS (PRE-PAINTED WHITE GALV STEEL PANELS W/POLYETHYLENE CORE)            |
| <i>REAR DOOR LOCK RODS</i>                | (1) REAR DOOR LOCK ROD PER DOOR  |
| <i>REAR DOOR HINGES</i>                   | ➤ REAR DOOR ANTI-THEFT TAMPER PROOF HARDWARE FOR THEFT   |
| <i>REAR DOOR HINGES</i>                   | ➤ (1) ADDITIONAL PAIR OF REAR DOOR HINGES  |
| <i>HOLDBACKS</i>                          | CHAIN LINK AND HOOK TYPE DOOR HOLDBACKS  |
| <i>REAR CASE &amp; BUCKPLATE MATERIAL</i> | SATIN FINISH SST REAR DOOR CASE  |
| <i>GRAB HANDLE AT REAR OF TRAILER</i>     | ➤ 36" VERT BOLT-ON CHROME-PLATED GRABHANDLE ON C/S EDGE OF R/S SWING DOOR                            |
| <i>REAR TREADPLATE</i>                    | .219 HIGH STRENGTH STEEL X 27" DEEP STEEL REAR TREADPLATE<br>INTEGRAL WITH REAR BUCKPLATE            |
| <i>REAR DOOR HINGE MATERIAL</i>           | NON-POLISHED ALUMINUM  |
| <b>14-Floor</b>                           |  |
| <i>FLOOR TYPE</i>                         | 20,000LB 1-3/8"NOM LAM HDWD FLR; FACTORY CHOICE:OAK OR SUGAR MPL W/(3) SCREWS PER BOARD PER CMEM     |
| <i>FLOOR JOINT SEALANT</i>                | CAULKING APPLIED PRIOR TO ASSEMBLY BETWEEN EACH JOINT  |
| <b>16-Lining</b>                          |  |
| <i>FRONT WALL LINING</i>                  | .016 PPW GALV HIGH STRENGTH STEEL FRONT WALL LINING  |
| <i>SIDE WALL LINING</i>                   | PRE-PAINTED WHITE GALV STEEL "ANTI-SNAG" SIDEWALL LINING   |
| <i>WEARBAND</i>                           | ➤ 14GA X 5/16" X 8" NOM GALV STL HD SIDEWALL WEARBAND FOR USE WITH TALL BOTTOM RAIL (TBR)            |
| <i>WEARBAND ON FRONT</i>                  | 14GA X 14" EXTRA HEAVY DUTY CORRUGATED GALV STEEL WEARBAND   |

*SIDE WALL LINING CLOSURES*

45 DEGREE FRONT CORNER DIAGONAL SIDE WALL LINING CLOSURES

**17-Electrical System**

*MAIN HARNESS*

UTM MOISTURE RESISTANT "BASIC" 6-WIRE CABLE HARNESS WITH INTERNAL GROUND AND 7-WAY PLUG

*ELECTRICAL RECEPTACLE*

7-WAY RECEPTACLE WITHOUT CIRCUIT BREAKERS SURFACE MOUNTED

*CLEARANCE LIGHT QUANTITY*

➡ 2-1-2-5 CLEARANCE LIGHT PACKAGE

*ADDITIONAL STOP/TAIL LIGHTS*

➡ ONE ADDITIONAL STOP/TAIL LIGHT EACH SIDE WITH EXTENDED LIGHT PROTECTOR BAR

*SIDE MOUNTED DIRECTIONAL LIGHT*

GROTE SUPERNOVA LED COMBO SIDE MTD DIR/CLRN LIGHT ON BRACKET BELOW BOTTOM RAIL EACH SIDE

*STOP/TAIL/TURN LIGHTS*

GROTE 4" L.E.D. (10-DIODE) STOP/ TAIL/TURN LIGHTS (2) PER SIDE WITH BLACK SNAP-IN FLANGE

*LICENSE LIGHT*

GROTE MICRONOVA L.E.D. LICENSE LIGHT

*CONSPICUITY TAPE LOCATION*

CONSPICUITY TAPE ON BOTTOM RAILS AND AT REAR OF TRAILER FOR D.O.T. MINIMUM LOCATION

*CONSPICUITY TAPE*

FACTORY CHOICE CONSPICUITY TAPE

*UPPER CLEARANCE LIGHTS*

FACTORY CHOICE LED UPPER SIDE RAIL CLEARANCE LIGHTS WITH 3" MOUNTING HOLE C/L

*LOWER CLEARANCE LIGHTS*

GROTE MICRONOVA LED PC RATED LIGHT

*ABS (ANTI-LOCK) WARNING LIGHT*

GROTE MICRONOVA L.E.D. PC RATED LIGHT

*STOP/TAIL/TURN LIGHT CONFIGURATION*

GROUPED STOP/TAIL/TURN LIGHTS

*REAR HEADER CLEARANCE LIGHTS*

➡ (5) 3" GROTE LED THINLINE MULTI FUNCTION CLEARANCE/MARKER LIGHTS ON REAR HEADER

**18-Finish Specifications**

*TOP FRONT & TOP SIDE RAIL FINISH*

NATURAL ALUM FINISH TOP FRONT & TOP SIDE RAILS

*BOTTOM SIDE RAIL FINISH*

NATURAL ALUM FINISH BOTTOM SIDE RAILS

*FRONT CORNER POST FINISH*

NATURAL ALUMINIUM FINISH FRONT CORNER POSTS

*FRONT PANEL FINISH*

PREPAINTED WHITE FRONT PANELS

*SIDE PANEL FINISH*

PREPAINTED WHITE SIDE PANELS

*FRONT SUBFRAME ASSEMBLY FINISH*

FRONT SUB FULLY FLOODED INSIDE WITH BLACK RUST PREVENTATIVE FINISH, TOP PLATE PRIME PAINTED

*SUPPORT LEG FINISH*

BLACK RUST PREVENTATIVE COATING ON SUPPORT LEGS

*REAR SUBFRAME FINISH*

BLACK RUST PREVENTATIVE COATING ON REAR SUBFRAME

REAR CASE FINISH

SATIN FINISH STAINLESS STEEL REAR CASE

VRTCL & HORZNTL DOCK  
BMPR FINISH

UTM BLACK ENAMEL FINISH ON HORIZ DOCK BUMPER; BLACK  
SCHARPF ON VERTICAL DOCK BUMPER

ROOF EXTERIOR FINISH

NATURAL ALUM ROOF EXTERIOR FINISH

REAR DOOR COLOR

PREPAINTED WHITE REAR DOORS

FLOOR UNDERCOAT

BLACK SEALER/PAINT ON BOTTOM OF WOOD FLOOR

#### 19-Miscellaneous

MUDFLAP TYPE

BLACK PLASTIC ANTI-SAIL MUDFLAPS W/UTM LOGO, MTD WITH  
STEEL REINFORCING STRAPS

PERMIT HOLDER

- TRUCKLITE #97960 ROUND PERMIT HOLDER MTD ON FRONT WALL  
REQUIRED INFORMATION:

Dealer must specify location of permit/document/registration holder on  
either R/S, C/S or C/L in special instructions unless otherwise stated in  
the option description.

>> R/S

SIDE MOUNTED  
AERODYNAMIC AIR  
DEFLECTORS

BASE SPEC:USS120A-4 "ADVANCED" AERODYNAMIC BLACK SIDE  
SKIRT MTD BELOW BOTTOM RAIL

#### 20-Tires and Wheels

22.5"X8.25"STANDARD WIDTH  
WHEELS

- 8 - 22.5X8.25 ALUM ACCURIDE 10 H/P; ACCU-LITE #43644SP STD  
POLISH (10 HAND HOLE)

22.5" STANDARD PROFILE  
TIRES

- 8 - 11R 22.5 MICH X-LINE ENERGY-T2 14PLY 40.80"T/D,LOAD RNG'G'  
MAX SPEED RATED @75 MPH;

---

## Special Instructions

None.

---

## Weight

Total Weight 13,209 lbs. (+/- 3%)

---

## Terms & Conditions