



Unit# 97959-70

## **Build Sheet**

**MODEL RSB-32L SUPER B TRI-AXLE LEAD ITEM ID:TBC MODEL YEAR:2026**

### **Body Structure**

**Dimensions:** Length 32'(Deck), Width 102" Front Deck Height 57" Rear Deck Height 54 1/2"  
**Beams:** Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"  
**Crossmembers:** 4" Super Light I Beam 16" Centers  
**Floor:** 1-5/16 BC Douglas Fir Shiplap  
**Side Rails:** 3.5" x 3.5" x 0.188" Steel Tube  
**Rub Rail:** Fully Welded 1/4" Round At Bottom Of Rail  
**Knee Braces:** Steel Tube @ 4/Side  
**Kingpin:** 30" Inset, 2.0" SAF Holland  
**Coupler Assembly** 3/8" Plate @ 48" Coupler Plate Height  
**Front Bolster:** Formed Front Bolster W/ 4 Integrated Stake Pockets  
**Rear Bolster:** Formed W/ 5 Integrated Stake Pockets  
**Rear Light Box:** Bolted Lightbox Steel - Half Width

### **Securement**

**Stake Pockets:** Integrated In Side Rail At 48" Centers  
**Pipe Spools:** N/A  
**Winches:** 19 – Bottom Mount 3 Bar Welded, Ocean Config(First Winch 16" Center From Front, 14 Winches CS Randomly Spaced, 5 Winches RS  
**J-Hooks:** Opposite Winches  
**Accessory Tie Flat Bar 2 1/2" X 3/8" Steel:** Yes  
**Tarp Rope Hooks:** Yes

### **Axles/Suspension/Tires/Wheels**

**Suspension:** Hendrickson AANT23K Air Ride with 3-23,000lb axles, HP Spindle, 60"-60" Spread -, 15" Ride Height, 77 1/2" Track Width,  
**Brakes:** HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Spring Brake Pots 30/30 TSE, Short 28 Spline Cam Bendix TABS-6 ABS w/Amber Warning Light (2 Sensors/1 Modulator), Dust Shields  
**Hubs:** ADI w/Long Studs, HXL5 5-year Wheel End Warranty, Semi Fluid CHEVRON DELO SF w/Ventless Hub/Vented Axle, Precision 320 Spindle Nut  
**Drums:** Fused  
**Tires:** 11R22.5 Cooper Roadmaster RM 872  
**Rims:** 22.5" x 8.25" Aluminum Better Hi Polish (inner & outer)

### **Ratings**

**Distributed Load:** 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,  
**GVWR:** 41,000kgs  
**Weight:** EST 11,400lbs





**Data:** Meets or Exceeds all Canadian Motor Vehicle Safety Standards

**Safety:** Reflective 2" Red/White Conspicuity Tape

## **Systems - Air/Electrical**

**Control Box:** SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

**Air System:** 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

**Air Tanks:** Steel Tank Air Brake 9.0" - 1488 Cu. In. Small, Tank Air Brake 12.0" - 2850 Cu. In. Large

**Air Lines:** Grote Hose Coiled Nylon 15.0' C/w 0.5" Male End 12" Lead Red&blue Combo w/Aluminum Anodized Gladhandle Set, Isolation Ball Valves

**Lighting:** 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side 5 - 3/4" Micro Nova In Rear Light Box Plate, 1 - License Plate Light,

## **Components**

**Document Holder:** 1 - Tube Style

**Landing Gear:** 62500lb Dual Speed SAF Holland Mark V With Low-Pro Sand Shoe

**Fifth Wheel Plate:** Hitch Fifth Wheel SAF Holland FW35 5.6" Height

## **Options**

**Toolbox:** Aluminum Tool Box w/Barn Doors, Grote LED int Light 24"h x 23"d x 60" 1 Curb Side(STD)

**Paint:** Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Black

**Fenders:** Aluminum Checker Plate above 2nd axle

**Dunnage Rack:** Cross-frame carrier, 2 - 3 Bar Winches/j-hooks

**Dunnage Basket:** 0

**Dunnage Box:** 0

**Wide Load Pull Out Lights –** 0

**Steps:** Steel Access Step between 2nd and 3rd axle - Curb/Road Side

**Mudflaps:** 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

**Strobe Lights:** 0

**Tire Chain Carrier Formed:** Undermount Curb Side - 1





# **Build Sheet**

**MODEL: RSB-28R SUPER B TANDEM AXLE REAR ITEM ID:17380    MODEL YEAR:2026**

## **Body Structure**

**Dimensions:** Length 28'(Deck), Width 102" Front Deck Height 55 3/4" Rear Deck Height 50 1/2",

**Beams:** Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"

**Crossmembers:** 4" Super Light I Beam 16" Centers

**Floor:** 1-5/16 BC Douglas Fir Shiplap

**Side Rails:** 3.5" x 3.5" x 0.188" Steel Tube

**Rub Rail:** Fully Welded 1/4" Round At Bottom Of Rail

**Knee Braces:** Steel Tube @ 2/Side

**Kingpin:** 19"(Std) Inset, 2.0" SAF Holland

**Coupler Assembly** 3/8" Plate @ 48" Coupler Plate Height

**Front Bolster:** Formed Front Bolster W/ 4 Integrated Stake Pockets

**Rear Bolster:** Formed W/ 5 Integrated Stake Pockets

**Impact Guard:** Weld On, Meets CMVSS

## **Securement**

**Stake Pockets:** Formed, 48" Centers

**Pipe Spools:** N/A

**Winches:** 16 – Bottom Mount 3 Bar Welded, Ocean Config(First Winch 15" Center From Front, 12 Winches CS Randomly Spaced, 4 Winches RS

**Cross Tie Winches:** Yes – Welded At Rear With J/Hooks

**J-Hooks:** Opposite Winches

**Accessory Tie Flat Bar 2 1/2" X 3/8" Steel:** Yes

**Tarp Rope Hooks:** Yes

## **Axles/Suspension/Tires/Wheels**

**Suspension:** Hendrickson AANT23K Air Ride with 2-23,000lb axles, HP Spindle, 50" Spread, 39 1/2" Inset -, 14.5" Ride Height, 77 1/2" Track Width,

**Brakes:** HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Spring Brake Pots 30/30 TSE, Short 28 Spline Cam Bendix TABS-6 ABS w/Amber Warning Light (2 Sensors/1 Modulator), Dust Shields

**Hubs:** ADI w/Long Studs, HXL5 5-year Wheel End Warranty, Semi Fluid CHEVRON DELO SF      w/Ventless Hub/Vented Axle, Precision 320 Spindle Nut

**Drums:** Fused

**Tires:** 11R22.5 Cooper Roadmaster RM 872

**Rims:** 22.5" x 8.25" Aluminum Better Hi Polish (inner & outer)

## **Ratings**

**Distributed Load:** 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,

**GVWR:** 31,500kgs



**Weight:** EST 8400lbs

**Data:** Meets or Exceeds all Canadian Motor Vehicle Safety Standards

**Safety:** Reflective 2" Red/White Conspicuity Tape

## **Systems - Air/Electrical**

**Control Box:** SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

**Air System:** 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

**Air Tanks:** Tank Air Brake 12.0" - 2850 Cu. In. Large

**Lighting:** 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side 5 - 3/4" Micro Nova In Rear Bolster Plate, 1 - License Plate Light,

## **Components**

**Document Holder:** 1 - Tube Style

**Landing Gear:** Pair - 62500lb Dual Speed SAF Holland Mark V with Low Pro Sand Shoe

**Dock Bumper:** 2 - Mounted Rear Bolster

**Tow Point:** 2 - D-Ring 1.0" w/weld-on Bracket - Forged Steel - 15000#

**Lifting Lug:** 2 x Lift Lug Hook - 27" Wide

## **Options**

**Toolbox:** Aluminum Box with Barn Doors 24"h x 23"d x 60" 1 Curb Side

**Paint:** Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Black

**Fenders:** N/A

**Dunnage Rack:** Cross-frame carrier, 2 - 3 Bar Winches/j-hooks

**Dunnage Basket:** 0

**Wide Load Pull Out Lights –** 0

**Steps:** N/A

**Mudflaps:** 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

**Strobe Lights:** 0

**Logo Checker Plate Backed with Red Reflector Tape (located below rear bolster** Yes Logo: Renn

**Tire Chain Carrier Formed:** 0