

Trailer Specs

Customer:

53'TANDEM SWING MULTI TEM

894 DELTA,BC

RYAN PATZER

98708 - 98714

CA-76881

Production No.

2027-U-7668-007

Factory of Production

UTAH

Shipping Instructions

DEALER ARRANGED

SPECIFICATIONS

BASE MODEL: VS2RA

DWG:

OVERALL LENGTH:

OVERALL WIDTH:

OVERALL HEIGHT:

FIFTH WHL HT:

POST HT FRONT:

POST HT REAR:

KINGPIN LOC:

REAR SUSPENSION LOC:

REFRIG. UNIT PREP:

GVWR: 65,000

53'

102 3/8"

13' 6"

46 1/2

107 1/8 "

107 1/8 "

36"

SLIDER

PRECEDNT C600M

Option No.	Qty	Description	Unit Price	List Price
001-500-008		FRENCH/ENGLISH VIN LABEL REQD FOR IMPORT TO CANADA AND QAI CERTIFICATION		
004-007-037		5/16" HIGH STRENGTH STEEL APPROACH PLATE (TWO PIECE CONSTRUCTION)		
006-018-026		DO NOT NOTCH OUT BOTTOM RAIL AT REAR		
006-098-031		8" C/L CMEM SPACING FULL LENGTH (EXCEPT 6"C/L @LEG ASSY TO TANK) FOR USE W/ 24,000LB FLOOR RATING		
006-099-045		12GA GALV STEEL 24" WIDE TWO PIECE TIRE PROTECTOR PLATES AT FRONT		
008-112-023		DUST SHIELDS FOR 16-1/2" X 7" BRAKES		
008-342-114		BASE SPEC:STL JACKET 10STD HBPLT SYS W/OB BLNCD STL LT WT DRUMS 16-1/2"X7"BRKS FOR CNMET PRESET+		
008-435-016		HENDRICKSON SURELOK ANTI-DOCK WALK DEVICE FOR USE WITH MANUAL DUMP VALVE		
008-501-029		HENDRICKSON AKLS1006-1 LOAD SCALE W/MANUAL DUMP VALVE AND LIQUID-FILLED GAUGE IN POLY BOX		

009-541-011		PREP FOR THERMO KING SPECTRUM S3 CEILING MTD EVAP INCL GUARD PREP (REQS MIN OF 3-1/2" ROOF INSUL)
009-545-001		WARNING DECAL "DO NOT INSTALL CARRIER VECTOR HOST UNIT OR REMOTE EVAP ON THIS TRAILER"
009-549-041		PREP FOR TK PRECEDNT C600M MULTI TEMP FRONT MOUNT REEFER UNIT WITHOUT ELECTRIC STANDBY
009-568-010		(5) H.D. ALUM PALLET STOPS 9-1/2" HIGH
010-606-002		RUB PROTECTOR(EXT S/WALL)EXTR AL W/END CAPS;(1)MTD ABOVE BOT RAIL FULL LGTH EA SIDE
012-049-036		.0215 STAINLESS STEEL DIAMOND PATTERN REAR DOOR PANELS
012-050-018		STAINLESS STEEL REAR DOOR CROSSBRACES
012-051-030		(1) ADDL REAR DOOR LOCKROD ON CURBSIDE FOR A TOTAL OF (3)
012-052-026		(5) REAR DOOR HINGES PER DOOR
012-054-019		RECESSED SWING DOOR HOLDBACKS (INCLUDES HOLE CUTOUT IN BOTTOM RAIL)
012-353-005		5/8" SST HORIZONTAL FLANGE ON REAR BUCKPLATE (VS STD 3/8")
014-057-286		1-3/8" NOM HD EXTRU ALUM HIGH WEAR DRY FRT FLOOR NON-KNURLED
014-058-023		10"HIGH .300"EXTRA HVY DTY EXTRU ALUM NON-TAPERED W/B INTEGRAL W/FLOOR
014-126-038		EXTRU ALUM I SHAPED CORES REAR 72" OF DRY FREIGHT FLOOR FULL WIDTH
014-661-002		24,000LB FLR RATING FOR FORK TRK W/12"WIDE FRT TIRES;INCLS LEG & SLIDER REINF(REQ'S 8"C/L CMEMS)
015-065-035		3-1/2" ROOF INSULATION "FOR USE WITH REMOTE EVAP(S) ONLY"
016-074-164		6" EXTRA HEIGHT .300" EXTRU ALUM EXT HVY DTY W/BAND TOTAL OF 16" INCL REINFORCING BEHIND WEARBAND
016-130-157	2.00	(1) ROW SERIES "E" GALV SURFACE MTD LOG TRACK ON SIDE WALLS
017-077-189		2-3-3-5 CLEARANCE LIGHT PACKAGE
019-143-043		BETTS PS-1 ROUND PERMIT HOLDER MTD ON FRONT WALL
020-640-625	8.00	22.5X8.25 ALUM ACCURIDE 10 H/P; ACCU-LITE #43644SP STD POLISH (10 HAND HOLE)
020-647-670	8.00	11R 22.5 CONTINENTAL CONTI HYBRID HT3 14P, 41.2" T/DIA,LOAD RANGE"G", MAX SPEED RATED @75MPH

SPECIAL INSTRUCTIONS:

Group 10:

A) Locate rub protector approx 6" from top of bottom rail to C/L of rub rail.

Group 9:

A) Locate remote evap at 591" from extreme front to C/L of evap, offset R/S with airflow forward.

Group 16:

A) Locate (1) row of 'E' track at 30" and 60" from top of floor to C/L of track.

Group 19:

A) Locate Permit Holder on front wall R/S.

ATTENTION;
PLEASE CAREFULLY REVIEW THIS INFORMATION AND
IMMEDIATELY COMMUNICATE ANY DISCREPANCIES.

Acknowledged by: SARAH FLEIG
DIRECT

3/12/26
3/17/26

Prod Fcty: U

Line: 2

PROPOSED VIN NUMBERS:

1UY VS253X V27668 01	1UY VS2531 V27668 02
1UY VS2533 V27668 03	1UY VS2535 V27668 04
1UY VS2537 V27668 05	1UY VS2539 V27668 06
1UY VS2530 V27668 07	

This Trailer Production Order is executed pursuant to that Utility Trailer Manufacturing Company Dealer/Distributor Sales and Service Agreement entered into between Utility Trailer Manufacturing Company and Dealer. The Parties agree to conduct this transaction by electronic means and this electronically submitted Trailer Production Order shall be binding on the parties and their respective successors and assigns. In the event that Dealer intends to execute subsequent transactions using a method other than electronic submission, Dealer shall contact Utility Trailer Manufacturing Company.

If you believe that your vehicle has a defect which could cause injury or death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying UTILITY TRAILER MANUFACTURING COMPANY.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer or UTILITY TRAILER MANUFACTURING COMPANY.

To contact NHTSA, you may either call the Auto Safety Hotline toll-free at 1-800-424-9393 (or 366-0123 in Washington, D.C. area) or write to: NHTSA, U.S. Department of Transportation, Washington, D.C. 20590. You can also obtain other information about motor vehicle safety from the Hotline.