



Ocean  
TRAILER

PO #98940-98951

## Build

## Sheet

MODEL RSB-32L SUPER B TRI-AXLE LEAD

ITEM ID:30924

MODEL YEAR:2027

QUOTE#: Q25222

### Body Structure

**Dimensions:** Length 32'(Deck), Width 102" Front Deck Height 57" Rear Deck Height 54 1/2"

**Beams:** Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"

**Crossmembers:** 4" Super Light I Beam 16" Centers

**Floor:** 1-5/16 BC Douglas Fir Shiplap

**Side Rails:** 3.5" x 3.5" x 0.188" Steel Tube

**Rub Rail:** Fully Welded 1/4" Round At Bottom Of Rail

**Knee Braces:** Steel Tube @ 4/Side

**Kingpin:** 30" Inset, 2.0" SAF Holland

**Coupler Assembly** 3/8" Plate @ 48" Coupler Plate Height

**Front Bolster:** Formed Front Bolster W/ 4 Integrated Stake Pockets

**Rear Bolster:** Formed W/ 5 Integrated Stake Pockets

**Rear Light Box:** Bolted Lightbox Steel - Half Width

### Securement

**Stake Pockets:** Integrated In Side Rail At 48" Centers

**Pipe Spools:** N/A

**Winches:** 19 – Bottom Mount 3 Bar Welded, Ocean Config(New)(First Winch 12" Center From Front, 16 Winches RS, 3 Winches CS

**J-Hooks:** Opposite Winches

**Accessory Tie Flat Bar 2 1/2" X 3/8" Steel:** Yes

**Tarp Rope Hooks:** Yes

### Axles/Suspension/Tires/Wheels

**Suspension:** Hendrickson INTRAAX AANT23K Air Ride with 3-23,000lb axles, 15" Ride Height, 77 1/2" Track Width,

**Axle Spacing:** 60" CTC

**Tire Inflation:** No, N/A

**Lift Axle:** No **Position:**(N/A)

**Brakes:** Drum Brakes, HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Short 28 Spline Cam

**Brake Pad /Lining Rating:** H20K GAWR Drum





**Brake Chamber:** 30/30 TSE (Drum)  
**ABS Sensors:** Haldex  
**ABS System:** Bendix TABS-6 w/Amber Warning Light (2 Sensors/1 Modulator)  
**Dust Shield:** Yes  
**Rotor Material:** N/A  
**Drum Material:** Fused  
**Rotor Mounting:** N/A  
**RTR Wheel Ends Package:** HXL 5 Extended Life System (5-Year Warranty)  
**Spindle Type:** HP(Parallel)  
**Hub Material:** Dura-Light  
**Hub Style:** Hub-Piloted × 10-stud × 11.25" BC (for 22.5" and 24.5" tires)  
**Stud Length:** Long  
**Lubrication:** Semi-Fluid Grease  
**Seal:** Hendrickson  
**Bearings:** Hendrickson  
**Spindle Nut:** PRECISION320  
**Hub Cap:** Standard Aluminum Bolt-On  
**Tires:** 11R22.5 Cooper Roadmaster RM 872  
**Rims:** 22.5" x 8.25" Aluminum Accuride Hi Polish (inner & outer)

## Ratings

**Distributed Load:** 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,  
**GVWR:** 41,000kgs  
**Weight:** EST 11,400lbs  
**Data:** Meets or Exceeds all Canadian Motor Vehicle Safety Standards  
**Safety:** Reflective 2" Red/White Conspicuity Tape

## Systems - Air/Electrical

**Control Box:** SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear  
**Air System:** 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate  
**Air Tanks:** Steel Tank Air Brake 9.0" - 1488 Cu. In. Small, Tank Air Brake 12.0" - 2850 Cu. In. Large  
**Air Lines:** Grote Hose Coiled Nylon 15.0' C/w 0.5" Male End 12" Lead Red&blue Combo w/Aluminum Anodized Gladhandle Set, Isolation Ball Valves  
**Lighting:** 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side 5 - 3/4" Micro Nova In Rear Light Box Plate, 1 - License Plate Light,

## Components

**Document Holder:** 1 - Tube Style  
**Landing Gear:** 62500lb Dual Speed SAF Holland Mark V With Low-Pro Sand Shoe  
**Fifth Wheel Plate:** Hitch Fifth Wheel SAF Holland FW35 5.6" Height





## Options

**Toolbox:** Aluminum Tool Box w/Barn Doors, Grote LED int Light 24"h x 23"d x 60" 1 Curb Side(STD)

**Paint:** Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Black

**Fenders:** Aluminum Checker Plate above 2nd axle

**Dunnage Rack:** Cross-frame carrier, 2 - 3 Bar Winches/j-hooks

**Dunnage Basket:** 0

**Dunnage Box:** 0

**Wide Load Pull Out Lights – 0**

**Steps:** Steel Access Step between 2nd and 3rd axle - Curb/Road Side

**Mudflaps:** 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

**Brake Pot Mudflaps:** No,

**Strobe Lights:** 0

**Tire Chain Carrier Formed:** Undermount Curb Side - 1



## Build Sheet

**SUPER B TANDEM AXLE REAR**

**MODEL: RSB-30R**

**ITEM ID: 30925**

**MODEL YEAR: 2027**

**QUOTE#: Q25222**

### Body Structure

**Dimensions:** Length 28'(Deck), Width 102" Front Deck Height 55 3/4" Rear Deck Height 51 1/2",

**Beams:** Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"

**Crossmembers:** 4" Super Light I Beam 16" Centers

**Floor:** 1-5/16 BC Douglas Fir Shiplap

**Side Rails:** 3.5" x 3.5" x 0.188" Steel Tube

**Rub Rail:** Fully Welded 1/4" Round At Bottom Of Rail

**Knee Braces:** Steel Tube @ 2/Side

**Kingpin:** 19"(Std) Inset, 2.0" SAF Holland

**Coupler Assembly** 3/8" Plate @ 48" Coupler Plate Height

**Front Bolster:** Formed Front Bolster W/ 4 Integrated Stake Pockets

**Rear Bolster:** Formed W/ 5 Integrated Stake Pockets

**Impact Guard:** Weld On, Meets CMVSS

### Securement

**Stake Pockets:** Formed, 48" Centers

**Pipe Spools:** N/A

**Winches:** 18 – Bottom Mount 3 Bar Welded, Ocean Config(New)(First Winch 12" Center From Front, 14 Winches RS, 4 Winches CS

**Cross Tie Winches:** Yes – Welded at Rear With J/Hooks

**J-Hooks:** Opposite Winches

**Accessory Tie Flat Bar 2 1/2" X 3/8" Steel:** Yes

**Tarp Rope Hooks:** Yes

### Axles/Suspension/Tires/Wheels

**Suspension:** Hendrickson INTRAAX AANT23K Air Ride with 3-23,000lb axles, 15" Ride Height, 77 1/2" Track Width,

**Axle Spacing:** 60" CTC





*Ocean*  
**TRAILER**

**Tire Inflation:** No, N/A

**Lift Axle:** No **Position:**(N/A)

**Brakes:** Drum Brakes, HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Short 28 Spline Cam

**Brake Pad /Lining Rating:** H20K GAWR Drum

**Brake Chamber:** 30/30 TSE (Drum)

**ABS Sensors:** Haldex

**ABS System:** Bendix TABS-6 w/Amber Warning Light (2 Sensors/1 Modulator)

**Dust Shield:** Yes

**Rotor Material:** N/A

**Drum Material:** Fused

**Rotor Mounting:** N/A

**RTR Wheel Ends Package:** HXL 5 Extended Life System (5-Year Warranty)

**Spindle Type:** HP (Parallel)

**Hub Material:** Dura-Light

**Hub Style:** Hub-Piloted x 10-stud x 11.25" BC (for 22.5" and 24.5" tires)

**Stud Length:** Long

**Lubrication:** Semi-Fluid Grease

**Seal:** Hendrickson

**Bearings:** Hendrickson

**Spindle Nut:** PRECISION320

**Hub Cap:** Standard Aluminum Bolt-On

**Tires:** 11R22.5 Cooper Roadmaster RM 872

**Rims:** 22.5" x 8.25" Aluminum Accuride Hi Polish (inner & outer)

## **Ratings**

**Distributed Load:** 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,

**GVWR:** 31,500kgs

**Weight:** EST 8400lbs

**Data:** Meets or Exceeds all Canadian Motor Vehicle Safety Standards

**Safety:** Reflective 2" Red/White Conspicuity Tape

## **Systems - Air/Electrical**

**Control Box:** SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

**Air System:** 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

**Air Tanks:** Tank Air Brake 12.0" - 2850 Cu. In. Large

**Lighting:** 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side 5 - 3/4" Micro Nova In Rear Bolster Plate, 1 - License Plate Light,



## Components

**Document Holder:** 1 - Tube Style

**Landing Gear:** Pair - 62500lb Dual Speed SAF Holland Mark V with Low Pro Sand Shoe

**Dock Bumper:** 2 - Mounted Rear Bolster

**Tow Point:** 2 - D-Ring 1.0" w/weld-on Bracket - Forged Steel - 15000#

**Lifting Lug:** 2 x Lift Lug Hook - 27" Wide

## Options

**Toolbox:** Aluminum Box with Barn Doors 24"h x 23"d x 60" 1 Curb Side

**Paint:** Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Black

**Fenders:** N/A

**Dunnage Rack:** Cross-frame carrier, 2 - 3 Bar Winches/j-hooks

**Dunnage Basket:** 0

**Wide Load Pull Out Lights –** 0

**Steps:** N/A

**Mudflaps:** 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

**Brake Pot Mudflaps:** No,

**Strobe Lights:** 0

**Logo Checker Plate Backed with Red Reflector Tape (located below rear bolster Yes Logo:** Renn

**Tire Chain Carrier Formed:** 0

**Lift Axle:** No (N/A)