



Build

Sheet

SUPER B TRI-AXLE LEAD

MODEL SLSB-32L

ITEM ID:33074

MODEL YEAR:2027

QUOTE#: Q25250

Body Structure

Dimensions: Length 32'(Deck), Width 102" Front Deck Height 57" Rear Deck Height 54 1/2"

Beams: Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"

Crossmembers: 4" Super Light I Beam 16" Centers

Floor: 1-5/16 BC Douglas Fir Shiplap

Side Rails: 3.5" x 3.5" x 0.188" Steel Tube

Rub Rail: Fully Welded 1/4" Round At Bottom Of Rail

Knee Braces: Steel Tube @ 4/Side

Kingpin: 30" Inset, 2.0" SAF Holland

Coupler Assembly 3/8" Plate @ 48" Coupler Plate Height

Front Bolster: Formed Front Bolster W/ 4 Integrated Stake Pockets

Rear Bolster: Formed W/ 5 Integrated Stake Pockets

Rear Light Box: Bolted Lightbox Polished Stainless Steel - Full Width

Securement

Stake Pockets: Integrated In Side Rail At 48" Centers

Pipe Spools: N/A

Winches: 19 – Bottom Mount 3 Bar Welded, Ocean Config(New)(First Winch 12" Center From Front, 16 Winches RS, 3 Winches CS

J-Hooks: Opposite Winches

Accessory Tie Flat Bar 2 1/2" X 3/8" Steel: Yes

Tarp Rope Hooks: Yes

Axles/Suspension/Tires/Wheels

Suspension: Hendrickson INTRAAX AANT23K Air Ride with 3-23,000lb axles, 15" Ride Height, 77 1/2" Track Width,

Axle Spacing: 60" CTC

Shock Absorber: ZMD (Zero Maintenance Damping)

Tire Inflation: No, N/A

Lift Axle: No **Position:**(N/A)





Brakes: Drum Brakes, HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Short 28 Spline Cam

Brake Pad /Lining

Rating: H20K GAWR Drum

Brake Chamber: 30/30 TSE (Drum)

ABS Sensors: Haldex

ABS System: Bendix TABS-6 w/Amber Warning Light (2 Sensors/1 Modulator)

Dust Shield: Yes

Rotor Material: N/A

Drum Material: Fused

Rotor Mounting: N/A

RTR Wheel Ends Package: HXL 5 Extended Life System (5-Year Warranty)

Spindle Type: HP(Parallel)

Hub Material: Dura-Light

Hub Style: Hub-Piloted x 10-stud x 11.25" BC (for 22.5" and 24.5" tires)

Stud Length: Long

Lubrication: Semi-Fluid Grease

Seal: Hendrickson

Bearings: Hendrickson

Spindle Nut: PRECISION320

Hub Cap: Standard Aluminum Bolt-On

Tires: 11R22.5 Yokohama Bluearth 109L 14 Ply

Rims: 22.5" x 8.25" Aluminum Accuride Hi Polish (inner & outer)

Ratings

Distributed Load: 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,

GVWR: 41,000kgs

Weight: EST 11,400lbs

Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards

Safety: Reflective 2" Red/White Conspicuity Tape

Systems - Air/Electrical

Control Box: SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

Air System: 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

Air Tanks: Steel Tank Air Brake 9.0" - 1488 Cu. In. Small, Tank Air Brake 12.0" - 2850 Cu. In. Large

Air Lines: Grote Hose Coiled Nylon 15.0' C/w 0.5" Male End 12" Lead Red&blue Combo w/Aluminum Anodized Gladhandle Set, Isolation Ball Valves

Lighting: 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Heated Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side - Flashing Directional Arrow, 5 - 3/4" Micro Nova In Rear Light Box Plate, 1 - License Plate Light,





Components

Document Holder: 1 -

Tube Style

Landing Gear: 62500lb Dual Speed SAF Holland Mark V With Low-Pro Sand Shoe

Fifth Wheel Plate: Hitch Fifth Wheel SAF Holland FW35 5.6" Height

Options

Toolbox: Aluminum Tool Box w/Barn Doors, Grote LED int Light 30"h x 23"d x 60" 1 Curb Side, 1 Road Side

Paint: Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Silver(Dark Grey)

Fenders: Polished No Rib Stainless Steel Half Round Fender Over all Duals

Dunnage Rack: Cross-frame Carrier - No Winches

Dunnage Basket: 0

Dunnage Box: 1 - 18H x 100D x 31W Aluminium Cross Frame Dunnage Box

Wide Load Pull Out Lights – 4- Aluminum Pullout Wide Load Lights

Steps: Aluminum Access Step between 2nd and 3rd axle - Curb/Road Side

Mudflaps: 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

Brake Pot Mudflaps: 2 Plain Rubber Mudflaps Located In Front of Brake Pots Between Frame,

Strobe Lights: Switch In Air Box 2 Strobes/Trailer, Amber, Located In Tail Light Cluster

Tire Chain Carrier Formed: Undermount Curb Side - 1



Build Sheet

SUPER B TANDEM AXLE REAR

MODEL: SLSB-28R

ITEM ID: 33121

MODEL YEAR:2027

QUOTE#:Q25222

Body Structure

Dimensions: Length 28'(Deck), Width 102" Front Deck Height 55 3/4" Rear Deck Height 51 1/2",

Beams: Web 3/16" Gr90 KSI HTS, Flange GR130 KSI 5" X 3/8" HTS, Robotically Welded, Camber 2 1/2"

Crossmembers: 4" Super Light I Beam 16" Centers

Floor: 1-5/16 BC Douglas Fir Shiplap

Side Rails: 3.5" x 3.5" x 0.188" Steel Tube

Rub Rail: Fully Welded 1/4" Round At Bottom Of Rail

Knee Braces: Steel Tube @ 2/Side

Kingpin: 19"(Std) Inset, 2.0" SAF Holland

Coupler Assembly 3/8" Plate @ 48" Coupler Plate Height

Front Bolster: Formed Front Bolster W/ 4 Integrated Stake Pockets

Rear Bolster: Formed W/ 5 Integrated Stake Pockets

Impact Guard: Weld On, Meets CMVSS

Securement

Stake Pockets: Formed, 48" Centers

Pipe Spools: N/A

Winches: 18 – Bottom Mount 3 Bar Welded, Ocean Config(New)(First Winch 12" Center From Front, 14 Winches RS, 4 Winches CS

Cross Tie Winches: Yes – Welded at Rear With J/Hooks

J-Hooks: Opposite Winches

Accessory Tie Flat Bar 2 1/2" X 3/8" Steel: Yes

Tarp Rope Hooks: Yes

Axles/Suspension/Tires/Wheels

Suspension: Hendrickson INTRAAX AANT23K Air Ride with 3-23,000lb axles, 15" Ride Height, 77 1/2" Track Width,

Axle Spacing: 60" CTC

Shock Absorber: ZMD (Zero Maintenance Damping)



Tire Inflation: No, N/A

Lift Axle: No **Position:**(N/A)

Brakes: Drum Brakes, HXS 16.5" x 7" Shoes, Haldex Auto Slack Adjusters 5.5, Short 28 Spline Cam

Brake Pad /Lining Rating: H20K GAWR Drum

Brake Chamber: 30/30 TSE (Drum)

ABS Sensors: Haldex

ABS System: Bendix TABS-6 w/Amber Warning Light (2 Sensors/1 Modulator)

Dust Shield: Yes

Rotor Material: N/A

Drum Material: Fused

Rotor Mounting: N/A

RTR Wheel Ends Package: HXL 5 Extended Life System (5-Year Warranty)

Spindle Type: HP (Parallel)

Hub Material: Dura-Light

Hub Style: Hub-Piloted x 10-stud x 11.25" BC (for 22.5" and 24.5" tires)

Stud Length: Long

Lubrication: Semi-Fluid Grease

Seal: Hendrickson

Bearings: Hendrickson

Spindle Nut: PRECISION320

Hub Cap: Standard Aluminum Bolt-On

Tires: 11R22.5 Yokohama Blueearth 109L 14 Ply

Rims: 22.5" x 8.25" Aluminum Accuride Hi Polish (inner & outer)

Ratings

Distributed Load: 60,000lbs, 20' Concentrated-45,000lbs, 10' Concentrated-37,500lbs, 4' Concentrated-30,000lbs,

GVWR: 31,500kgs

Weight: EST 8400lbs

Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards

Safety: Reflective 2" Red/White Conspicuity Tape

Systems - Air/Electrical

Control Box: SS W/Liquid Gauge, Sight Window, Manual Dump Valve – Mounted DS Front of Landing Gear

Air System: 3/8" Air Filter In-line For Supply Line, Valve Air Ride Height Control - Hendrickson Akh-238-3, Manual Dump/Inflate

Air Tanks: Tank Air Brake 12.0" - 2850 Cu. In. Large

Lighting: 7 Year Grote Harness System, All LED Lighting, 6 Grote 4" Round Heated Stop/Tail/Turn W/Anti-Theft Bezels, 4 - Amber - 3/4" Micro Nova Located Front/Side Corners, 2 - Red - 3/4" Micro Nova Located Rear Side Corners, 1 - Signal/Marker Per Side - Flashing Directional Arrow, 2 x 4" Round Strobes with 3 - 3/4" Micro Nova In Rear Bolster Plate, 1 - License Plate Light,



Components

Document Holder: 1 - Tube Style

Landing Gear: Pair - 62500lb Dual Speed SAF Holland Mark V with Low Pro Sand Shoe

Dock Bumper: 2 - Mounted Rear Bolster

Tow Point: 2 - D-Ring 1.0" w/weld-on Bracket - Forged Steel - 15000#

Lifting Lug: 2 x Lift Lug Hook - 27" Wide

-

Options

Toolbox: Aluminum Tool Box w/Barn Doors, Grote LED int Light 30"h x 23"d x 60" 1 Curb Side, 1 Road Side

Paint: Steel Shot Blasted, PPG Zinc Epoxy Primer Topcoat PPG Urethane Silver(Dark Grey)

Fenders: Polished No Rib Stainless Steel Half Round Fender Over all Duals

Dunnage Rack: Cross-frame Carrier - No Winches

Dunnage Basket: 0

Wide Load Pull Out Lights – 4- Aluminum Pullout Wide Load Lights

Steps: N/A

Mudflaps: 24" X 30" X 0.375" - Poly - Renn/Ocean, Aluminum Checkerplate Z-angle Mudflap Hanger, Front Of Landing Gear - 4, Rear – 2

Brake Pot Mudflaps: 2 Plain Rubber Mudflaps Located In Front of Brake Pots Between Frame,

Strobe Lights: Switch In Air Box 2 Strobes/Trailer, Amber, Located in Middle Bolster Above Logo Plate

Logo Checker Plate Backed with Red Reflector Tape (located below rear bolster Yes Logo: Renn

Tire Chain Carrier Formed: 0

Lift Axle: No (N/A)