



99052 JHN
99082

Order Date: 2026-04-28

Order Number: 39761 REV. 1

Reference: Stock w/22.5- 35979

Company: C KEAY INVESTMENTS / OCEAN TRAILER
Jim Farrell

**Canadian Velocity 53' Tridem Air Slider
(Model Code: HBVSF22TAS)**

Overall Length: 53 feet x 102 inches
Suspension Type: Sliding air tridem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 100,000 lbs distributed- GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch wood
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Side Rails: 6 inch structural channel @ 6.5 lbs/ft
Stake Pockets: 3/16 inch steel on 24 inch centers
Pipe Spools: Double between stake pockets
Rubrail: 3/8 inch x 2 1/2 inch steel
Main Beams: 130K load bearing flanges
Kingpin: 24 inches; 5/16" Plate
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: None standard
Number of Axles: 3 Intraax
Axle Position: 96 inch adjustable
Axle Spread: 60 inches, 60 inches -- Kingpin to C/L Rear Axle: 39 feet 4 3/4 inches in front position- 47 feet 4 3/4 inches in rear position
Axle Spindle: Parallel (Straight)
Dust Shields: Installed on all axles
Brakes: TSE Spring brakes, Haldex auto slacks
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Hub and Drums: 10-hole hub-piloted with outboard cast drums (Webb)
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 steel disc wheels - 12 pre-painted white - STANDARD
Tires: 11R 22.5 14PR OEM standard tires -- quantity 12 -- STANDARD
Tire Brand: OEM standard
Tire Inflation System: None standard
Suspension Detail: Hendrickson AAZNT69K Intraax air ride slider with ride height limiters- 96 inch adjustable; (1) Removable slide position stop bar
Air Assist Slide Box Pins: Controls mounted inside box on front of slider box
Manual Dump Valve: Standard
Air Load Scale: Installed
Front Corners: Tapered
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Other Electrical Specifications: 3 4-way sockets with one hot/one ground pin for wide load and strobe light connections: 1 rear, 1 ea. side at rear
Paint: Black urethane with Velocity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed on rubrails
Bumper: Weld-on type - meets underride requirements
Mudflaps: 1 set OEM standard behind rear axle
Spare Tire Carrier: None standard
Side Mounted Winches: 26 standard - without straps: 13 per side-three bar type
Special J Hooks: 26 total - 13 per side-opposite winches
Tarp Hooks: 2 foot centers on all sides when possible: undermount rs/cs: side mount front/back
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: Install registration holder - Tite Seal
Tool Box: 1 CAM LOCK aluminum double door box - 18 inches x 24 inches x 60 inches - installed Road Side
Tow Hooks: 1 Installed on rear
VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges
Unit Numbers & Decals: Not installed
Stacking: Price includes Standard stacking of each trailer

Quantity (Units): 36

Estimated Weight (lbs) (+/- 3%) 14,640

Net 30 Days

Price is subject to change up to 60 Days (i.e. lockout date) from the communicated production date.

This Quotation is subject to Fontaine's current terms and conditions of sale.

[Click here for Terms and Condition of Sale for details](#)