

OTR # 99088-99105



Order Date: 2026-04-28
 Order Number: 39762
 Reference: Will - Stock 22.5
 Company: C KEAY INVESTMENTS / OCEAN TRAILER
 Jim Farrell

**Canadian Velocity Drop Deck 53' Tridem Air Ride
 (Model Code: HBVSD22TAF)**

Overall Length: 53 feet x 102 inches
Suspension Type: Tri-axle air
Deck Lengths: 11 feet front and 42 feet rear
Frame Rating: 100,000 lbs distributed- GAWR and tire ratings determine legal payloads
Rear Deck Height: 40 inches - loaded
Flooring: 1 1/8 inch wood
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel
Side Rails: 6 inch structural channel @ 6.5 lbs/ft
Stake Pockets: 3/16 inch steel on 24 inch centers
Pipe Spools: Double between stake pockets
Rubrail: 3/8 inch x 2 1/2 inch steel
Main Beams: 130K load bearing flanges
Kingpin: 18 inches; 5/16" Plate
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM standard
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: None standard
Number of Axles: 3 Intraax
Axle Position: Fixed
Axle Spread: 60 inches, 60 inches -- kingpin to center axle 40 feet 10 7/8 inches -- center axle to rear 126 1/8 inches
Axle Spindle: Parallel (Straight)
Brakes: Spring brakes, auto slacks
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Hub and Drums: 10-hole hub-piloted with outboard cast drums (Webb)
Dust Shields: Installed on all axles
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: (12) 22.5 x 8.25 Steel disc wheels - pre-painted white - STANDARD
Tires: 255/70R 22.5 16PR - quantity 12 OEM standard
Tire Inflation System: None standard
Suspension Detail: AANL23K Intraax air ride
Manual Dump Valve: Installed Inside Box with Liquid Filled Load Gauge
Air Lift: None Standard
Front Corners: Tapered
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Other Electrical Specifications: (5) 4 way sockets with one hot/one ground pin each for wide load and strobe light connections: 1 on rear, 2 each side
Air Load Scale: Installed
Paint: Black urethane with Velocity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed on rubrails
Bumper: Weld-on type - meets underride requirements
Mudflaps: 1 set OEM standard behind rear axle
Side Mounted Winches: 26 standard - without straps: 13 per side-three bar type
Special J Hooks: 26 total - 13 per side-opposite winches
Tarp Hooks: 2 foot centers on all sides when possible; undermount rs/cs; side mount front/back
Dock Bumpers: 1 pair rubber on rear
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams
Hubodometer: None standard
Registration Holder: Install registration holder - Tite Seal
Tool Box: 1 CAM LOCK aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side
Tow Hooks: 1 Installed on rear
VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges
Unit Numbers & Decals: Not installed
Stacking: Price includes Standard stacking of each trailer

Dealer Net Cost Each FOB Haleyville, AL:	
Surcharge (*If Applicable):	
Price Including Surcharge:	
Quantity (Units):	
Grand Total:	
Estimated Weight (lbs) (+/- 3%):	14,460

1% 10 Days - Net 30 Days

Price is subject to change up to 60 Days (i.e. lockout date) from the communicated production date.

This Quotation is subject to Fontaine's current terms and conditions of sale.

[Click here for Terms and Condition of Sale for details](#)