Confirmation

Wilson TRAILER
Since 1890... A Good Name to Have Behind You!™

4400 So Lewis Blvd
PO Box 6300
SIOUX CITY, IA 51106

Phone: 712-252-6500
Fax: 712-252-6510

Type of order.....: Flatbed
Number .....: 637769-2
Mfg. Location .....: Plant 6
Order date.....: 6/30/2026
Revision date .....: 9/22/2026
Requested ship date.....: 11/7/2026
Customer Account .....: 100439

Dealer's customer info.: PO#99647-REF 632195

Trailer number.....: 637769
Model Year.....: 2027
VIN number.....:
Sales person .....: Schlines, Danielle L
Salesperson phone .....: 712-252-6539

OCEAN TRAILER - (PTS/TRL)
9076 RIVER RD
DELTA, BC V4G 1B5
CAN

Contact person.....:
Customer phone .....: 204-940-7364

Unit #99647-99649

Pblite Revision .....: 2

	Description	Quantity	Price
1)	MODEL CD-1080		
2)	TRAILER BUILT FOR EXPORT TO CANADA		
3)	--INSTALL CANADIAN VIN PLATE ILO US		
4)	2026 PRODUCTION		
5)	--FLATBED PRICING IS SUBJECT TO ADJUSTMENT UP TO NINETY (90) DAYS BEFORE PRODUCTION OF YOUR ORDER		
6)	--(90) DAYS FROM THE START OF PRODUCTION YOU WILL RECEIVE NOTICE IF PRICING ADJUSTMENT IS REQUIRED		
7)	--CUSTOMER HAS THE RIGHT TO ACCEPT THE ADJUSTMENT OR CANCEL THE ORDER		
8)	LENGTH 53 FT		
9)	WIDTH 102"		
10)	FIFTH WHEEL HEIGHT 48" (STD)		
11)	KING PIN 24"		
12)	KING PIN CORSOL PAINTED (STD)		
13)	10-3/4" KING PIN BEAM DEPTH (STD)		
14)	STANDARD KING PIN		
15)	JOST UL550 ULTRALIGHT LANDING GEAR W/ CUSHION FOOT (STD)		
16)	11' TOP DECK LENGTH (STD)		
17)	REAR DECK HEIGHT 39-1/2" (22.5 TIRES) (STD)		
18)	FRONT DROP - 21" (STD)		
19)	GN SLOPE - SQUARE (STD)		
20)	SUSPENSION SETTING - (TAC LEGAL) MAXIMUM DISTANCE		
21)	FRICTION SLIDER (AA250L INTRAAX) FRONT AXLE SLIDE TANDEM		
22)	MANUAL SUSPENSION DUMP (STD)		
23)	HENDRICKSON HEIGHT CONTROL VALVE (STD)		
24)	HENDRICKSON TIREMAAX PRO TIRE INFLATION SYSTEM TANDEM		
25)	AIR GAUGE FOR AIR RIDE (100 PSI) W/MANUAL DUMP IN SEALED METAL BOX W/LATCH ***Mounted by landing gear with slider valve in box***		
26)	ABS BENDIX (EATON) 4S/2M		
27)	HENDRICKSON H26 BRAKE LININGS (26K BRAKE RATING) ILO STANDARD H20 BRAKES (PER AXLE)	(2)	
28)	TAPERED SPINDLE W/ TN BEARINGS (PER AXLE) (STD)	(2)	

29) OIL LUBE (STD) (2)
30) STEMCO GUARDIAN SEAL (#3070743) (STD) (2)
31) STEMCO ALUMINUM HUBCAP (STD) (2)
32) AXILOCK SPINDLE NUT (STD) (2)
33) DUST SHIELDS - STEEL (PER AXLE) (2)
34) DURALITE HUBS/CAST DRUMS (PER AXLE) (STD) (2)
35) GOLD SEAL CHAMBERS W/3" STROKE AND INDICATOR (PER AXLE) (2)
36) HALDEX 6.0 AUTO SLACK ADJUSTERS (PER AXLE) (2)
37) TRAMEC SPRING BRAKE VALVE (STD) (2)
38) MUDFLAPS- BLACK RUBBER WTC FOR FRONT AXLE
39) MUDFLAPS- BLACK RUBBER WTC FOR SET AHEAD REAR AXLE
40) WHEEL ALUM (HP) ALCOA ULTRA ONE 10HOLE 8.25X22.5 (PER EA) (8)
41) ROADX RH652 255/70R 22.5 LR-H (8)
42) ***TIRES ARE SUBJECT TO AVAILABILITY, IF A SUBSITUTE TIRE MUST BE USED THE SALE PRICE WILL BE ADJUSTED ACCORDINGLY***
43) PLASTIC LINER (SET OF 4) BETWEEN HUB/WHEEL
44) FLOOR ALUM 1-3/8 (4) NAILERS (PER FT) (53)
45) 18" X-BAR SPACING 4-1/2" ALUM (MAIN BED) (STD) (42)
46) C+ STYLE SIDE RAIL 6-1/4" PKTS ON 24" CTRS/SGL SPOOL/RUB BAR
47) KNEE BRACES (STD)
48) BUMPER WITH ALUMINUM R.I.G. (STD)
49) FRONT CORNER POCKETS TURNED TO SIDE (STD)
50) GLADHANDS & 7-WAY CONNECTIONS AT FRONT (STD)
51) GROTE LED MICRO NOVA CLEARANCE LIGHTS
52) RECESSED IN GROTE RUBBER GROMMET
53) PACKAGE B - 4 EXTRA (ROW OF 5)
54) SPACE LIGHTS EQUALLY - GIVE PRIORITY TO WINCH STRAP CLEARANCE
55) GROTE LED CENTER TURN SURFACE MOUNT (STD)
56) GROTE LED 4" ROUND TAIL LIGHTS CLUSTER OF 3 (GROMMET) (STD)
57) 2 GROTE 4" AMBER STROBE ON INSIDE POSITION OF CLUSTER OF 3 (GROMMET)
With on off switch in box with air gauge
58) QUICK TIE PLATE (PER EA) (16)
59) QUICK TIE PLATE STORAGE BRACKET(HOLDS 16)
60) QUICK TIE PLATE STORAGE BRACKET LOCATION - SPECIFY LOCATION
Locate by landing gear DS
61) KINEDYNE WINCH FIXED LO-PRO 3-BAR WITH CLAW HOOK KYN14001 (PER EA) (26)
62) PERMANENT WINCH LOCATION - DS/CS STAGGERED SPACED EVENLY
locate 5 on the upper deck staggered, spaced evenly starting on the DS, Balance on bottom deck staggered spaced appox evenly.
63) AERO TOOL BOX 24D X 18H X 60L CAM LOCKS W/ 2 POLISHED DOORS (2)
64) TOOL BOX LOCATION - AT DROP DS & CS
65) MOUNT AS HIGH AND CLOSE TO BEAM AS POSSIBLE
66) DUNNAGE RACK: 10FT LONG X 8IN TALL OUTSIDE BEAMS X-BAR MOUNT WITH .184 PUNCHED OVAL FLOOR PAN
67) DUNNAGE STORAGE LOCATION - AHEAD OF FRONT AXLE CS
68) PAINT WITH FLAT BLACK CORSOL ONLY (STD)
69) INSTALL CONSPICUITY TAPE ON RUB BAR (STD)
70) INSTALL DECALS AT STANDARD LOCATIONS
71) REGISTRATION HOLDER - TUBE TYPE (STD)
72) CUSTOMER IS RESPONSIBLE FOR SECURING DECKED TRAILERS AND COMPLYING WITH LOAD HEIGHT RESTRICTIONS
73) APPROVAL DRAWING - SIDE VIEW OF LIGHT AND SUSPENSION LOCATIONS

74) APPROVAL DRAWING - SIDE VIEW W/ARCH SHOWING DECK HEIGHTS