


PO19684



**Quote Date:** 2026-01-27  
**Quote Expires:** 2026-02-07  
**Quote Number:** 3013644  
**Quote Reference:** Will Tucker  
**Company Quoting:** Ocean Trailer

Tyler Vickers  
 FONTAINE SPECIALIZED  
 5398 US Highway 11  
 Springville, AL 35146  
 2054671083  
 tvickers@fontainespecialized.com

Please Fax back to this number with your authorization: 2054671083

### QUOTE

| Canadian Renegade X20C Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, Mechanical Gooseneck (Model: RENEGADE X20C)                                                                          |                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
|                                                                                                                                                                                                      | Est. Wt.: 23,198# +/- 3% |
| <b>TRAILER - GENERAL</b>                                                                                                                                                                             |                          |
| <b>Capacity:</b> 40 tons in 16-foot length - GAWR and tire ratings determine legal loads                                                                                                             |                          |
| <b>Load Base:</b> 16-foot rigid 2-point load centered in deck when deck is fully closed.<br>Note: Only rigid self supporting loads when deck is open. The load base becomes the open deck minus 2ft. |                          |
| <b>Length (Trailer Only):</b> 47 feet 3 inches                                                                                                                                                       |                          |
| <b>Width:</b> 8 feet 6 inches                                                                                                                                                                        |                          |
| <b>Compatibility:</b> Designed to accept optional flip box (gooseneck extension) and third flip axle                                                                                                 |                          |
| <b>GOOSENECK</b>                                                                                                                                                                                     |                          |
| <b>Gooseneck Design:</b> Mechanical removable with removable fifth wheel guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches        |                          |
| <b>Gooseneck Platform:</b> Full width gooseneck platform with 1 1/8 inch wood floor                                                                                                                  |                          |
| <b>Tool Box:</b> Lockable toolbox in riser portion of GN between MB                                                                                                                                  |                          |
| <b>Gooseneck Fenders:</b> Aluminum fenders at rear of gooseneck                                                                                                                                      |                          |
| <b>DECK</b>                                                                                                                                                                                          |                          |
| <b>Deck Design:</b> Flat level telescopic deck design                                                                                                                                                |                          |
| <b>Deck Length:</b> 27 feet 7 inch clear deck length (retracted) - 47 feet 2 inches (extended)                                                                                                       |                          |
| <b>Loaded Deck Height:</b> 20 inches with 6 inches ground clearance                                                                                                                                  |                          |
| <b>Flooring:</b> 1 3/8 inch nominal wood (full width)                                                                                                                                                |                          |
| <b>Recessed Floor Mounted D-Ring Package:</b> 8 Pair of D-rings recess mounted in floor inboard of outside beams ** NOTE: Must select High Density Crossmember Package                               |                          |
| <b>Crossmembers:</b> High Density Crossmember Package- Additional stub crossmembers installed between existing crossmembers, net spacing of 12 inches                                                |                          |
| <b>Front Ramps:</b> None, front of deck sloped top down to assist in loading with traction cleats                                                                                                    |                          |
| <b>Mini Boom Trough &amp; Traction Cleats:</b> Mini boom trough and traction cleats installed on sloped bogie ramp                                                                                   |                          |
| <b>Front Bogie Ramp:</b> Sloped steel bogie ramp (full width)                                                                                                                                        |                          |
| <b>Outriggers:</b> 13 pair - 26 total outriggers, 1 pair 2 total heavy duty outriggers                                                                                                               |                          |
| <b>Deck to Bogie Connection:</b> Fixed                                                                                                                                                               |                          |
| <b>AXLES</b>                                                                                                                                                                                         |                          |
| <b>Number of Axles:</b> 2                                                                                                                                                                            |                          |
| <b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.                                                             |                          |
| <b>Axle Spread:</b> 60 inches spread (between axles)                                                                                                                                                 |                          |
| <b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount                                                                                           |                          |
| <b>Spring Brakes:</b> Spring brakes on 2 axles                                                                                                                                                       |                          |
| <b>Dust Shields:</b> Dust shields on 2 axles                                                                                                                                                         |                          |
| <b>SUSPENSION</b>                                                                                                                                                                                    |                          |
| <b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs                                                                               |                          |
| <b>Suspension:</b> Air ride with automatic controls                                                                                                                                                  |                          |

|                                                                                                                                |                                 |
|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| <b>ABS:</b> 2S/2M system without diagnostic tool and cable                                                                     |                                 |
| <b>Load Scale:</b> None Standard                                                                                               |                                 |
| <b>WHEELS AND TIRES</b>                                                                                                        |                                 |
| <b>Wheels:</b> 8.25 x 22.5 LVL One buffed wheels                                                                               |                                 |
| <b>Tire Brand:</b> OEM Standard                                                                                                |                                 |
| <b>Tires:</b> 255/70R 22.5 H ply OEM Standard                                                                                  |                                 |
| <b>Hubodometer:</b> None Standard                                                                                              |                                 |
| <b>Tire Inflation:</b> None Standard                                                                                           |                                 |
| <b>REAR BRIDGE</b>                                                                                                             |                                 |
| <b>Covered Rear Bogie:</b> Rear bogie platform with 1 1/8 inch wood floor                                                      |                                 |
| <b>Rear Bogie Height:</b> 41 inches                                                                                            |                                 |
| <b>Bumper:</b> 3 tail light package                                                                                            |                                 |
| <b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears                 |                                 |
| <b>Liquid Filled Gauge:</b> Included                                                                                           |                                 |
| <b>Winches:</b> 11 - three bar type, 4 per side on deck, 2 mount roadside on gooseneck, 1 mounted curbside center of gooseneck |                                 |
| <b>Special J Hooks:</b> Opposite winches                                                                                       |                                 |
| <b>Accent Package:</b> Stainless steel accent package                                                                          |                                 |
| <b>Electrical System:</b> Two (2) pair 4-way receptacles (One pair on gooseneck, one pair on bogie)                            |                                 |
| <b>LIGHTING</b>                                                                                                                |                                 |
| <b>Lighting:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes            |                                 |
| <b>Marker Lights:</b> 7 marker lights per side including mid-turn                                                              |                                 |
| <b>Electrical Receptacle:</b> J560 7-pin connector                                                                             |                                 |
| <b>Additional Marker Lights:</b> None Standard                                                                                 |                                 |
| <b>PAINT</b>                                                                                                                   |                                 |
| <b>Paint:</b> Fontaine black polyurethane enamel PN 51172000/G02BC0001                                                         |                                 |
| <b>MISCELLANEOUS</b>                                                                                                           |                                 |
| <b>Lash Rings:</b> 8 pair - 16 total side mount 2 pair, 4 total recessed in main deck                                          |                                 |
| <b>Flag Holders:</b> 2 pair flag holders                                                                                       |                                 |
| <b>VIN Plate:</b> Bilingual VIN plate                                                                                          |                                 |
| <b>Registration/Document Holder:</b> Registration/document holder installed                                                    |                                 |
| <b>Please Note:</b> Price includes commodity surcharges                                                                        |                                 |
| <b>Commercial Terms:</b> Ex Works- Springville, AL, USA                                                                        |                                 |
| <b>Flipbox:</b> None                                                                                                           |                                 |
| <b>AVAILABLE COMPONENTS</b>                                                                                                    |                                 |
| <b>Flip Axle:</b> Rear Axle -LVL One buffed wheels                                                                             |                                 |
| <b>Dust Shields on Flip Axle:</b> Standard                                                                                     |                                 |
| <b>Additional Options:</b>                                                                                                     |                                 |
| <b>2 Additional D-Rings in Bogie Transition</b>                                                                                |                                 |
| <b>Total</b>                                                                                                                   |                                 |
| <b>Discount Type</b>                                                                                                           |                                 |
| <b>Discount Percent</b>                                                                                                        |                                 |
| <b>Discount Amount</b>                                                                                                         |                                 |
| <b>Net Total</b>                                                                                                               |                                 |
| <b>Grand Total</b> (Price for 2 units)                                                                                         |                                 |
| <b>Total Weight</b>                                                                                                            | <b>Est. Wt.: 23,198# +/- 3%</b> |

PO# 99658 HNW 99659