

99672 JMW 99674



Order Date: 2026-07-06
 Order Number: 40056 **REV. 1**
 Reference: 39761: Stock w/24.4
 Company: C KEAY INVESTMENTS / OCEAN TRAILER
 Jim Farrell

**Canadian Velocity 53' Tridem Air Slider
 (Model Code: HBVSF22TAS)**

Overall Length: 53 feet x 102 inches
Suspension Type: Sliding air tridem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 100,000 lbs distributed- GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch wood
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Side Rails: 6 inch structural channel @ 6.5 lbs/ft
Stake Pockets: 3/16 inch steel on 24 inch centers
Pipe Spools: Double between stake pockets
Rubrail: 3/8 inch x 2 1/2 inch steel
Main Beams: 130K load bearing flanges
Kingpin: 24 inches; 5/16" Plate
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: None standard
Number of Axles: 3 Intraax
Axle Position: 96 inch adjustable
Axle Spread: 60 inches, 60 inches -- Kingpin to C/L Rear Axle: 39 feet 4 3/4 inches in front position- 47 feet 4 3/4 inches in rear position
Axle Spindle: Parallel (Straight)
Dust Shields: Installed on all axles
Brakes: TSE Spring brakes, Haldex auto slacks
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Hub and Drums: 10-hole hub-piloted with outboard cast drums (Webb)
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 24.5 x 8.25 6 steel disc inside wheels - 6 aluminum LVL One Buffed outside with 6 Spacers
Tires: 11R 24.5 14PR OEM standard tires- quantity 12
Tire Brand: OEM standard
Tire Inflation System: None standard
Suspension Detail: Hendrickson AAZNT69K Intraax air ride slider with ride height limiters- 96 inch adjustable; (1) Removable slide position stop bar
Air Assist Slide Box Pins: Controls mounted inside box on front of slider box
Manual Dump Valve: Standard
Air Load Scale: Installed
Front Corners: Tapered
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Other Electrical Specifications: 3 4-way sockets with one hot/one ground pin for wide load and strobe light connections: 1 rear, 1 ea. side at rear
Paint: Black urethane with Velocity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed on rubrails
Bumper: Weld-on type - meets underride requirements
Mudflaps: 1 set OEM standard behind rear axle
Spare Tire Carrier: Spare tire carrier - bolted on curbside
Side Mounted Winches: 26 standard - without straps: 13 per side-three bar type
Special J Hooks: 26 total - 13 per side-opposite winches
Tarp Hooks: 2 foot centers on all sides when possible: undermount rs/cs: side mount front/back
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: Install registration holder - Tite Seal
Tool Box: None standard
Tow Hooks: 1 Installed on rear
VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges
Unit Numbers & Decals: Not installed
Stacking: Price includes Standard stacking of each trailer

Estimated Weight (lbs) (+/- 3%) 14,536